Project	IEEE 802.16 Broadband Wireless Access Working Group < <u>http://ieee802.org/16</u> >			
Title	FAST-FEEDBACK processing time correction			
Date Submitted	2004-11-02			
Source(s)	Intel.			
	Yuval Lomnitz Yuval.Lomnitz@intel.com			
	Yigal Eliaspur			
	Dov Andelman			
	Noam Kogan			
Re:	IEEE P802.16REVd/D5-2004			
Abstract	Correct definition for FAST-FEEDBACK processing time			
Purpose	Adopt changes			
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.			
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.			
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures http://ieee802.org/16/ipr/patents/policy.html , including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with recent to essential for compliance with both mendatory and optional participant of the			

FAST-FEEDBACK processing time correction

Yuval Lomnitz, Yigal Eliaspur Dov Andelman, Noam Kogan

1. Motivation

There is no good reason why processing time of FFB will be differ between FDD and TDD The response time should be proportional to the frame length only.

2. Changes summary

10.1 Global values

[Add the following entry in table 340]

System	Name	Time reference	Minimum value
BS,SS	FAST-FEEDBACK	The time allowed between the end	TDD: One Frame
	processing time	of the burst carrying the FAST-	duration FDD: 1/2
		FEEDBACK subheader and the	Frame duration
		start of the UL-subframe carrying	
		the FAST-FEEDBACK response.	