

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	SMC parameters	
Date Submitted	2005-03-16	
Source(s)	Giulio Cavalli Siemens	giulio.cavalli@siemens.com
	Joël Demarty SEQUANS Communications.	joel@sequans.com
Re:	IEEE P802.16REVd/D5-2004	
Abstract	Parameters for secondary management connection	
Purpose	Adopt changes.	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < http://ieee802.org/16/ipr/patents/policy.html >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < mailto:chair@wirelessman.org > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < http://ieee802.org/16/ipr/patents/notices >.	

SMC parameters

Giulio Cavalli (Siemens)

Joël Demarty (SEQUANS Communications)

1. Introduction

Secondary Management Connection (SMC) has no traffic parameters. So no peak rate and no traffic priority respect to other traffic connections are defined.

Currently this is not an issue for the other management connections (Basic and Primary management connections) since messages that belong to these management connection shall respect constraints, timers and roles mandated by the protocols.

Currently, since the scheduling algorithms are vendor specific, there is no control on the constraints about the SMC.

For example it can be possible that during a software download the SMC takes priority over all the data transport connections. Since an FTP session could require some seconds, it's possible that data traffic is blocked for a long time period.

The following proposal adds QoS parameter to the SCM within REG-RSP message used to create SCM during network entry phase.

2. Text changes

[Change page 14, Line 16, chapter 6.3.2.3.8 of P802.16-2004/Cor1-D1 as indicated]

Secondary Management CID (11.7.5)

Present only if the SS has indicated in the REG-REQ that it is a managed SS.

When the Secondary Management CID is present, the following uplink QoS parameters may be also included in the message:

Traffic priority (11.13.5)

Maximum sustained traffic rate (11.13.6)

Minimum reserved traffic rate (11.13.8)

Maximum latency (11.13.14)

[Insert page 136, Line 56, chapter 11.13.5 of P802.16-2004/Cor1-D1]

11.13.5 Traffic priority

Change the following table at page 699 of IEEE 802.16-2004

Type	Length	Value	Scope
------	--------	-------	-------

[145/146].6	1	0 to 7 — Higher numbers indicate higher priority Default 0	DSx-REQ DSx-RSP DSx-ACK REG-RSP
-------------	---	---	--

11.13.6 Maximum sustained traffic rate

Change the following table at page 699 of IEEE 802.16-2004

Type	Length	Value	Scope
[145/146].7	4	Rate (in bits per second)	DSx-REQ DSx-RSP DSx-ACK REG-RSP

11.13.8 Minimum reserved traffic rate

Change the following table at page 700 of IEEE 802.16-2004

Type	Length	Value	Scope
[145/146].9	4	Rate (in bits per second)	DSx-REQ DSx-RSP DSx-ACK REG-RSP

[Insert page 136, Line 60, chapter 11.13.14 of P802.16-2004/Cor1-D1]

11.13.14 Maximum latency

Change the following table at page 702 of IEEE 802.16-2004

Type	Length	Value	Scope
[145/146].14	4	Ms	DSx-REQ DSx-RSP DSx-ACK REG-RSP