

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	RS R amble Repetition Rate	
Date Submitted	2007-03-13	
Source(s)	Dorin Viorel, dviorel@fmci.fujitsu.com Voice: +1 403 207 6309;	
	Charlie Huo Voice: +1 403 207 6334; chuo@fmci.fujitsu.com	
	Fujitsu Microelectronics Canada Inc.	
		Voice: +44 20 86064523; mike.hart@uk.fujitsu.com
	Mike Hart	
	Fujitsu Laboratories Europe	michi@labs.fujitsu.com ; Voice : +81 468 39 5371
	Michiharu Nakamura	
	Fujitsu Laboratories Japan	
	Mark Naden , Israfil Bahceci , Hang Zhang , Peiying Zhu , Mo-Han Fong , Wen Tong , David Steer , Gamini Senarath , Derek Yu , G.Q. Wang Nortel	pyzhu@nortel.com ;
Re:	80216j-07_007r2 : "Call for Technical Comments and Contributions regarding IEEE Project 802.16j"	
Abstract	This document specifies the RS amble repetition rate.	
Purpose	Text proposal for 802.16j Baseline Document	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained	

in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.

Patent
Policy and
Procedures

The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures <<http://ieee802.org/16/ipr/patents/policy.html>>, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair <<mailto:chair@wirelessman.org>> as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site <<http://ieee802.org/16/ipr/patents/notices>>.

RS Amble Repetition Rate.

Dorin Viorel, Charlie Huo
Fujitsu Microelectronics Canada Inc.

Mike Hart
Fujitsu Laboratories Europe

[Michiharu Nakamura](#)
[Fujitsu Laboratories Japan](#)

[Mark Naden](#), [Israfil Bahceci](#), [Hang Zhang](#), [Peiyong Zhu](#), [Mo-Han Fong](#), [Wen Tong](#), [David Steer](#), [Gamini Senarath](#), [Derek Yu](#), [G.Q. Wang](#)
[Nortel](#)

1. Introduction

In order to provide proper time and frequency synchronization, and Cell ID information for the sub-ordinated Relay Stations attempting to enter the network through getting connected to a parent RS, a relay amble structure has to be defined. One of the parameters of this relay structure is its related repetition rate.

2. Details

The repetition rate of the relay amble has to comply with the following conditions:

- The intended amble position is in the last symbol of the DL sub-frame.
- The relay amble has to provide support for the time and frequency synchronization algorithms (implementation specific). The initial synchronization takes places on the access preamble while the RS' holding sync and AFC tracking logic rely on the repetition rate of the relay amble sequence.
- The functionality of the Common Sync symbol as defined by [2], Section #8.4.6.1.1.1 has to be preserved
- The BW throughput degradation due to relay amble repetition rate has to be minimized.

3. Conclusion

In order to comply with the above conditions, the relay amble shall be a repetitive structure, with a repetition rate of at least 1 out of 4 every frames. It is proposed that the text in the following section be included into the baseline document to specify this requirement.

4. Specific text changes

Add sub-clause #8.4.6.1.1.1 [Insert new subclause 8.4.6.1.1.3]

8.4.6.1.1.3+ Relay amble

The relay amble is a repetitive structure with a maximum repetition periodrate given by Equation xxx.

Max RelayAmbleRepetitionPeriodRate = 40 ms/4 frames

Equation xxx

References

1. IEEE 802.16-2004 “IEEE Standard for Local and Metropolitan Area Networks – Part 16”
2. IEEE 802.16e-2005