Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 Obtaining Sleep Mode Information in RS with distributed scheduling 2007-3-05	
Title		
Date Submitted		
Source(s)	Yuefeng Zhou; Mike Hart; Sunil Vadgama Fujitsu Laboratories of Europe Ltd	Voice: +44 (0) 20 8573 4444 FAX: +44 (0) 20 8606 4539
	Hayes Park Central, Hayes End Road, Hayes, Middlesex, UB4 8FE, UK	
	 Shiao-Li Tsao, Fang-Ching Ren, Wern-Ho Sheen, I-Kang Fu National Chiao Tung University (NCTU) /Industrial Technology Research Institute (ITRI), Taiwan No. 195, Sec. 4, Chung Hsing Rd., Chutung, Hsinchu, Taiwan 310, R.O.C. 	Voice: +886-3-5712121-54717 Fax: +886-3-5721490 E-mail: sltsao@cs.nctu.edu.tw;frank_ren@itri.org.tw
	Shulan Feng, Yanling Lu, Ting Li, Liangliang Zhang Hisilicon Technologies Harbour Building, No.8, Dongbeiwang West Road, HaiDian District, Beijing, China	Voice: 86-10-82829010 Fax: 86-10-82829075 mailto:luyanling@hisilicon.com
Re:	IEEE 802.16j-06/027: "Call for Technical Proposals regarding IEEE Project P802.16j"	
Abstract	In MR networks, RS could have more flexibility for scheduling, if it can obtain MS sleep mode information.	
Purpose	Discuss and adopt proposed text.	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	

The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures Patent <http://ieee802.org/16/ipr/patents/policy.html>, including the statement "IEEE standards may Policy and include the known use of patent(s), including patent applications, provided the IEEE receives Procedures assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft approved publication. publication will be for Please notify the Chair <mailto:chair@wirelessman.org> as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site <<u>http://ieee802.org/16/ipr/patents/notices</u>>.

Obtaining Sleep Mode Information in RS with Distributed Scheduling

This revision of contribution propose a harmonization text proposal on sleep mode.

1. Problem Statement

In MR networks, distributed scheduling RS shall allocate resources to this sleep-mode MS to properly perform the event-based actions. However, if the RS does not decode MOB_SLP-RSP messages, it may not allocate proper resources to MSs on time, thus the event-based actions may failed.

Moreover, if RS, in distributed case, can know that an MS has switched to sleep mode by decoding the MOB_SLP-RSP message, it shall avoid sending management message to this MS. Also, an RS, in distributed case, can cancel the bandwidth resources allocated to this MS during the sleep period, thus saving bandwidth.

In order to facilitate the centralized management of sleep mode in distributed MR networks, text is required to clarify how the RS and MR-BS shall synchronize the sleep-mode information between MR-BS and RS.

MR-BS can instruct the MS sleep mode by sending MOB_SLP-RSP, RNG-RSP, or DL sleep control extended subheader. If the RS could share the security key (HMAC, CMAC) with MR-BS, it can obtain the sleep mode information by decoding these received message (as shown in figure 1).




Fig. 1. RS decodes the MOB_SLP_RSP message for further scheduling

3. Specific Text Change

6.3.21 Sleep mode for mobility-support MS

[Insert a new subclause after 6.3.21.7] 6.3.21.7.x MS sleep mode support for distributed scheduling approach

In MR networks, the sleep mode shall be centrally controlled by MR-BS in the presence distributed scheduling.

In distributed case, RS may receive and decode the relevant sleep-mode messages, such as MOB_SLP-RSP, RNG-RSP, or DL sleep control extended subheader, sent by MR-BS to obtain sleep mode information, so as to be aware of MSs being in sleep state.