

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	Simultaneous Reception and Transmission Support	
Date Submitted	2007-04-06	
Source(s)	<p>Young-jae Kim, Kyu Ha Lee, Jae Hyung Eom, Changkyoon Kim Samsung Thales San 14, Nongseo-Dong, Giheung-Gu, Y ongin, Gyeonggi-Do, Korea 449-712</p> <p>Byung-Jae Kwak, Young-il Kim ETRI 161, Gajeong-Dong, Yuseong-Gu, Dae jeon, Korea 205-350</p> <p>Aik Chindapol Siemens Corporate Research 755 College Road East Princeton, NJ, USA</p> <p>Yousuf Saifullah Nokia 6000 Connection Drive, Irving, TX</p> <p>Jun Bae Ahn SOLiD Technologies 10th Fl., IT Venture Tower East Wing, 78 Garak-Dong, Songpa-Gu, Seoul, Ko rea 138-803</p> <p>Jai H. Eu Jcast Networks Korea, Inc. Anyang K-Center #1004 Kwanyang-D ong 1591-9, Dongan-Gu, Anyang-Si, G yeonggi-Do, Korea 431-815</p>	<p>Voice: +82-31-280-9975 Fax: +82-31-280-1562 youngjae2.kim@samsung.com kyuha.lee@samsung.com</p> <p>Voice: +82-42-860-6618 Fax: +82-42-861-1966 bjkwak@etri.re.kr yikim@etri.re.kr</p> <p>Voice: +1 609 734 3364 Fax: +1 609 734 6565 aik.chindapol@siemens.com</p> <p>Voice: +1 972 894 5000 Yousuf.Saifullah@nokia.com</p> <p>Voice: +82 2 2142 3861 Fax: +82 2 2142 3999 jbahn@st.co.kr</p> <p>Voice : +82 31 476 6989 Fax : +82 31 476 6930 jeu@jcastnet.com</p>
Re:	IEEE 802.16j-07/007r2: "Call for Technical Comments and Contributions regarding IEEE Project 802.16j"	
Abstract	The document contains technical proposals for IEEE P802.16j that provides TLV for simultaneous reception and transmission support.	
Purpose	Text proposal for 802.16j Baseline Document	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards	

publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.

Patent Policy and Procedures

The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures <<http://ieee802.org/16/ipr/patents/policy.html>>, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair <<mailto:chair@wirelessman.org>> as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site <<http://ieee802.org/16/ipr/patents/notices>>.

Simultaneous Reception and Transmission Support

Introduction

So far, RS' transmission of preamble and MAPs for MS of access link has been discussed. It is necessary to enhance coverage and improve performance. To do that, RS need to know preamble index and MAPs data. These can be received thru payload. And RS also needs some reference for synchronization, thus R-amble has been introduced. All these were based on an assumption that RS cannot transmit frame start preamble and MAPs while receiving.

But if RS can transmit frame start preamble and MAPs while receiving those, we can have some benefits from it. Then, RS can have three different methods for relaying.

- 1) Transmitting while receiving: RS transmits its own frame start preamble and MAPs to MS while receiving frame start preamble from BS for synchronization.
 - This method has a benefit that R-amble can be removed for non-transparent RS..
- 2) Direct relaying : RS just amplifies and forwards received preamble and MAPs to MS.
 - This method is useful for virtual grouping and centralized scheduling.

In considering simultaneous transmission and reception, generally RS would consist of two sets of PA & LNA, which are major components, for each relay link from/to BS and access link from/to MS. But if the common hardware architecture is used, a RS could have only one PA, because only one way transmission exists at a time.

Proposed text changes

[+++++++ start text proposal ++++++](#)

[\[Insert the followings at section 11.8.3.7.xx\]](#)

[This filed indicates the availability of RS support for simultaneous Tx/Rx.](#)

<u>Type</u>	<u>Length</u>	<u>Value</u>	<u>Scope</u>
<u>TBA</u>	<u>1</u>	0: Switching Tx/Rx support 1: Simultaneous but separate Tx/Rx support 2: Direct relaying support 3-255: Reserved	SBC-REQ SBC-RSP

[+++++++ end of text proposal ++++++](#)