Signaling for Efficient Routing

Document Number:

IEEE S802.16j-06/159

Date Submitted:

15 November 2006

Source:

K. Baum, M. Cudak, P. Sartori, E. Visotsky

Motorola Labs

1301 E. Algonquin Rd, Schaumburg, IL USA

email:philippe.sartori@motorola.com

email: shyamal.ramachandran@motorola.com

S. Ramachandran

Motorola

1064 Greenwood Blvd. Suite 400, Lake Mary, FL 32746 USA

Venue: IEEE 802.16 Session 46Base

Purpose: Presentation Material

Notice:

This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.

Release:

The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.

IEEE 802.16 Patent Policy:


The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures http://ieee802.org/16/ipr/patents/policy.html, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair mailto:chair@wirelessman.org as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site http://ieee802.org/16/ipr/patents/notices.

Signaling for Efficient Routing

Reference Contribution: C802.16j-06/159 Motorola

Overview

- Due to backward compatibility, MS will choose to attach to BS or RS based on legacy methods (e.g., preamble RSSI)
 - These methods lead to suboptimal route selection
 - No account for the channel capacity used for the BS<->RS link
 - Optimal route on UL may be different than DL



- We propose messages to allow information collection and corrective action, such as:
 - 1. Establish the link using the legacy method
 - 2. Acquire/report any missing C_{xy} link quality information to the BS
 - 3. Let the BS figure out the 'right' path
 - 4. Move the SS to the right network entity on DL and/or UL

Note that existing MOB_* messages can be leveraged to assist with this process

Requires a few new messages on the BS<->RS link

Example

SS linked to RS, but should be linked to BS

