Management CID allocation

IEEE 802.16 Presentation Submission Template (Rev. 8.3)

Document Number:

IEEE S802.16j-06/281

Date Submitted:

2006-11-14

Source:

Voice: Kenji Saito, Takashi Inoue +81 46 847 6347 KDDI R&D Laboratories Inc. Fax: +81 46 847 0947 E-mail: saito@kddilabs.jp

Hikarino-oka 7-1, Yokosuka, Kanagawa 239-0847

Japan

Hyunjeong Kang, Sungjin Lee, HyoungKyu Lim Voice: +82 31 279 5084 Samsung Electronics Fax: +82 31 279 5130

> E-mail: hyunjeong.kang@samsung.com

Venue:

IEEE 802.16 Session #46, Dallas, TX, USA

Base Document:

IEEE C802.16j-06/281

Purpose:

Discuss and adapt proposed text and message format.

Notice:

This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.

Release:

The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.

IEEE 802.16 Patent Policy:

The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures http://ieee802.org/16/ipr/patents/policy.html, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair <mailto:chair@wirelessman.org> as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site http://ieee802.org/16/ipr/patents/notices>.

Management CID allocation

Main features

✓ Management CID shall be divided into two range

Tab]	٦	2	15		α		١~
Tab	ıe	.)4	+.)	-	LΙ	ш	18

CID	Value	Description				
Basic CID		Basic CID range for MS.				
	$0x0001 \sim \underline{x}$	The same value is assigned to both the DL and UL				
		connection.				
		Basic CID range for RS.				
	$\underline{x+1} \sim m$	The same value is assigned to both the DL and UL				
		connection.				
Primary management CID		Primary management CID range for MS.				
	$m+1 \sim \underline{m+x}$	The same value is assigned to both the DL and UL				
		connection.				
		Primary management CID range for RS.				
	$\underline{m+(x+1)} \sim 2m$	The same value is assigned to both the DL and UL				
		connection.				

- ✓BS can assign a part of management CID range to RS
- ✓RS also can assign these CID to its subordinate node

Management CID allocation

