

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	System parameters for point to point links for use in Coexistence Simulations (revision 1)	
Date Submitted	2001-09-13	
Source(s)	Philip Whitehead Radiant Networks Plc The Mansion, Chesterford Park Little Chesterford, Essex CB10 1 XL UK	Voice: +44 1799 533600 Fax: +44 1799 533601 mailto:pw@radiantnetworks.co.uk
Re:	Parameters necessary for preparation of coexistence simulations (revised during session #15)	
Abstract	This document provides tables of parameters and parameter values revised during session#15, for point to point systems operating in the 23.5-43.5 GHz frequency range. These parameters are relevant to interference calculations and simulation work.	
Purpose	For use in simulation work.	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	<p>The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures (Version 1.0) <http://ieee802.org/16/ipr/patents/policy.html>, including the statement "IEEE standards may include the known use of patent(s), including patent applications, if there is technical justification in the opinion of the standards-developing committee and provided the IEEE receives assurance from the patent holder that it will license applicants under reasonable terms and conditions for the purpose of implementing the standard."</p> <p>Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair <mailto:r.b.marks@ieee.org> as early as possible, in written or electronic form, of any patents (granted or under application) that may cover technology that is under consideration by or has been approved by IEEE 802.16. The Chair will disclose this notification via the IEEE 802.16 web site <http://ieee802.org/16/ipr/patents/notices>.</p>	

System parameters for point to point links for use in Coexistence Simulations (revision 1)

Introduction

This document provides tables of parameters and parameter values updated during session#15, for point to point systems operating in the 23.5-43.5 GHz frequency range. These parameters are relevant to interference calculations and simulation work, in scenarios.

Table 1: “multi – link point to point systems”

Characteristic (point to point systems)	Examples
Layout of system(s) including diagrams	Quasi – random layout of links Consider multiple star/hub configurations
Link lengths	50 to 5000m at 25 GHz 50 to 3000m at 38 GHz
Density of terminal stations	Up to 5/ sq km
Distribution of terminal stations in relation to link length	Uniform (all link lengths have same probability)
Frequency of operation (for each variant to be studied)	Circa 25GHz, circa 38GHz
Duplex method	FDD
Access method	N/A
Receiver parameters	
Channel bandwidth	12.5, 14, 25, 28, 50, 56 MHz Start analysis by assuming 25/28 MHz
filter response	Root Nyquist, 25% roll-off
noise floor	TBA (6dB noise figure at 25 GHz, 9dB at 38 GHz)
acceptable level for co-channel interference	I/N = -6dB (aggregate of all interferers)
Transmitter parameters	
Channel bandwidth	12.5, 14, 25, 28, 50, 56 MHz Start by assuming 25/28 MHz
emission mask	Depends on modulation – to be specified Assume ETSI or FCC (further discussion required)
maximum power	1W
Typical power	To meet link budget
use of ATPC, steps and range	Uplink and downlink, 2dB steps, 40dB range
Tx-Rx parameters	NFD (net filter discrimination; call for contributions needed)
Antenna characteristics (station at point of connection to backhaul or core network)	Composite RPE 1 ft antenna as per contribution from RW – note 1 Gain 40-42dBi tbc
Antenna characteristics (subscriber station)	Composite RPE 1 ft antenna as per contribution from RW - note 1 Gain 40-42dBi tbc
Antenna characteristics (repeater station)	Same as other antennas
Backhaul links	In – band, separate assignments

Table 2: Discrete point to point links

(where assignments for point to point systems are made in the same frequency bands as FWA systems)

Characteristic (point to point systems)	Examples
Layout of system(s) including diagrams	Individual, planned link, coordinated by regulatory body
Link lengths	50 to 5000m at 25 GHz 50 to 3000m at 38 GHz
Density of terminal stations	N/A
Distribution of terminal stations in relation to link length	N/A
Frequency of operation (for each variant to be studied)	25GHz, 38GHz
Duplex method	FDD
Access method	N/A
Receiver parameters	
Channel bandwidth	12.5, 14, 25, 28, 50, 56 MHz Start analysis by assuming 25/28 MHz MHz
filter response	Root Nyquist, 25% roll-off
noise floor	(6dB noise figure at 25 GHz, 9dB at 38 GHz)
acceptable level for co-channel interference	I/N = -6dB (aggregate of all interferers)
Transmitter parameters	
Channel bandwidth	12.5, 14, 25, 28, 50, 56 MHz Start by assuming 25/28 MHz MHz
emission mask	Depends on modulation – to be specified Assume ETSI or FCC (further discussion required)
maximum power	1W
Typical power	To achieve link budget
use of ATPC, steps and range	Uplink and downlink, 2dB steps, 40dB range
Tx-Rx parameters	NFD (net filter discrimination). Use ETSI values if no other data available (call for contributions needed)
Antenna characteristics (station at point of connection to backhaul or core network)	Composite RPE 1ft and 2ft antenna(s) as per contribution from RW – note 1 Gain = 40-42dBi tbc
Antenna characteristics (subscriber station)	Composite RPE 1ft and 2ft antenna(s) as per contribution from RW – note 1 Gain = 40-42 dBi tbc
Antenna characteristics (repeater station)	N/A
Backhaul links	In – band, separate assignments

Note 1: RW (Bob Whiting) has produced a contribution containing a review of practical antenna RPEs. Composite (worst case) RPEs have been produced. [add document reference]