

Project	IEEE 802.16 Broadband Wireless Access Working Group <http://ieee802.org/16>
Title	Corrections for the definition of repetition code
Date Submitted	2004-06-25
Source(s)	<p>Intel:</p> <p>Yuval Lomnitz, yuval@envara.com</p> <p>Yigal Eliaspur, yigal.eliaspur@intel.com</p> <p>Voice: +972-547-884877</p> <p>Dov Andelman, dov.andelman@intel.com</p>
Re:	IEEE P802.16e/D3-2004
Abstract	Proposing corrections for the definition of the repetition code in 802.16REVd
Purpose	Correct errors in definition of repetition code.
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.
Patent Policy and Procedures	<p>The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures <http://ieee802.org/16/ipr/patents/policy.html>, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair <mailto:chair@wirelessman.org> as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site <http://ieee802.org/16/ipr/patents/notices>.</p>

Corrections for the definition of repetition code

Yuval Lomnitz

1. Motivation

There are several problems in the definition of the repetition code (8.4.9):

- (1) Repetition code is defined only for repetition of 2, however, used for repetition of 4 and 6 - needs definition.
- (2) Definition of repetition code is in frequency domain only, so repetition of 6 is inefficient (e.g. for MAP this repetition would leave empty slots).
- (3) Repetition code as defined in the standard, cannot be applied in the UL, because of the uni-dimensional allocation. The beginning and end of the UL allocation may have edges which are 1 subchannel wide, so the number of subchannels doesn't divide by the repetition level.

2. Details

We propose to re-define the repetition code:

- (1) Define repetitions of up to 6 by repetition patterns of 1x2, 2x1 for repetition 2, 4x1, 2x2, 1x4 for repetition 4, and 1x6, 2x3, 3x2 and 6x1 for repetition 6.
- (2) Provide separate definition for repetition code in the UL.

Repetition code should supply frequency diversity and therefore use the maximal number of subchannels, while in the same time, allow narrow allocations where this is desired.

3. Changes summary

TBD