

Project	<b>IEEE 802.16 Broadband Wireless Access Working Group</b> < <a href="http://ieee802.org/16">http://ieee802.org/16</a> >	
Title	<b>Scan Report Operation</b>	
Date Submitted	<b>[2004-05-07]</b>	
Source(s)	Hyunjeong Kang Sohyun Kim Jungje Son Changhoi Koo  Samsung Elec. 416, Maetan-3dong, Youngtong-gu Suwon-si, Gyeonggi-do Korea	Voice: +82-31-279-5091 Fax:+82-31-279-5130  <a href="mailto:hyunjeong.kang@samsung.com">hyunjeong.kang@samsung.com</a> <a href="mailto:binde.kim@samsung.com">binde.kim@samsung.com</a> <a href="mailto:jungje.son@samsung.com">jungje.son@samsung.com</a> <a href="mailto:chkoo@samsung.com">chkoo@samsung.com</a>
Re:	This contribution is for call for contribution IEEE802.16e/D2-2004	
Abstract	This contribution proposes the reporting operation of scan result for the handover process.	
Purpose	Propose scan result reporting operation for the IEEE802.16e Handoff Ad hoc group	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < <a href="http://ieee802.org/16/ipr/patents/policy.html">http://ieee802.org/16/ipr/patents/policy.html</a> >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < <a href="mailto:chair@wirelessman.org">mailto:chair@wirelessman.org</a> > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < <a href="http://ieee802.org/16/ipr/patents/notices">http://ieee802.org/16/ipr/patents/notices</a> >.	

# Scan Report Operation

Hyunjeong Kang, Sohyun Kim, Jungje Son, Changhoi Koo

Samsung Electronics

## Introduction

Except CINR field in MOB-MSSHO-REQ, there is no mechanism that informs the MSS's scanning operation results. With using only handover mechanism in current draft document, the Serving BS cannot know the exact status of neighbor BSs such as signal power for the MSS and recommend the best neighbor BS in case of BS initiated handover.

Therefore it is necessary to provide mechanisms to report neighbor BSs' CINR status, and if the Serving BS knows the received CINR of neighbor BS by transmitted by the MSS, the BS can find the proper Target BS for BS initiated handover.

For the purpose, we propose the mechanism for reporting the scanning results to the Serving BS.

## Proposed Mechanism

For efficient handover and MSS operation, we propose the following reporting mechanisms for the BS initiated handover case.

- Periodic report
- Event triggering report

### 1) Periodic report

With this periodic report mechanism, a MSS scans CINR of neighbor BSs and periodically reports the scanning results to its Serving BS based on the MAHO report period defined in MOB-NBR-ADV. The Serving BS, through this report mechanism, can know the status of neighbor BSs and indicate the suitable neighbor BS to the MSS when the Serving BS initiates handover operation.

Figure 1 shows the example of scan report message using periodic reporting mechanism.




Figure 1 Example of scan report message using periodic report mechanism

2) Event triggering report

In this event triggering report mechanism, a MSS reports the scanning results when the specific event is triggered. The event can be something that the rank of received CINR of neighbor BSs is changed while the CINR of the Serving BS still remains the highest value. Similar to the periodic report mechanism, with this scanning report, the Serving BS can know the ranking changes of received CINR of neighbor BSs.

The figure 2 shows the example of scan report message using event triggering mechanism.




Figure 2 Example of scan report message using event triggering mechanism

Therefore we propose the remedies as followings:

- Add “the operation that the MSS reports scanning results to the Serving BS by sending MOB-SCAN-REPORT message” to section 6.3.20.1.2, page 41
- Add a new section “Scanning Result Report (MOB-SCAN-REPORT) message” after section 6.3.2.3.52 page 22
  - MOB-SCAN-REPORT message

## Proposed Text Changes

We propose the following remedies in IEEE P802.16e/D2 to provide the scan result reporting mechanism.

[Insert this section after the section 6.3.2.3.52 in page 22]

### 6.3.2.3.xx Scanning Result Report (MOB-SCAN-REPORT) message

The MSS transmits a MOB-SCAN-REPORT message to report the result of the scan operation to its Serving BS. The message includes the scanning result same as CINR of neighbor BS.

Table XXX – MOB-SCAN-REPORT Message Format

<u>Syntax</u>	<u>Size</u>	<u>Notes</u>
<u>MOB-SCAN-REPORT_Message_Format(){</u>		
<u>Management Message Type = ??</u>	<u>8bits</u>	
<u>Report Mode</u>	<u>2bits</u>	<u>00: Periodic</u> <u>01: Event-triggering</u> <u>10-11: reserved</u>
<u>N_NEIGHBORS</u>	<u>8bits</u>	
<u>For(j=0; j&lt;N_NEIGHBORS; j++){</u>		
<u>Neighbor BS-ID</u>	<u>48bits</u>	
<u>BS CINR mean</u>	<u>8bits</u>	
<u>}</u>		
<u>}</u>		

A MSS shall generate MOB-SCAN-REPORT messages in the format shown in Table XXX. The following parameters shall be included in the MOB-SCAN-REPORT message,

#### Report Mode

This parameter indicates the report mode:

Periodic – the MSS reports the scan result to the Serving BS periodically

Event-triggering – the MSS reports the scan result in the case that specific event has been triggered

For each neighbor BS, the following parameter shall be included:

#### Neighbor BS-ID

Same as the Base Station ID parameter in the DL-MAP message of neighbor BS.

#### BS CINR mean

This parameter indicates the signal to noise and interference ratio measured by the MSS from the particular BS. The value shall be interpreted as an unsigned byte with units of 0.25dB.

2004-05-07

IEEEC802.16e\_04/54

[Add the followings after line 61 page 41]

After scanning for neighbor BSs using the allocated scanning interval, the MSS shall report the scanning result to the Serving BS through MOB-SCAN-REPORT message periodically based on MAHO report period in MOB-NBR-ADV. Addition to the periodic report, the MSS may report the scanning result in case of a specific event such that the rank of the received CINR of neighbor BSs is changed. This scanning report may assist Serving BS to recommend suitable BSs for BS initiated handover operation.