

Proposal for 802.16m PHY Requirements

IEEE 802.16 Presentation Submission Template (*Rev. 8.3*)

Document Number:

IEEE C802.16m-07/013

Date Submitted:

2007-02-23

Source:

In-Kyeong Choi, Dong-Seung Kwon

ETRI

Voice:+82 42 860 5242

E-mail: ikchoi@etri.re.kr

Venue:

IEEE 802.16 Session #48, Orlando, USA

Base Document:

None

Purpose:

To propose 802.16m PHY requirements

Notice:

This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.

Release:

The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.

IEEE 802.16 Patent Policy:

The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures <<http://ieee802.org/16/ipr/patents/policy.html>>, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair <<mailto:chair@wirelessman.org>> as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site <<http://ieee802.org/16/ipr/patents/notices>>.

Proposal for 802.16m PHY Requirements

In-Kyeong Choi
Dong-Seung Kwon
ETRI

Outline

- Definitions
- Functional Requirements
- Performance Requirements

Definitions (1)

- Frequency Reuse Factor
 - The total number of cells (sectors) in a given multi-cell (sectorized) structure divided by the number of cells (sectors) reusing the same frequency
 - $FRF=1$ means that all cells (sectors) in a multi-cell (sectorized) structure reuse the same frequency

Definitions (2)

- Spectral Efficiency (bps/Hz/cell(sector))
 - Effective channel bandwidth
 - The effective bandwidth used in UL and DL
 - Example:
 - Maximum spectral efficiency
 - The ratio of the maximum throughput (ruling out all PHY/MAC overhead) supported by the BS in a single cell (sector) divided by the effective channel bandwidth
 - Average spectral efficiency
 - The ratio of the average throughput (ruling out all PHY/MAC overhead) supported by a BS in multicell environment divided by the effective channel bandwidth

Definitions (3)

- User Throughput:
 - Average throughput per user in a unit MHz
 - Average throughput in a unit MHz by allowing 5% loss of cell boundary users

Functional Requirements

- Peak Data Rate
 - 4x4 MIMO in 100MHz for 1Gpbs/Hz for stationary users

Mobility	Mod. order	MIMO	Coding rate	BW	Coverage
Very High	QPSK	Diversity	Low	Small	Macro
Medium High	16QAM	Diversity+SM	Low	Medium	Macro
Stationary	64QAM	SM	High	Large	Pico

	Mobile users			Stationary users	
Channel BW (MHz)	20	40	40	100	100
MxN MIMO	4x2	4x2	4x4	2x2	4x4
Occupied BW	0.9	0.9	0.9	0.9	0.9
Spatial Multiplexing	2	2	4	2	4
Modulation order	2	4	4	6	6
Coding rate	1/2	1/2	1/2	3/4	3/4
w/o Overhead	0.7	0.7	0.7	0.7	0.7
Peak data rate (Mbps)	25.2	100.8	201.6	567.0	1134.0

- Overhead in PHY layer includes Guard band, DL MAP, Preamble, UL control information, TTG/RTG, cyclic prefix, and Pilots.
- Overhead is to be less than 30% of radio resource

Performance Requirements (1)

- The maximum spectral efficiency based on the moving speed shall be at least the followings:

	DL (based on 2x2)				UL (based on 1x2)			
Mobility (km/h)	3	60	120	300	3	60	120	300
Maximum Spectral efficiency (bps/Hz/sector)	5	3.5	2	0.4	2.5	1.75	1	0.2

- The system average spectral efficiency shall be at least the followings:

	DL (based on 2x2)			UL (based on 1x2)		
Mobility (km/h)	3	120	>120	3	120	>120
Average Spectral efficiency (bps/Hz/sector)	2	1.5	Graceful degradation	1	0.75	Graceful degradation

Performance Requirements (2)

- Coverage

- Example of typical cell type parameters

Cell type	Radio environment	Cell radius (km)	Mobile speed (km/h)
Macro	Rural	5 ~ 35	0 ~ 500
	Suburban	~ 5	0 ~ 120
Micro	Urban	~ 1	0 ~ 100
Hbt-spot	Business area	~ 0.1	0 ~ 10
Personal	Wireless personal area	~ 0.01	0 ~ 10