

# Comments on Outer Permutation Size

Document Number: IEEE C802.16m-08/511

Date Submitted: 2008-05-12

## Source:

Sophie Vrzcic, Mo-Han Fong, Dongsheng Yu, Robert Novak, Jun Yuan, Sang-Youb Kim, Kathiravetpillai Sivanesan

Nortel Networks

E-mail: [svrzcic@nortel.com](mailto:svrzcic@nortel.com), [mhfong@nortel.com](mailto:mhfong@nortel.com)

\*<http://standards.ieee.org/faqs/affiliationFAQ.html>>

Re: IEEE 802.16m-08/016 – Call for Comments on C802.16mDL\_PHY-08/046 “802.16m DL PHY Structure Baseline Content Suitable for use in the 802.16m SDD”

Purpose: Adopt the proposal into the IEEE 802.16m System Description Document

## Notice:

*This document does not represent the agreed views of the IEEE 802.16 Working Group or any of its subgroups. It represents only the views of the participants listed in the “Source(s)” field above. It is offered as a basis for discussion. It is not binding on the contributor(s), who reserve(s) the right to add, amend or withdraw material contained herein.*

## Release:

The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE’s name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE’s sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.

## Patent Policy:

The contributor is familiar with the IEEE-SA Patent Policy and Procedures:

<http://standards.ieee.org/guides/bylaws/sect6-7.html#6> and <http://standards.ieee.org/guides/opman/sect6.html#6.3>.

Further information is located at <http://standards.ieee.org/board/pat/pat-material.html> and <http://standards.ieee.org/board/pat> >.

# Channelization Procedure


- In C802.16mDL\_PHY-08/046 and as described in C80216m-08/009r5, the proposed text indicates that the outer permutation should be performed in the units of PRUs
- Outer permutation spreads the PRUs of each frequency partition evenly across the band as shown in the figure below. The localized resource units (LLRU) will be evenly spread over the entire band even for the case where there is no distributed resource with the frequency partition.
- For example, if there are 4 FFR zones then each FFR zone contains PRUs that are spaced by 4 PRUs.
- For frequency selective scheduling, the mobiles report multiple C/I. In order to reduce MS complexity, the mobiles should be calculating a C/I based on a sub-band rather than per PRU.
- With this outer permutation, when there are 4 FFR zones the number of PRUs in a sub-band is one. This results in only one assigned LLRU per user per sub-band, which increases the signaling overhead.



Sub-band  
Used for  
For C/I  
Reporting

# Proposed Channelization Procedure

- The outer permutation should be performed in the units of N PRUs
- In this case, there will be N contiguous LLRUs and the contiguous blocks of LLRUs from each FFR zone are evenly spread over the entire band.
- When there are 4 FFR zones there are multiple PRUs in a sub-band.
- Each assigned user can be assigned multiple PRUs, which will reduce the signaling overhead.
- Even when a FFR zone is divided into LLRU and DRU, for example, 2/3 of resource is allocated for LLRU and 1/3 of resource is allocated for DRU, there will be 2 contiguous LLRU is one sub-band. At the same time, each DRU has 4-order diversity which already saturates the diversity gain.



Sub-band  
Used for  
For C/I  
Reporting

# Proposed Text Changes in C802.16mDL\_PHY-08/046

- Section 11.5.2.2 Downlink Subcarrier to Resource Unit Mapping