

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >
Title	Multi-carrier Support in Relay
Date Submitted	2009-03-10
Source(s)	Jerry Sydir, Kamran Etemad Intel Corporation jerry.sydir@intel.com * http://standards.ieee.org/faqs/affiliationFAQ.html >
Re:	SDD Change Request
Abstract	This contribution specifies multi-carrier support in the RS.
Purpose	For consideration and adoption into the 16m SDD document.
Notice	<i>This document does not represent the agreed views of the IEEE 802.16 Working Group or any of its subgroups.</i> It represents only the views of the participants listed in the "Source(s)" field above. It is offered as a basis for discussion. It is not binding on the contributor(s), who reserve(s) the right to add, amend or withdraw material contained herein.
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.
Patent Policy	The contributor is familiar with the IEEE-SA Patent Policy and Procedures: < http://standards.ieee.org/guides/bylaws/sect6-7.html#6 > and < http://standards.ieee.org/guides/opman/sect6.html#6.3 >. Further information is located at < http://standards.ieee.org/board/pat/pat-material.html > and < http://standards.ieee.org/board/pat >.

Multi-carrier Support in Relay

*Jerry Sydir, Kamran Etemad
Intel Corporation*

Multi-carrier Operation in Deployments with Relay

In a multi-carrier deployment of 802.16m based system an ABS may operate in multicarrier mode where more than one RF carrier is utilized by a single instantiation of the MAC supporting AMSs also capable of operating on more than one RF carrier.

The RF carriers may all be fully configured or some may be partially configured. Section 19 defines “scenario 1” as the case where all RF carriers are fully configured and “scenario 2” as the case in which some of the RF carriers are partially configured.

In such multi-carrier system there is need for SDD to clarify how ARS’s may be used and support the multi-carrier operation.

We believe that ARSs should be used only to relay fully configured carriers as partially configured carriers are mainly targeted for high power broadcast only carriers which in most cases are synchronized to provide macro-diversity. When ARSs are deployed in a multi-carrier deployment individual ARSs can support multiple RF carriers or only a single RF carrier. An example of multi-carrier operation using a multi-carrier RS is shown in Figure 1. A more interesting and useful usage of ARS is when single carrier ARS’s are used to provide multi-carrier connections., Examples of this usage are conceptually shown in Figure 2. It should be noted that in Figure 2 RF carrier 1 and RF carrier 2 are assumed to be different RF carriers with different center frequencies and that multi-carrier operation across single-carrier ARSs does not involve cooperative relay transmissions or the use of virtual MIMO techniques.




Figure 1 Multi-carrier operation across multi-carrier ARS




Figure 2 Multi-carrier operation using single-carrier ARSs

When ARSs operate in a multi-carrier deployment, data is transmitted on a given carrier for the entire path between the ABS and AMS. For example, an MPDU transmitted from the ABS to the ARS on RF carrier 1 is transmitted to the AMS on RF carrier 1.

When a multihop topology is used (distance between ABS and AMSs is 3 hops or more) all of the ARSs in a path handle the same RF carriers. That is, if the first hop ARS is a multi-carrier ARS configured to operate on RF carriers 1 and 2, the second hop ARSs attached to it are also multi-carrier ARSs configured to operate on RF carriers 1 and 2. Similarly if the first hop ARS is a single carrier ARS configured to operate on RF carrier 1, the subordinate ARSs attached to this ARS are also single-carrier ARSs configured to operate on RF carrier 1.

In order to avoid too much complexity and dependency of technical developments of multi-carrier and relay concepts some design restrictions may need to be enforced to facilitate practical solutions. For example for all multi-carrier ABS-AMS connections involving a ARS:

- Only Fully Configured Carrier are used
- Only MAC PDU segmentation is used
- Control information pertaining to the secondary carrier is transmitted on the secondary.

Text Proposal

[Insert the following text into section 15 of the SDD]

15.4.x Relay Support of Multi-Carrier Operation

In general all operational principals for multi-carrier operation apply to a system involving ARS's unless explicitly stated otherwise.

When ARSs are deployed in a deployment where the multi-carrier feature is used individual ARSs can support multiple RF carriers or only a single RF carrier. ARSs are used only to relay fully configured carriers. When multi-carrier service is provided to an AMS, all of the carriers

over which the service is provided to the AMS, are transmitted by the same station (ABR or ARS).