

Project	IEEE 802.16 Broadband Wireless Access Working Group < <a href="http://ieee802.org/16">http://ieee802.org/16</a> >
Title	Cleanup texts for Superframe Header (16.3.6.2.1)
Date Submitted	2010-03-05
Source(s)	Mihyun Lee, Hyunkyun Yu, Jaeweon Cho, Hokyu Choi <a href="mailto:mihyun.mac.lee@samsung.com">mihyun.mac.lee@samsung.com</a>  Samsung Electronics Co., Ltd.
Re:	IEEE 802.16-10/0011, "IEEE 802.16 Working Group Letter Ballot#31" Target topic: "IEEE P802.16m/D4, section 16.3.6.2.1".
Abstract	The contribution provides the clean up text for SFH
Purpose	To be discussed and adopted by TGM for the 802.16m/D5
Notice	<i>This document does not represent the agreed views of the IEEE 802.16 Working Group or any of its subgroups. It represents only the views of the participants listed in the "Source(s)" field above. It is offered as a basis for discussion. It is not binding on the contributor(s), who reserve(s) the right to add, amend or withdraw material contained herein.</i>
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.
Patent Policy	The contributor is familiar with the IEEE-SA Patent Policy and Procedures: < <a href="http://standards.ieee.org/guides/bylaws/sect6-7.html#6">http://standards.ieee.org/guides/bylaws/sect6-7.html#6</a> > and < <a href="http://standards.ieee.org/guides/opman/sect6.html#6.3">http://standards.ieee.org/guides/opman/sect6.html#6.3</a> >. Further information is located at < <a href="http://standards.ieee.org/board/pat/pat-material.html">http://standards.ieee.org/board/pat/pat-material.html</a> > and < <a href="http://standards.ieee.org/board/pat">http://standards.ieee.org/board/pat</a> >.

# Cleanup texts for Superframe Header (16.3.6.2.1)

Mihyun Lee, Hyunkyu Yu, Jaeweon Cho, Hokyu Choi

Samsung Electronics Co., Ltd.

## 1. Introduction

This contribution provides the cleanup text to clarify the following issues:

- Remedy #1: To describe how to determine the DLRU size of P-SFH and S-SFH, respectively
- Remedy #2: The usage of the remaining DLRU not occupied by SFH in first subframe of superframe is already described in line 25, page 433. Remove the redundant text in line 52, page 434.

~~Removed text~~

Added text

## 2. References

[1] IEEE P802.16m/D4, “P802.16m DRAFT Amendment to IEEE Standard for Local and metropolitan area networks Part 16: Air Interface for Broadband Wireless Access Systems”, 2010-02-03

## 3. Proposed Text Changes

[Remedy#1: Adopt the following modification text in line 40 on page 433, Table 806, section 16.3.6.2.1]

Table 806 - Parameters and values for resource allocation of SFH

Parameters	Description	Value
$N_{SFH}$	The number of distributed LRUs which are occupied by SFH. Note that $N_{SFH} = N_{P-SFH} + N_{S-SFH}$	$N_{P-SFH} + N_{S-SFH}$
$N_{P-SFH}$	The number of distributed LRUs which are occupied by P-SFH	<del>Fixed (value is TBD)</del> <u><math>\text{Ceil}(N_{Rep, P-SFH} \times \text{Size}_{P-SFH} / 40)</math></u>
$N_{S-SFH}$	The number of distributed LRUs which are occupied by S-SFH	<del>Variable according to the type of S-SFH SP</del> <u><math>\text{Ceil}(N_{Rep, S-SFH} \times \text{Size}_{S-SFH} / 40)</math></u>

Where:

$N_{Rep, P-SFH}$  is the number of repetitions for P-SFH transmission.

$\text{Size}_{P-SFH}$  is the sum of the bit size of P-SFH IE and 5 bit CRC. This value is 26.

---

$N_{Rep, S-SFH}$  is the number of repetitions for S-SFH transmission and carried in P-SFH IE.

$Size_{S-SFH}$  is the sum of information bit of S-SFH IE and 16 bit CRC.  $Size_{S-SFH}$  is different according to the scheduled S-SFH SPx IE. When any S-SFH SPx IE is not scheduled at the superframe,  $Size_{S-SFH}$  is 0.

The factor of 1/40 is calculated by considering the code rate of 1/4 and QPSK across 80 data subcarriers

***[Remedy#2: Delete the text in line 52 on page 434, section 16.3.6.2.1]***

~~When there is no S-SFH SP in the SFH, the SFH resources are used for transmitting other control information or A-MAP.~~