

33.2.4.9 Type 3 and Type 4 variables

CC_DET_SEQ

A constant indicating the sequence in which the PSE performs connection check and detection.

Values:

0: Connection Check is followed by staggered detection for a single-signature PD and parallel detection for a dual-signature PD.

1: Detection on a pairset is followed by connection check and then detection on the other pair-set for a single-signature PD and parallel **or staggered (starting with first pairset)** detection for a dual-signature PD.

2: Connection check and detection on both pairsets are performed within a single Tdet window.

3: Connection check is followed by staggered detection.

pinpong_en

A variable indicating if the PSE uses the method consisting in alternating between Alt A and Alt B during initial detection phase until there is a valid detection.

TRUE: alt_pri alternates between a and b until a first valid detection.

FALSE: alt_pri does not change and is user defined.

semi_pwr_en

A variable indicating if, in the case of SS PD, the PSE uses the method consisting in turning off only the pairset on which a short-circuit, overload or out of range V_{PSE} is detected.

TRUE: Only the pairset with the fault condition is turned off.

FALSE: both pairsets are turned off if there is a fault on one pairset.

option_vport_lim_pri

This optional variable indicates if V_{PSE} on the primary alternative is out of the operating range during normal operating state.

Values:

FALSE: V_{PSE} on the primary alternative is within the V_{Port_PSE-2P} operating range as defined in Table 33–17.

TRUE: V_{PSE} on the primary alternative is outside of the V_{Port_PSE-2P} operating range as defined in Table 33–17.

option_vport_lim_sec

This optional variable indicates if V_{PSE} on the secondary alternative is out of the operating range during normal operating state.

Values:

FALSE: V_{PSE} on the secondary alternative is within the V_{Port_PSE-2P} operating range as defined in Table 33–17.

TRUE: V_{PSE} on the secondary alternative is outside of the V_{Port_PSE-2P} operating range as defined in Table 33–17.

class_4PID_mult_events_sec

A variable indicating if the PSE uses the method consisting in generating 3 class events on the secondary alternate to determine if the dual signature PD is a candidate for 4-pair power.

TRUE: the PSE generates at least 3 class events to determine if the PD is a candidate for 4-pair power.

FALSE: the PSE does not need to generate 3 class events to determine if the PD is a candidate for 4-pair power.

mps_sum

A variable indicating if the PSE uses the method consisting in measuring the sum of $I_{\text{PORT-2P}}$ of both pairsets to determine if the DC MPS component is present.

TRUE: MPS presence determination is based on the sum of current of both pairsets

FALSE: MPS presence determination is based on $I_{\text{PORT-2P}}$ of the pairset having the highest current.

highest_2p

A variable indicating which of the 2 pairsets has the highest current.

pri: the primary alternative has the highest current.

sec: the secondary alternative has the highest current.