



IEEE802.3 4P Task Force
Ripple and Noise requirements for Type 3 and 4
systems

Rev 002

November 2014
San Antonio, TX

Supporters:

Christian Beia
Kousalya Balasubramanian / Cisco
Rick Frosch / PHIHONG
Fred Schindler / Seen Simply

Yair Darshan
Microsemi
ydarshan@microsemi.com

Objectives

- To derive the requirements for differential noise and common mode noise for Type 3 and 4 PSEs and PDs
- Proposing a base line text for Tables 33-11 and 33-18

Background

- DM and CM noise for PSEs and PDs are defined over 2 pairs in Table 33-11 and 33-18 for frequencies up to 1MHz.
- For Frequencies >1MHz it is defined by 33.4.4 and 33.4.6.
- Data integrity is affected by DM and CM noise.
 - Data integrity is not function of PD power level if DM and CM limits are met.

Type 3 Ripple and Noise requirements

- Type 3 has ripple and noise sources at the PI for each pair set.
- Each 2P noise source affects the 2P data on that pairs.
- As a result IEEE802.3-2012 ripple and noise requirements are the same per each pair set for Type 3 and 4 systems.
- For 10GBaseT applications, the ripple and noise requirements up to 1MHz is the same.
- For CM and DM noise above 1MHz:
 - Amplitude as specified by 33.4.4 and 33.4.6.
 - Proposal to diff noise to be reduced to 1.6mVpp
 - Frequency range to extent to 500MHz
- Same applies for type 4.

Baseline text proposal for Table 33-11

Item	Parameter	Symbol	Unit	Min	Max	PSE Type	Additional information
3	Power feeding ripple and noise						
	$f < 500$ Hz		V_{pp}		0.500	1, 2,3,4	See 33.2.7.3.
	500 Hz to 150 kHz				0.200		
	150 kHz to 500 kHz				0.150		
	500 kHz to 1 MHz				0.100		

33.2.7.3 Power feeding ripple and noise

The specification for power feeding ripple and noise in Table 33–11 shall be met for common-mode and/or pair-to-pair noise values for power outputs from $(I_{Hold\ max} \times V_{Port_PSE\ min})$ to $P_{Type\ min}$ for PSEs at static operating V_{Port_PSE} . The limits are meant to preserve data integrity. To meet EMI standards, lower values may be needed. For higher frequencies, see 33.4.4, ~~and~~ 33.4.5 and 33.4.6.

Baseline text proposal for Table 33-11 cont

33.4.4 Common-mode output voltage

The magnitude of the common-mode AC output voltage measured according to Figure 33–21 and Figure 33–22 at the transmit PI while transmitting data and with power applied, E_{cm_out} , shall not exceed 50 mV peak when operating at 10 Mb/s, and 50 mV peak-to-peak when operating at 100 Mb/s or greater. The frequency of the measurement shall be from 1 MHz to 100 MHz.
For 10GBaseT systems, the frequency of measurements shall be from 1 MHz to 500 MHz.

33.4.6 Differential noise voltage

For 10/100/1000Mb/s: The coupled noise, E_{d_out} in Figure 33–22, from a PSE or PD to the differential transmit and receive pairs shall not exceed 10 mV peak-to-peak when measured from 1 MHz to 100 MHz under the conditions specified in 33.4.4, item 1) and item 2).

For 10GBase-T: The coupled noise, E_{d_out} in Figure 33–22, from a PSE or PD to the differential transmit and receive pairs shall not exceed 1.6 mV peak-to-peak when measured from 1 MHz to 500 MHz under the conditions specified in 33.4.4, item 1) and item 2).

Baseline text proposal for Table 33-18

- Change Table 33-18 item 10, PD Type column from:
1,2
To
1,2,3,4

Summary

- Noise and Ripple requirements for Type 3 and 4 system are identical to Type 2 systems.
- It is proposed to update IEEE802.3-2012 as shown in the baseline proposal.