


# PoDL - 1000Base-T1 Liason Report

Dave Dwelley  
Linear Technology

# Contribution to the EMC Ad Hoc

- PoDL will add noise to the 1000Base-T1 link
  - Noise originates from the PoDL power supply circuitry
- Most of the noise power will be at low frequencies relative to 1000Base-T1 data frequencies
- Additional filtering will be performed by the coupling network that attaches the PoDL subsystem to the wire

# Simplified PoDL Coupling Network



# Proposed PoDL Noise Limits

- Taken directly from Clause 33 (PoE):


**Table 33–11—PSE output PI electrical requirements for all PD classes, unless otherwise specified**

Item	Parameter	Symbol	Unit	Min	Max	PSE Type	Additional information
1	Output voltage in the POWER_ON state	$V_{Port\_PSE}$	V	44.0	57.0	1	See 33.2.7.1.
				50.0	57.0	2	
2	Voltage transient below $V_{Port\_PSE\ min}$	$K_{Tran\ lo}$	%		7.6	2	See 33.2.7.2.
3	Power feeding ripple and noise:						
	$f < 500\ Hz$				0.500	1, 2	See 33.2.7.3.
	500 Hz to 150 kHz		$V_{pp}$		0.200		
	150 kHz to 500 kHz				0.150		
	500 kHz to 1 MHz				0.100		
4	Continuous output current capability in POWER_ON state	$I_{Con}$		A	$\frac{P_{Class}}{V_{Port\_PSE}}$		1, 2

# Notes for 33-11

- 33.2.7.3 Power feeding ripple and noise
  - The specification for power feeding ripple and noise in Table 33–11 shall be met for common-mode and/or pair-to-pair noise values for power outputs from (IHold max × VPort\_PSE min) to PType min for PSEs at static operating VPort\_PSE. The limits are meant to preserve data integrity. To meet EMI standards, lower values may be needed. For higher frequencies, see 33.4.4 and 33.4.5.
- 33.4.4, 33.4.5 are not directly applicable to PoDL

# Noise Limit Curve



# Notes

- Noise is specified as  $V_{pp}$  in PoE/PoDL
  - Source impedance is very low at low frequencies so spec is voltage, not power
  - Crest factor is fairly low since power supply output is typically a filtered pulse train
- Noise is specified at the output of the PoDL subsystem before the coupling network
- Clause 33 PoE spec effectively stops at 1MHz
  - Reasonable to assume that noise will continue with similar amplitude to ~10MHz
  - Coupling network should provide significant attenuation at 10MHz and beyond

# Direct Vbat Connection

- Previous slides assume PoDL power is provided by a dedicated voltage regulator in the PSE
- Some systems may connect directly to Vbat without a regulator at the PSE end
  - Low frequency noise (below 150kHz) may be substantially higher in this case
  - The PoDL group will attempt to gather better data on this case for the next ad hoc meeting

# Next Steps: Noise

- Calculate required coupling network cutoff frequencies to ensure data integrity
- If inductor values are reasonable, no further work is required
- If inductor values are unreasonable with the proposed noise limits, please propose new limits to 802.3bu
- 802.3bu will evaluate feasibility of lower noise limits as required