

Project	IEEE 802.16 Broadband Wireless Access Working Group < <a href="http://ieee802.org/16">http://ieee802.org/16</a> >	
Title	Proposals for Potential Interference Detection	
Date Submitted	2006-11-10	
Source(s)	Shulan Feng Hisilicon Tech. Co., LTD Bld.17, No.8, Dongbeiwang West Road, Hai-Dian District, Beijing, P. R. China	Voice: +86-10-82829151 Fax: e-mail to : <a href="mailto:fengsl@hisilicon.com">fengsl@hisilicon.com</a>
Re:	IEEE 802.16 Working Group Letter Ballot #24, on P802.16h/D1	
Abstract	In this contribution, some proposals which has discussed in the interference management ad-hoc group are introduced for TG consideration.	
Purpose	Introduce proposals proposed in interference management ad hoc for further consideration.	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < <a href="http://ieee802.org/16/ipr/patents/policy.html">http://ieee802.org/16/ipr/patents/policy.html</a> >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < <a href="mailto:chair@wirelessman.org">mailto:chair@wirelessman.org</a> > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard	

---

being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site <<http://ieee802.org/16/ipr/patents/notices>>.

---

## Proposals for Potential Interference Detection

*Shulan Feng*

*Hisilicon Technologies Co., LTD*

### Introduction

As the action item of meeting #46 in Mont Tremblant, an ad-hoc group discussing the interference management in network entry and operating stage is created. One of the big issues to be resolved in this ad-hoc is the blind area problem [2]. In this contribution, I'll introduce the proposals we have discussed in the ad-hoc group [3] and ask for task group consideration.

### Proposals discussed in ad-hoc

First, we all agree to solve the blind area problem, potential interference should be detected and solved first. John proposes to use DL CMI channel for detecting interference and UL CMI channel for reporting interference. But I think because SS is not installed with GPS, so it is impossible for SS to find CMI slot and decode CMI message before it enters network (I think it is impossible that SS without any pre-information can get DL synchronization and decode burst correctly in one frame). And another fault about this scheme is that SS can't report anything before performing ranging with the target BS. The third problem is this scheme can only be used in a common PHY profile. If these problems can be resolved, then this is the best way for the problem. I and John can't get consistence and we need more PHY experts.

In the ad-hoc group, we all also agree that a periodic quiet slot should be reserved for SS in blind area if the scheme mentioned in the first paragraph is impossible. There are three proposals.

One of the proposals is using CX\_CC channel, including CMI slots for SS in blind area. But CX\_CC channel is too spare and short for initialization of SS.

Another way is reserving a zone during master sub-frame for SS in blind area. This zone should be large enough for SS reporting channel measurement and random enough to avoiding conflict. So this scheme is inefficient.

The third way is letting BS work on more than one channel. For example, during common sub-frame and master sub-frame, BS works on a channel, and during slave sub-frame, BS works on another channel. Because the slave sub-frame is periodic and long enough, everything can be done in this period, including SS registration and data transmission. The benefit of this scheme is the probability of blind area is decreased since each BS works independently on more than one channel. Another benefit of this scheme is the capacity of system is improved since BS works at all time. The main disadvantage is that there is not suitable channel exist. John has doubted its complexity, but I don't think so. I give a detailed description in another contribution [4].

### Conclusion

These are all proposals regarding to this problem. It is the duty of TG who decides which scheme to be adopted. There are three schemes available now:

- ✧ Use DL CMI/CSI channel for interference detection and UL CMI channel for interference report.
  - More PHY experts needed for feasibility
- ✧ Reserve a zone during master sub-frame
- ✧ System works on more than one channel.

Or we continue the ad-hoc until better solution is found.

## Reference

- [1] IEEE 802.16h-D1: Air Interface for Fixed Broadband Wireless Access Systems: Amendment for Improved Coexistence Mechanisms for License-Exempt Operation
- [2] C80216h-06\_094, Dynamic Interference Maintenance in Coexistence Community
- [3] <http://dot16.org/forum/index.php?topic=55.0>
- [4] C80216h-06\_103, A method which can improve capacity in WirelessMAN-CX