Project	IEEE 802.16 Broadband Wireless Access Working Group <a href="http://ieee802.org/16">http://ieee802.org/16</a> >
Title	Corrections for EVM definitions in OFDMA PHY
Date Submitted	2004-11-01
Source(s)	Yuval Lomnitz Yuval.Lomnitz@intel.com
	Elad Dayan
	Intel.
Re:	IEEE P802.16REVd/D5-2004
Abstract	Corrections for EVM definitions in OFDMA PHY
Purpose	Adopt changes
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures <a href="http://ieee802.org/16/ipr/patents/policy.html">http://ieee802.org/16/ipr/patents/policy.html</a> , including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair <a href="mailto:chair@wirelessman.org">mailto:chair@wirelessman.org</a> as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site <a href="http://ieee802.org/16/ipr/patents/notices">http://ieee802.org/16/ipr/patents/notices</a> .

# Corrections for EVM definitions in OFDMA PHY

Yuval Lomnitz Elad Dayan

## 1. Motivation

EVM (constellation error) definition seems to be borrowed from OFDM and not relevant for OFDMA this contribution proposes corrections for the definition.

## 2. Details

#### 2.1. Problems

The following problems exist in the current definition in 8.4.12.3 (Transmitter constellation error and test method):

- (1) No definition of EVM on empty subcarriers this is important since no transmitter can avoid interference to unused subcarriers, and this interference affects other users in the UL.
- (2) Frequency estimation is mentioned in EVM definition but not relevant per burst.
- (3) Regarding test of frequency offset: It should be specified if EVM includes degradation due to frequency offset (currently it probably doesn't since 2% carrier spacing yields ICI of about 28dB, and requirement for 64QAM is 31.4dB). The treatment of frequency offset is different for BS and SS, since SS is expected to lock to BS frequency (therefore BS is not required to estimate SS frequency and lock on it).
- (4) Need to define reference channel & phase estimation mechanism (esp for tiles)
- (5) No definition of specific subchannel / averaging over subchannels for the EVM test

#### 2.2. Discussion

- Equation (145) should be extended to include EVM measurement on unmodulated subcarriers.
- Regarding treatment of frequency and time offsets there are two approaches:
  - 1. If these errors are part of the EVM definition, then the test equipment should transmit a preamble to synchronize the SS, and measure EVM without correcting these errors. This approach is more comprehensive however complicates the test equipment and test definition. In addition since frequency offset of 2% carrier spacing is equivalent to EVM of 28.8dB, the EVM levels need to be changed.
  - 2. If these errors are not considered part of EVM, then the test equipment needs to estimate these parameters and correct them. In this case although the estimation may be complex, the test equipment is simpler (only needs to receive), and frequency locking should be tested separately.

• In this contribution we selected the 2<sup>nd</sup> approach, since it matches the spirit of the original definition, does not require change in the defined EVM levels, and the test equipment is simpler.

# 3. Changes summary

8.4.12.3 Transmitter constellation error and test method [modify the text starting at p.629 line 6 as follows]

### EVM measurement for BS:

The sampled signal shall be processed in a manner similar to an actual receiver, according to the following

steps, or an equivalent procedure [B29]. The test will be performed at PUSC when only 1/3 of the subcarriers are used:

- a) Start of frame shall be detected.
- a) Locate the Preamble.
- b) Transition from short sequences to channel estimation sequences shall be detected, and fine timing (with one sample resolution) shall be established.
- b) Perform timing and frequency estimation.
- c) Coarse and fine frequency offsets shall be estimated.
- d) The packet shall be de-rotated according to estimated timing and frequency offset.
- e) The complex channel response coefficients shall be estimated for each of the subcarriers from the Preamble.
- f) For each of the data OFDMA symbols: transform the symbol into subcarrier received values, estimate

the phase from the pilot subcarriers, de-rotate the subcarrier values according to estimated phase, and divide each subcarrier value with a complex estimated channel response coefficient.

- g) For each data-carrying subcarrier, find the closest constellation point and compute the Euclidean distance from it.
- h) Compute the RMS average of all errors in a packet. It is given by:

$$Error_{RMS} = \frac{1}{N_f} \sum_{1}^{N_f} \frac{\sum_{j=1}^{L_p} \sum_{k=0}^{Nused-1} \left[ \left( I(i,j,k) - I_0(i,j,k) \right)^2 + \left( Q(i,j,k) - Q_0(i,j,k) \right)^2 \right]}{\sum_{j=1}^{L_p} \sum_{k=0}^{Nused-1} \left[ I_0(i,j,k)^2 + Q_0(i,j,k)^2 \right]}$$
(145)

where:

 $L_P$  is the length of the packet;

 $N_f$  is the number of frames for the measurement;

 $(I_0(i,j,k), Q_0(i,j,k))$  - denotes the ideal symbol point of the *i*-th frame, *j*-th OFDMA symbol of the frame, *k*-th subcarrier of the OFDMA symbol in the complex plane. For the DC subcarrier and unmodulated (empty) subcarriers this value shall be 0;

(I(i,j,k), Q(i,j,k)) denotes the observed point of the *i*-th frame, *j*-th OFDMA symbol of the frame, *k*-th subcarrier, of the OFDMA symbol in the complex plane;

*Nused* denotes the maximal number of used subcarriers as defined in the symbol structure (see 8.4.6), including subcarriers that are not transmitted.

## [Add the following text at the end of the section]

### EVM measurement for SS:

- a. The SS under test shall transmit on part of the UL subchannels. Recommended value is 1/4 of the UL subchannels.
- b. The tester will locate a complete UL subframe.
- c. Estimate the averaged timing and frequency offset.
- d. The packet shall be de-rotated according to estimated timing and frequency offset.
- e. Estimate the average channel according to the pilots (use linear interpolation between pilots).
- f. For each symbol, transform the symbol into subcarrier received values, estimate the phase by the pilots, for symbols w/o pilots use linear interpolation to estimate the phase.
- g. Each symbol, de-rotate the subcarrier values according to estimated phase, and divide each subcarrier value with a complex estimated channel response coefficient.
- h. For each data-carrying subcarrier, find the closest constellation point and compute the Euclidean distance from it.
- i. Compute the RMS average of all errors in a packet. It is given by equation (145).