

Project	<b>IEEE 802.16 Broadband Wireless Access Working Group</b> < <a href="http://ieee802.org/16">http://ieee802.org/16</a> >	
Title	<b>BS ID Clarification</b>	
Date Submitted	<b>2005-01-13</b>	
Source(s)	Yerang Hur, Bong Ho Kim, Jungnam Yun, Jihoon Yoon, Jaehyeong Kim	Voice: 408-986-1140 Fax: 408-986-1145 <a href="mailto:{yehur,bhkim,jnyun,jihoon,jaekim}@posdata-usa.com">[mailto: {yehur,bhkim,jnyun,jihoon,jaekim}@posdata-usa.com]</a>
	POSDATA Co., Ltd.	
Re:	Corrigendum to IEEE Std 802.16-2004	
Abstract	This clarifies the usage of BS ID.	
Purpose	Review and adoption of the proposed text change into Corrigendum to IEEE Std 802.16-2004	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < <a href="http://ieee802.org/16/ipr/patents/policy.html">http://ieee802.org/16/ipr/patents/policy.html</a> >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < <a href="mailto:chair@wirelessman.org">mailto:chair@wirelessman.org</a> > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < <a href="http://ieee802.org/16/ipr/patents/notices">http://ieee802.org/16/ipr/patents/notices</a> >.	

## BS ID Clarification

*Yerang Hur, Bong Ho Kim, Jungnam Yun, Jihoon Yoon, Jaehyeong Kim*  
*POSDATA Co., Ltd.*

### 1. Problem Statements

There is ambiguity in P802.16-REVd/D5 regarding the usage of BS ID. Since one base station could have as many different BS IDs as the number of sectors within a cell, the usage of BS ID needs to be clarified in the sense that how to identify base station and its sectors from one BS ID.

For example, this statement assumes that a single base station composes a cell with multiple sectors.

- Line 17~19, Page 31, Section 6.1:

The IEEE Std 802.16 wireless link operates with a central base station and a sectorized antenna which is capable of handling multiple independent sectors simultaneously.

The following statement indicates different BS IDs are used for identifying a sector within a multi-sector cell.

- Line 18~19, Page 552, Section 8.4.5.6.1:

Sector ID

This field holds the least significant 8 bits of the 48-bit Base Station ID.

### 2. Proposed Text Changes

[Modify Line 17~19, Page 31, Section 6.1 as follows:]

The IEEE Std 802.16 wireless link operates with a central base station ~~and a sectorized antenna which is capable of handling multiple independent sectors simultaneously~~ with single or multiple sectors. Each sector is identified with the 8 least significant bits of 48bit BS ID and the central base station is identified with the 40 most significant bits of the BS ID.