

Project	IEEE 802.16 Broadband Wireless Access Working Group < <a href="http://ieee802.org/16">http://ieee802.org/16</a> >	
Title	Automatic PSC Reactivation Procedure	
Date Submitted	09-22-2006	
Source(s)	Floyd Simpson, Stephen Wang, Mark Cudak  Motorola, Inc. 8000 W. Sunrise Blvd Plantation, FL 33322, USA	Voice: +1-954-723-5269 Fax : +1-954-723-3391 mailto: <a href="mailto:floyd.simpson@motorola.com">floyd.simpson@motorola.com</a>
Re:	IEEE Maintenance Project	
Abstract	<p>This contribution solves a problem created, but not adequately addressed, by the IEEE 802.16e specification. According to the current spec, a PSC may be automatically deactivated by MPDU or TRF-IND if so configured with the Traffic-Triggered-Wakening-Flag. This method provides an effective way for BS and MS to exchange non-real-time traffic (e.g. FTP, HTTP, e-mail, etc.) that is bursty in nature. However under the current spec, MS and BS must reactivate PSC via a series of message exchanges, which takes at least 8 frames to complete under the best case scenario. Such lengthy reactivation is costly to a MS as far as duty cycle is concerned.</p>	
Purpose	Adopt proposed changes	
Notice	<p>This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.</p>	
Release	<p>The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.</p>	
Patent Policy and Procedures	<p>The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures &lt;<a href="http://ieee802.org/16/ipr/patents/policy.html">http://ieee802.org/16/ipr/patents/policy.html</a>&gt;, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair &lt;<a href="mailto:chair@wirelessman.org">mailto:chair@wirelessman.org</a>&gt; as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site &lt;<a href="http://ieee802.org/16/ipr/patents/notices">http://ieee802.org/16/ipr/patents/notices</a>&gt;.</p>	

# Automatic PSC Reactivation Procedure

*Floyd Simpson, Stephen Wang*  
*Motorola*

## Motivation

This contribution solves a problem inherent to, but not adequately addressed by the IEEE 802.16e specification. The spec defines Power Saving Class of Type I for connections of BE and NRT-VR type. When the Traffic Triggered Wakening flag is set, power saving classes of type I may be automatically deactivated by reception of MPDU or TRF-IND or transmission of BW Request. This mechanism is well suited for the exchange of non-real-time traffic (e.g. HTTP, FTP, e-mail, etc.) that is bursty in nature.

However, under the current spec, BS and MS must complete a series of signaling exchanges to reactivate a power saving class. Taking power saving class activation using Bandwidth Request with UL Sleep Control Header/DL Sleep Control Extended Subheader as example, MS and BS must complete the following signaling exchange:

Under the best case scenario (e.g. no retransmission), it would take at least 8 frames to reactivate a power saving class. After taking into consideration of HARQ retries, the time required for PSC reactivation could be stretched to 100+ ms.

The lengthy procedure must be repeated each time a bursty traffic exchange is completed. It adds a significant overhead to both BS and MS and results in higher power consumption on the MS. More importantly, it prevents MS from using sleep intervals that is short than the time needed to a complete PSC reactivation.

Therefore, there is a need to reduce power saving class reactivation overhead through simplified signaling.

## Suggested Remedy:

For a PSC that is deactivated by traffic triggered waking flag, BS automatically includes DL Sleep Control Extended Subheader whenever it intends to end a bursty (BE or NRT-VR) traffic exchange with the MS. It encompasses following steps:

1. Each time when the Power Saving Class is deactivated by MPDU or TRF-IND or UL BW Request, the BS will automatically insert a DL Sleep Control Extended Subheader into a DL MPDU whenever it wants to end traffic exchange for connection of the PSC.
2. The Power Saving Class is reactivated from the next frame immediately after the frame in which DL Sleep Control Extended Subheader was transmitted.

## Formal Change Request

In page 41, change as follows:

### **6.3.2.2.7.2 DL Sleep control extended subheader**

The DL Sleep control extended subheader is sent by the BS to activate/deactivate certain Power Saving Class. The requested operation is effective from the next frame after the one where the message was transmitted.

The format of DL Sleep control extended subheader is as described in Table 13e. BS may transmit this message to reactivate the Power Saving Class after the BS determines the end of data transmission.

: