

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	ertPS resumption with single ertPS codeword on CQICH	
Date Submitted	2008-03-19	
Source(s)	Yeongmoon Son, Geunhwi Lim, Brian Shim Samsung Electronics	Voice: +82-31-279-5845 E-mail: ym1004.son@samsung.com
	Vladimir Yanover Alvarion	E-mail: vladimir.yanover@alvarion.com
	Erik Colban NextWave	E-mail: ecolban@nextwave.com
		*< http://standards.ieee.org/faqs/affiliationFAQ.html >
Re:	LB26b	
Abstract	This contribution proposes the scheme to resume multiple ertPS connections with single ertPS codeword on CQICH.	
Purpose	Accept the proposed specification changes on IEEE P802.16Rev2/D3.	
Notice	<i>This document does not represent the agreed views of the IEEE 802.16 Working Group or any of its subgroups. It represents only the views of the participants listed in the "Source(s)" field above. It is offered as a basis for discussion. It is not binding on the contributor(s), who reserve(s) the right to add, amend or withdraw material contained herein.</i>	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy	The contributor is familiar with the IEEE-SA Patent Policy and Procedures: < http://standards.ieee.org/guides/bylaws/sect6-7.html#6 > and < http://standards.ieee.org/guides/opman/sect6.html#6.3 >. Further information is located at < http://standards.ieee.org/board/pat/pat-material.html > and < http://standards.ieee.org/board/pat >.	

ertPS resumption with single ertPS codeword on CQICH

Yeongmoon Son*, Geunhwi Lim*, Brian Shim*, and Vladimir Yanover**, Erik Colban***
Samsung Electronics*, Alvarion, NextWave*****

Problem description

There is a CQICH codeword for ertPS resumption in Table 381 on page 777.

Table 381—Encoding of payload bits for MIMO mode feedback with enhanced fast-feedback channel

Value (binary)	Description
101000	STTD and PUSC/FUSC permutation
101001	STTD and adjacent-subcarrier permutation
101010	SM and PUSC/FUSC permutation
101011	SM and adjacent-subcarrier permutation
101100	Hybrid and PUSC/FUSC permutation
101101	Hybrid and adjacent-subcarrier permutation
101110–110110	Interpretation according to Table 382, Table 383 or Table 384, depending on if antenna grouping, antenna selection or a reduced precoding matrix codebook is used.
110111	Closed-loop precoding with 1 stream.
111000	Closed-loop precoding with 2 streams.
111001	Closed-loop precoding with 3 streams.
111010	Closed-loop precoding with 4 streams.
111011	Extended rtPS bandwidth request (see 8.4.5.4.10.14)
111100	Indication Flag Feedback (see 8.4.5.4.10.12)

However an MS may have multiple ertPS connections(e.g. for Voice and Video) and some ertPS connections have been stopped by transmission of BR header with BR=0 from the MS. In that case, when a BS receives the ertPS codeword(i.e. 111011) on CQICH from the MS, the BS cannot know which ertPS connection the MS wants to resume. Moreover, MS cannot resume more than a ertPS connections at the same time (e.g. ertPS for voice and ertPS for video).

Proposed Changes

1. When a BS receives the ertPS codeword on CQICH from an MS, the BS shall allocate the MS UL burst corresponding to the largest ‘Maximum Sustained Traffic Rate’ among ertPS connections in order to avoid insufficient BW for anonymous ertPS connection. BS can know the resumed ertPS connection by referring to CID of MAC PDU on the UL burst from MS. Afterward, BS or MS can increase/decrease proper BW for ertPS connection.

[Modify the section 8.4.5.4.10.14 on page 783, line 35]

8.4.5.4.10.14 Extended rtPS BR

~~In the case of~~ If an MS has Extended rtPS connections~~service~~, the MS may inform the serving BS of the existence of pending ertPS

~~data request bandwidth allocation, which is defined as the Maximum Sustained Traffic Rate in service flow encodings.~~ The codeword 0b111011 is used for that purpose. If the BS receives the codeword (i.e. 111011) on CQICH from the MS, the BS shall allocate for the MS an UL burst corresponding to the largest Maximum Sustained Traffic Rate of the MS's stopped ertPS UL service flows. The BS shall identify the ertPS service flow(s) to resume through data received on this allocation by referring to the CID included in the MAC header or the ertPS resumption bitmap extended subheader (refer to 6.3.2.2.7.9) included in the MAC PDU, and shall schedule UL allocations based on the QoS requirements of the indentified ertPS service flows.

2. MS may want to resume more than one ertPS connection at the same time.

[Add the following new section at the end of the section 6.3.2.2.7.8 on page 78, line 26]

6.3.2.2.7.9 ertPS resumption bitmap extended subheader

An MS may have multiple ertPS service flows that have been stopped by the MS sending BR headers with BR = 0. When the MS has more than one ertPS service flow to resume at the same time, the MS may include the following extended subheader in a MAC PDU to request the serving BS to resume scheduling of the identified ertPS service flows. When the BS receives this extended subheader, the BS shall allocate a UL burst for each UL ertPS service flow identified by the extended subheader.

Table XX- UL ertPS resumption bitmap extended subheader format

<u>Name</u>	<u>Size (bit)</u>	<u>Description</u>
<u>UL ertPS resumption bitmap</u>	<u>8</u>	<u>One bit is assigned to each UL ertPS service flow in descending order of their SFID (i.e. bit #7 is mapped to the UL ertPS service flow with the highest SFID, bit #6 is mapped to the UL ertPS service flow with the second highest SF, etc.).</u> <u>1: Request for resumption of the corresponding ertPS service flow</u> <u>0: No Request for resumption of the corresponding ertPS service flow</u>

References

[IEEE802.16-Rev2/D3] IEEE Computer Society and IEEE Microwave Theory and Techniques Society, "DRAFT Standard for Local and Metropolitan Area Networks Part 16: Air Interface for Broadband Wireless Access Systems", P802.16Rev2/D3 (February 2008). Revision of IEEE Std 802.16-2004 and consolidates material from IEEE Std 802.16e-2005, IEEE Std 802.16-2004/Cor1-2005, IEEE Std 802.16f-2005 and IEEE Std802.16g-2007.