

Project	<b>IEEE 802.16 Broadband Wireless Access Working Group</b> < <a href="http://ieee802.org/16">http://ieee802.org/16</a> >	
Title	<b>Improvements to the Uplink Channel Sounding Signaling for OFDMA</b>	
Date Submitted	<b>2004-11-18</b>	
Source(s)	Frederick W. Vook Xiangyang (Jeff) Zhuang Kevin L. Baum Timothy A. Thomas Philippe Sartori  Motorola Labs 1301 E. Algonquin Road Schaumburg, IL 60196  Zion Hadad Runcom	Voice: +1-847-576-7939 <a href="mailto:Fred.Vook@motorola.com">Fred.Vook@motorola.com</a>
Re:	IEEE P802.16-REVe/D5-2004	
Abstract	Modifications to Uplink Channel Sounding methodology to optionally include DL channel coefficients.	
Purpose	Adoption of proposed changes into P802.16e	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < <a href="http://ieee802.org/16/ipr/patents/policy.html">http://ieee802.org/16/ipr/patents/policy.html</a> >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < <a href="mailto:chair@wirelessman.org">mailto:chair@wirelessman.org</a> > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < <a href="http://ieee802.org/16/ipr/patents/notices">http://ieee802.org/16/ipr/patents/notices</a> >.	

# Improvements to the Uplink Channel Sounding Signaling for OFDMA

Frederick W. Vook, Xiangyang (Jeff) Zhuang, Kevin L. Baum, Timothy A. Thomas, Philippe Sartori

Motorola Labs, Schaumburg, IL, USA

## 1 Introduction

This contribution provides a modification to the Uplink channel sounding methodology in Section 8.4.6.2.7 of IEEE 802.16e to include the optional direct transmission of DL channel coefficients [1][2] in addition to the sounding waveform. The modification extends the UL channel sounding signaling to enable closed-loop transmission in FDD systems and TDD systems in which BS array transceiver calibration is not implemented. The modification consists of an additional bit in the UL\_Sounding\_Command\_IE() for the purpose of indicating whether or not channel coefficients are to be transmitted along with the sounding waveform in the sounding zone. When this functionality for the direct transmission of channel coefficients is used, the sounding waveform specified by the Sounding Command enables the BS to estimate the UL channel, which the BS then uses to estimate the DL channel coefficients being sent by the MSS in the subsequent symbol interval(s). These estimated DL channel coefficients can then be used by the BS to perform closed-loop transmit precoding.

## 2 Specific Text Changes

----- Beginning of Text Changes -----

[ In Section 8.4.6.2.7, modify Table 311 as follows: (modifications in RED) ]

Table ??: UL\_Sounding\_Command\_IE()

Syntax	Size	Notes
UL_Sounding_Command_IE(){		
<b>Extended UIUC</b>	4 bits	0x09
Length	4 bits	Variable
Sounding_Type	1 bit	0 = Type A 1 = Type B
Send Sounding Report Flag	1 bit	
If (Sounding_Type == 0) {		
<b>Include Channel Coefficients</b>	1 bit	<b>0 = Do not include coefficients</b> <b>1 = Include channel coefficients</b> <b>(See Section 8.4.6.2.7.3)</b>
<b>If Include Channel Coefficients=1 {</b>		
<b>Feedback type</b>	1	<b>1=feedback channel coefficients, 0=feedback</b>

		received pilot coefficients
}		
Num_Sounding_symbols	3 bits	Total number of sounding symbols being allocated in <b>this Sounding Zone Command</b> , from 1 (“000”) to $2^3=8$ (“111”)
Separability Type	1 bit	0: occupy all subcarriers in the assigned bands; 1: occupy decimated subcarriers
if (Separability type==0) {		(using cyclic shift separability)
Max Cyclic Shift Index P	2 bits	00: P=4; 01: P=8; 10: P=16, 11: P=32
} Else {		(using decimation separability)
Decimation Value D	3 bits	Sound every $D^{\text{th}}$ subcarrier within the sounding allocation. Decimation value D is 2 to the power of (2 plus this value), hence 4,8,... up to maximum of 64.
Decimation offset randomization	1 bit	0= no randomization of decimation offset 1= decimation offset pseudo-randomly determined
}		
For (i=0;i<Num_Sounding_symbols;i++){		
Sounding symbol index	3 bits	Symbol index within the Sounding Zone, from 1 (bits “000”) to $2^3=8$ (bits “111”)
Number of CIDs	4 bits	Number of CIDs sharing this sounding allocation
For (j = 0; j<Num. of CIDs; j++) {		
Shorted basic CID	12 bits	12 LS bits of the MSS basic CID value
Starting Frequency Band	7 bits	Out of 96 bands at most (FFT size dependent)
Number of frequency bands	7 bits	Contiguous bands used for sounding
Power Assignment Method	2 bits	0b00 = equal power; 0b01 = reserved; 0b10 = Interference dependent. Per subcarrier power limit; 0b11 = Interference dependent. Total power limit
Power boost	1 bit	0 = no power boost 1= power boost
Multi-Antenna Flag	1 bit	0=MSS sounds first antenna only 1=MSS sounds all antennas
if (Separability type==0) {		
Cyclic time shift index m	5 bits	Cyclically shifts the time domain symbol by multiples (from 0 to P –1) of N/P where

		N=FFT size, and P=Max Cyclic Shift Index.
} Else {		
Decimation Offset d	6 bits	Relative starting offset position for the first sounding occupied subcarrier in the sounding allocation
}		
Periodicity	2 bits	00=single command, not periodic, or terminate periodicity 01=repeat sounding once per frame until terminated 10= repeat instructions once per 2 frames 11= repeat instructions once per 4 frames
}		
}		
} else {		
Permutation	2 bits	0b00 = PUSC perm. 0b01 = FUSC perm. 0b10 = Optional FUSC perm. 0b11 = Adjacent subcarrier perm.
IDcell	6 bits	
Num_Sounding_symbols	3 bits	
for (i=0;i<Num_Sounding_symbols;i++){		
Number of CIDs	7 bits	
For (j=0; j<Number of CIDs; j++) {		
Shortend basic CID	12 bits	12 LS bits of the MSS basic CID value
Subchannel offset	7 bits	The lowest index subchannel used for carrying the burst, starting from subchannel 0
Number of subchannels	3 bits	The number subchannels with subsequent indexes, used to carry the burst.
Periodicity	2 bits	00=single command, not periodic, or terminate periodicity 01=repeat sounding once per frame until terminated 10= repeat instructions once per 2 frames 11= repeat instructions once per 4 frames
Power Assignment Method	2 bits	0b00 = equal power; 0b01 = reserved; 0b10 = Interference dependent. Per subcarrier power limit; 0b11 = Interference dependent. Total power limit

Power boost	1 bit	0 = no power boost 1 = power boost
}		
}		
}		
Padding	Variable	Pad IE to octet boundary. Bits shall be set to 0
}		

[ Add a new section 8.4.6.2.7.3 “Direct transmission of channel coefficients”. Add the following text.]

### Section 8.4.6.2.7.3 Direct transmission of DL channel coefficients

If the field “Include Channel Coefficients” is set to 1, then the UL Sounding Command IE() enables the MSS to perform the direct transmission of DL channel coefficients to the BS along with the UL sounding waveform. This functionality provides downlink channel state information to the BS in both FDD systems and TDD systems in which BS array transceiver calibration is not implemented. With this functionality enabled, DL channel coefficients are encoded as described below and are transmitted in one or more sounding zone symbols that immediately following each symbol being used to transmit UL sounding waveforms. In this case, the UL sounding waveform is used by the BS to estimate the UL channel so that the DL channel coefficients transmitted by the MSSs can be estimated by the BS. The channel coefficients can then be used to enable closed-loop transmission on the downlink.

There are two cases depending on the value of the separability type field. First, if separability type is 0 (cyclic shift separability in the sounding waveform), then a single additional symbol follows each sounding symbol being allocated with the UL\_Sounding\_command\_IE(). In that additional symbol, an MSS antenna that transmits sounding in the sounding symbol will transmit an encoded channel coefficient waveform that occupies the same sounding bands allocated for the sounding waveform. The encoded waveform for the  $u^{\text{th}}$  MSS (where  $u$  is the cyclic shift index in the UL Sounding Command) is defined for two cases: The first case is for where the MSS has a single transmit antenna, but multiple receive antennas and is told with the sounding command IE to sound all antennas (multi-antenna flag set to 1). In this case, the single transmit antenna transmits the sounding waveform appropriate for the single transmit antenna on the sounding symbol and transmits the following encoded waveform in the next symbol interval:

$$Z_u(k) = \beta_u \sum_{\ell=1}^{M_b} \sum_{m=1}^{M_{m,u}} \hat{H}_{u,m,\ell}(k) s_u(k) \exp\{-j2\pi k(m-1 + (\ell-1)M_{m,u}) / \alpha_u\}$$

where  $\hat{H}_{u,m,\ell}(k)$  is the estimated DL channel coefficient between the  $\ell^{\text{th}}$  BS transmit antenna and the  $m^{\text{th}}$  receive antenna of the  $u^{\text{th}}$  MSS for subcarrier  $k$ ;  $\beta_u$  is a scaling to make the average transmit power of the feedback waveform (averaged across all frequency) of  $Z_u(k)$  be one;  $s_u(k)$  is the sounding sequence of Section 8.4.6.2.7.1;  $M_{m,u}$  is the number of receive antennas on the  $u^{\text{th}}$  MSS,  $\alpha_u$  is  $M_{m,u}M_b$ ; and  $M_b$  is the number of BS transmit antennas.

The second case for a separability type of 0 is for when the MSS has a number of transmit antennas equal to the number of receive antennas. In this case, the encoded waveform to be transmitted by the MSS antenna assigned to cyclic shift index of  $u$  in the UL Sounding Command is

$$Z_u(k) = \beta_u \sum_{\ell=1}^{M_b} \hat{H}_{u,\ell}(k) s_u(k) \exp\{-j2\pi k(\ell-1)/\alpha_u\}$$

where  $\hat{H}_{u,\ell}(k)$  is the estimated DL channel coefficient between the  $\ell^{\text{th}}$  BS transmit antenna and the MSS antenna assigned to the cyclic shift index of  $u$  in the UL Sounding Command for subcarrier  $k$ ;  $\beta_u$  is a scaling to make the average transmit power of the feedback waveform (averaged across all frequency) of  $Z_u(k)$  be one;  $s_u(k)$  is the sounding sequence of Section 8.4.6.2.7.1;  $\alpha_u$  is  $M_{m,u}M_b$ ; and  $M_b$  is the number of BS transmit antennas.

When separability type is 1 in the UL Sounding Command (decimation separability in the sounding waveform), then every allocated sounding symbol is followed by a number of additional symbols equal to the number of BS antennas. In this case, an MSS antenna that transmits on subcarrier  $k$  of the sounding symbol shall transmit the DL channel coefficient for the  $i^{\text{th}}$  base antenna to that MSS antenna for the  $k^{\text{th}}$  subcarrier on subcarrier  $k$  of the  $i^{\text{th}}$  additional symbol following the allocated sounding symbol. In equation form, the MSS that transmits a sounding signal on subcarrier  $k$  of the sounding symbol shall transmit  $\hat{H}_\ell(k)$  on the  $\ell^{\text{th}}$  symbol following the sounding symbol, where  $\hat{H}_\ell(k)$  is the DL channel coefficient from the  $\ell^{\text{th}}$  BS antenna to that MSS antenna.

If feedback type = 0, the above equations are modified by sending the measured pilot signal values instead of the measured channel.

----- End of Text Changes -----

## References

- [1] T. L. Marzetta and B. M. Hochwald, "Fast Transfer of Channel State Information in Wireless Systems," submitted to IEEE Transactions on Communications, June 2004, available at <http://mars.bell-labs.com>.
- [2] T. L. Marzetta and B. M. Hochwald, "Learning the Channel at the Transmitter," *Forty-Second Annual Allerton Conference on Communication, Control, and Computing*, Monticello, IL, September 29-October 1, 2004.