
Project **IEEE 802.16 Broadband Wireless Access Working Group <<http://ieee802.org/16>>**

Title **Heterogeneous Neighbor information in MOB-NBR_ADV message**

Date Submitted **2004-11-4**

Source(s) Sungjin Lee, Jungje Son, Changhoi Koo
Samsung Electronics

Voice: +82 31 279 5248
e-mail : steve.lee@samsung.com

Re: This contribution is response to call for contribution about IEEE 802.16e-D5

Abstract This document proposes the a new info field in MOB-NBR-ADV message

Purpose Discuss and adapt proposed text and message format.

Notice This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.

Release The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.

Patent Policy and Procedures The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures <<http://ieee802.org/16/ipr/patents/policy.html>>, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair <<mailto:chair@wirelessman.org>> as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site <<http://ieee802.org/16/ipr/patents/notices>>.

Heterogeneous Neighbor Information in MOB-NBR_ADV message

Sungjin Lee, Jungje Son and Changhoi Koo

SAMSUNG Electronics

1. Problem Statement

The MOB-NBR_ADV message that is defined in IEEE P802.16e/D5 specification contains useful information of neighbor BSs. The information is only for the 802.16-compliant neighbor BSs. In some cases, a MSS may have dual mode or triple mode supporting 802.16, WLAN, 3G services in one terminal. Sometimes the dual mode terminal needs to roam or handoff between the heterogeneous wireless access services in order to have more bandwidth or mobility, then the dual mode MSS start to search WLAN APs until it finds any AP or periodically depends on the application. However, a MSS could consume power in order to keep searching any AP in the cell where there is no AP exist in. That is the only way to find out whether if there is any accessible AP in the cell or not.

Another problem that can be occurred

have information of heterogeneous wireless access service within the Serving BS cell coverage area, if any. The only way to do this is that MSS keeps trying to search heterogeneous wireless service access points (e.g. WLAN APs). Once MSS finds the APs or BSs, another problem still remains; the MSS could not figure out whether or not the heterogeneous wireless service is feasible until it tries to access the APs or BSs to see if it can be accepted based on the contracts with the operator the AP or BS is belongs to other operator or have no contract for interworking with the operator that the MSS have registered.

In this contribution, we propose new fields to provide information of heterogeneous wireless service APs or BSs which support roaming or handoff.

2. Proposed Remedy

MOB_NBR-ADV message may include HET_NBR_INFO fields in order to provide heterogeneous access service information.

1. Proposed text change

[Modify MOB-NBR-ADV message in Page 62-65, Table 106d]

Syntax	Size	Notes
MOB-NBR_ADV Message_Formant() {		
Management message type = 53	8 bits	
Operator ID	24 bits	Unique ID assigned to the operator
Configuration Change Count	8 bits	Incremented each time the information for the associated neighbors BS has changed
Fragmentation Index	4 bits	This field indicates the current fragmentation index.

Total Fragmentation	4 bits	This field indicates the total number of fragmentations.
Skip-Optional-Fields <u>bitmapFlag</u>	4 bits	[0] If set to '1' and if a neighbor has OFDMA PHY the BS-ID for that neighbor is omitted in this message. If set to '0', BS-ID is not omitted for any neighbor. [1] If set to '1' HET_NBR_INFO field shall be omitted in this message.
<u>HET_NBR_INFO</u>	4 bits	[0]: accessible WLAN AP existence [1]-[3]: reserved
<u>if (HET_NBR_INFO[0] = 0) {</u>		
<u>ESS ID</u>		<u>Accessible WLAN ESS ID</u>
<u>}</u>		
N_NEIGHBORS	8 bits	
For (j=0;j<N_NEIGHBORS;j++){		
Length	8 bits	Length of message information within the iteration of N_NEIGHBOR in bytes.
PHY Profile ID	8 bits	Aggregated IDs of Co-located FA Indicator, FA Configuration Indicator, FFT size, Bandwidth, Operation Mode of the starting subchannelization of a frame, and Channel Number
if (FA Index indicator==1){		
FA Index	8 bits	This field, Frequency Assignment Index, is present only the FA Index Indicator in PHY Profile ID is set. Otherwise, the neighbor BS has the same FA Index or the center frequency is indicated using the TLV encoded information.
}		
if (BS EIRP indicator==1){		
BS EIRP	8 bits	Signed Integer from -128 to 127 in unit of dBm This field is present only if the BS EIRP indicator is set in PHY Profile ID. Otherwise, the BS has the same EIRP as the serving BS.
}		
Neighbor BS-ID	24 bits	This is an optional field for OFDMA PHY
Preamble Index	8 bits	The index for the PHY profile specific preamble. Preamble Index is PHY specific for SCa and OFDMA. The value of Preamble Index shall be ignored and a value of '0x00' shall be used for OFDM PHY
HO Process Optimization	8 bits	HO Process Optimization is provided as part of this message is indicative only. HO process requirements may change at time of actual HO. For each Bit location, a value of '0' indicates the associated reentry management messages shall be required, a value of '1' indicates the reentry management message may be

		<p>omitted. Regardless of the HO Process Optimization TLV settings, the Target BS may send unsolicited SBC-RSP and/ or REG-RSP management messages</p> <p>Bit #0: Omit SBC-REQ/RSP management messages during current re-entry processing</p> <p>Bit #1: Omit PKM-REQ/RSP management message during current re-entry processing</p> <p>Bit #2: Omit REG-REQ/RSP management during current re-entry processing</p> <p>Bit #3: Omit Network Address Acquisition management messages during current reentry processing</p> <p>Bit #4: Omit Time of Day Acquisition management messages during current reentry processing</p> <p>Bit #5: Omit TFTP management messages during current re-entry processing</p> <p>Bit #6: Full service and operational state transfer or sharing between Serving BS and Target BS (ARQ, timers, counters, MAC state machines, etc...)</p>
Scheduling Service Supported	4 bits	<p>Bitmap to indicate if BS supports a particular scheduling service. '1' indicates support, '0' indicates not support:</p> <p>bit 0: Unsolicited Grant Service (UGS)</p> <p>bit 1: Real-time Polling Service (rtPS)</p> <p>bit 2: Non-real-time Polling service (nrtPS)</p> <p>bit 3: Best Effort value of '1111' indicates no information on service available</p>
Available Radio Resource	4 bits	<p>Percentage of reported average available subchannels and symbols resources per frame</p> <p>0000: 0%</p> <p>0001: 20%</p> <p>0010: 40%</p> <p>0011: 60%</p> <p>0100: 80%</p> <p>0101: 100%</p> <p>0110-1110: reserved</p> <p>0110-1110: reserved</p> <p>value of '1111' indicates no information on service available</p>
Handoff Neighbor Preference	2 bits	<p>00 Normal</p> <p>01 Preferred</p> <p>10 Non-Preferred</p> <p>11 Reserved</p>
DCD Configuration Change Count	3 bits	<p>This represents the Neighbor BS current DCD configuration change count</p>

UCD Configuration Change Count	3 bits	This represents the Neighbor BS current UCD configuration change count
TLV Encoded Neighbor information	Variable	TLV specific
}		
}		

HET NBR INFO

This field shall be omitted if Skip-optional-field bitmap #1 bit is set '1'. This field provide the information represent which heterogeneous access AP or BS existence and accessibility.

[0] bit : accessible WLAN AP existence (0: exist) (1:not exist)

[1]-[3] bits : reserved

ESS ID

This field present only if HET_NBR_Info [0] bit value is '0'. The message field provide accessible ESS-ID.