2004-11-04 IEEE C802.16e-04/530

Project	IEEE 802.16 Broadband Wireless Access Working Group http://ieee802.org/16 >
Title	Enable closed-loop MIMO channel estimation using partially beamformed midamble
Date Submitted	2004-11-04
Source(s)	Qinghua Li, Xintian Eddie Lin, Shilpa Talwar, qinghua.li@intel.com
	Intel Corporation Voice: +1-408-765-9698
Re:	
Abstract	Per-Stream ABL for MIMO Precoding Systems
Purpose	Adoption of proposed changes into P802.16e
	Crossed-out indicates deleted text, underlined blue indicates new text change to the Standard
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures (Version 1.0) http://ieee802.org/16/ipr/patents/policy.html >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, if there is technical justification in the opinion of the standards-developing committee and provided the IEEE receives assurance from the patent holder that it will license applicants under reasonable terms and conditions for the purpose of implementing the standard."
	Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair <mailto:r.b.marks@ieee.org> as early as possible, in written or electronic form, of any patents (granted or under application) that may cover technology that is under consideration by or has been approved by IEEE 802.16. The Chair will disclose this notification via the IEEE 802.16 web site http://ieee802.org/16/ipr/patents/notices>.</mailto:r.b.marks@ieee.org>

2004-11-04 IEEE C802.16e-04/530

Enable Closed-Loop MIMO Channel Estimation Using Beamformed Midamble

Qinghua Li, Xintian Eddie Lin
Intel Corporation

Abstract

For closed-loop MIMO (i.e. MIMO precoding), there is no training mechanism in the current standard for the composite channel, which consists of the beamforming matrix, the transmit chain response at the transmitter, the, wireless medium response, and the receive chain response at the receiver. This is because all the pilots and midamble are sent without beamforming. The receiver has to rely on the assumption that the receiver knows the beamforming matrix employed in the transmitter. However, the assumption doesn't hold for two cases. First, it fails when channel sounding and channel reciprocity is employed TDD modes. Secondly, it fails when there is a feedback error in FDD modes. For both cases, the MIMO precoding doesn't work. This can be solved by sending part the midable in beamformed mode, which is employed for the data portion.

1 Beamformed Midamble

2 Specific Text Changes

References:

[1] IEEE P802.16e/D5 Air Interface for Fixed and Mobile Broadband Wireless Access Systems – Amendment for Physical and Medium Access Control Layers for Combined Fixed and Mobile Operation in Licensed Bands, 2004.

[2] IEEE P802.16-REVd/D5-2004 Draft IEEE Standards for local and metropolitan area networks, Part 16: Air interface for fixed broadband wireless access systems, 2004.