

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	Clarifications on the Extended DIUC/UIUC	
Date Submitted	2005-03-16	
	Phillip Barber Broadband Mobile Technologies, Inc.	Voice: +1 (972) 365-6314 Fax: +1 (925) 396-0269 [mailto:pbarber@BroadbandMobileTech.com]
	Kamran Etemad Masoud Olfat Nextel Communications	Voice: +1 (240) 994-1792 Fax: +1 (703) 433-8435 [mailto:Kamran.Etemad@NEXTEL.COM]
	David McGinniss John Humbert Sprint	Voice: +82-31-279-5091 Fax: +82-31-279-5130 [mailto:david.s.mcginness@MAIL.SPRINT.COM]
	Mary Chion Sean Cai Jason Hou ZTE San Diego Inc.	Voice: + 1 (858) 554-0387 Fax: +1 (858) 554-0894 [mailto:mchion@ztesandiego.com]
	Yongseok Jin LG Electronics, Inc.	Voice: +82-31-450-7187 Fax: +82-31-450-7912 [mailto:jayjay@lge.com]
	Yigal Leiba Runcom Technologies Ltd.	Voice: +972-3-9528440 Fax: +972-3-9528805 [mailto:yigall@runcom.co.il]
	Mo-Han Fong, Nortel Networks	Voice: +1-613-765-8983 Fax: +1-613-765-6717 [mailto:mhfong@nortelnetworks.com]
	Jiho Jang Seung Joo Maeng Samsung Electronics	Voice: +82-31-279-3355 Fax: +82-31-279-3219 [mailto:jiho.jang@samsung.com]
	Yigal Eliaspur Intel	Voice: +972-54-7884877 [mailto:yigal.eliaspur@intel.com]

Lei Wang
Cygnus Multimedia Communications, Inc. Voice (760)448-1984
lwang@cygnuscom.com

Re: IEEE P802.16e/D6

Abstract This contribution includes clarification on the current extended DL/UL IEs.

Purpose Review and adopt suggested change into P802.16e/D6

Notice This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.

Release The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.

Patent Policy and Procedures The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures (Version 1.0) <http://ieee802.org/16/ipr/patents/policy.html>, including the statement “IEEE standards may include the known use of patent(s), including patent applications, if there is technical justification in the opinion of the standards-developing committee and provided the IEEE receives assurance from the patent holder that it will license applicants under reasonable terms and conditions for the purpose of implementing the standard.”

Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair <<mailto:r.b.marks@ieee.org>> as early as possible, in written or electronic form, of any patents (granted or under application) that may cover technology that is under consideration by or has been approved by IEEE 802.16. The Chair will disclose this notification via the IEEE 802.16 web site <<http://ieee802.org/16/ipr/patents/notices>>.

Clarifications on the Extended DIUC/UIUC

Seung Joo Maeng et al

1. Problem Statement

In IEEE P802.16e-D5a-2004, there are several problems related to Extended DIUC/UIUC usage for the OFDMA PHY mode:

- All 17 Extended DIUCs codes have been used. There are also more Extended DIUC IEs being defined in new contributions.
- The use of extended DL-MAPs is efficient for a number of uses and continued addition of extended DL-MAPs should not be curtailed simply because the current method suffers code constraints. Extension of the method to permit new contributions is warranted.
- Extended DIUC/UIUC usage needs to be clarified and corrected. There are a few Extended DL/UL IEs using the same DIUC/UIUC.

2. Proposed Solutions

This contribution proposes an Extended-2 format to increase the number of types of Extended IE for OFDMA PHY mode. This new Extended-2 format is defined for both DL MAP and UL MAP. The DIUC 14 and UIUC 11 are used to identify this new format. All Extended IEs defined in 802.16d remain unchanged and are identified by Extended DIUC/UIUC (0x00... 0x0F). This contribution redefines all Extended IE defined in 802.16e.

This contribution also adds allocation tables for Extended DIUC/Extended UIUC and Extended-2 Types. By adding these tables, duplicating usage can be avoided.

3. Specific Text Changes

[Add the following subsection title right after the subsection title 8.4.5.3.2:]

8.4.5.3.2 DL-MAP extended IE format

8.4.5.3.2.1 DL-MAP extended IE format

[Append the following to the end of section 8.4.5.3.2:]

Table 2757a defines the encoding for Extended DIUC that shall be used by DL-MAP Extended IEs.

Table 2757a—Extended DIUC Allocation

<u>Extended DIUC</u>	<u>Usage</u>
<u>0x00</u>	<u>Channel Measurement IE</u>
<u>0x01</u>	<u>STC Zone IE</u>
<u>0x02</u>	<u>AAS DL IE</u>
<u>0x03</u>	<u>Data location in another BS IE</u>

0x04	CID Switch IE
0x05	MIMO DL Basic IE
0x06	MIMO DL Enhanced IE
0x07	H-ARQ Map Pointer IE
0x08	PHYMOD DL IE
0x09	DL PUSC Burst Allocation in Other Segment
0x0A	UL interference and noise level IE
0x0B ... 0x0F	Reserved

[Insert the following section]

8.4.5.3.2.2 DL-MAP Extended-2 IE format

[A DL-MAP IE entry with a DIUC value of 14, indicates that the IE carries special information and conforms to the structure shown in Table 2757b. A station shall ignore an extended-2 IE entry with an extended-2 DIUC value for which the station has no knowledge. In the case of a known extended-2 DIUC value but with a length field longer than expected, the station shall process information up to the known length and ignore the remainder of the IE.](#)

Table 2757b—OFDMA DL-MAP extended-2 IE format

<u>Syntax</u>	<u>Size</u>	<u>Note</u>
DL Extended-2 IE {		
Extended-2 DIUC	4 bits	0x00 ... 0x0F
Length	8 bits	Length in bytes of Unspecified data field
Unspecified data	variable	
}		

[Table 2757c defines the encoding for Extended-2 DIUC that shall be used by DL-MAP Extended-2 IEs.](#)

Table 2757c—Extended-2 DIUC Allocation

<u>Extended-2 DIUC</u>	<u>Usage</u>
0x00	MBS MAP IE
0x01	HO Anchor Active DL MAP IE
0x02	HO Active Anchor DL MAP IE
0x03	HO CID Translation MAP IE
0x04	MIMO in another BS IE
0x05	Macro-MIMO DL Basic IE
0x06	Skip IE
0x07	HARQ DL MAP IE
0x08	HARQ ACK IE
0x09	Enhanced DL MAP IE
0x0A	Closed-loop MIMO DL Enhanced IE
0x0B ... 0x0F	Reserved

[Modify the following sections:]

8.4.5.3.4412 Multicast and Broadcast Service MAP IE (MBS_MAP_IE)

.....

Table 2835b—Multicast and Broadcast Service MAP IE

Syntax	Size	Note
MBS_MAP_IE {		
Extended-2 DIUC	4 bits	MBS_MAP_IE()=0x00
Length	4 8 bits	variable
.....		
}		

.....

8.4.5.3.4213 DL PUSC Burst Allocation in Other Segment IE

.....

Table 2845c—DL PUSC Burst Allocation in Other Segment IE

Syntax	Size	Note
DL PUSC Burst Allocation in Other Segment IE() {		
Extended DIUC	4 bits	DL PUSC Burst Allocation in Other Segment IE() =0x09
Length	4 bits	Length = 0x09
.....		
}		

.....

8.4.5.3.4314 HO Anchor Active DL MAP IE

.....

Table 2845d—HO Anchor Active DL MAP IE

Syntax	Size	Note
HO Anchor Active DL MAP IE() {		
Extended-2 DIUC	4 bits	HO Anchor Active MAP IE() = 0x01
Length	4 8 bits	variable
.....		
}		

.....

8.4.5.3.4415 HO Active Anchor DL MAP IE

.....

Table 2845e—HO Active Anchor MAP IE

Syntax	Size	Note
HO Active_Anchor_DL MAP IE () {		
Extended-2 DIUC	4 bits	HO Active_Anchor MAP IE = 0x02
Length	4 8 bits	variable
.....		
}		

.....

8.4.5.3.4516 HO CID Translation MAP IE

.....

Table 2845f—HO CID Translation MAP IE

Syntax	Size	Note
HO CID Translation MAP IE() {		
Extended-2 DIUC	4 bits	CID Translation MAP IE = 0x03
Length	4 8 bits	variable
.....		
}		

.....

8.4.5.3.4617 MIMO in another BS IE

.....

Table 2845g—MIMO in another BS IE

Syntax	Size	Note
MIMO in another BS IE () {		
Extended-2 DIUC	4 bits	MIMO in another BS IE = 0x04
Length	4 8 bits	variable
.....		
}		

.....

8.4.5.3.4718 Macro-MIMO DL Basic IE format

.....

Table 2845h—Macro MIMO DL Basic IE()

Syntax	Size	Note
Macro_MIMO_DL_Basic_IE() {		
Extended-2 DIUC	4 bits	Macro MIMO DL Basic IE = 0x05
Length	4 8 bits	variable
.....		
}		

.....

8.4.5.3.4819 UL noise and interference level IE

.....

Table 2845i—UL interference and noise level extended IE

Syntax	Size	Note
UL interference and noise level IE {		
Extended DIUC	4 bits	UL interference and noise level IE = 0x0A
Length	4 bits	variable
....		
}		

.....

[Move section 8.4.5.3.1920 to 8.4.5.4.2328 and modify as follows:]

8.4.5.34.192328 Feedback polling IE

.....

Table 28498j302s—Feedback Polling IE

Syntax	Size	Note
Feedback polling IE () {		
Extended-2 UIUC	4 bits	Feedback Polling IE()=0x05
Length	4 8 bits	Length in bytes of following fields
....		
}		

.....

[Add the following subsection title right after the subsection title 8.4.5.4.4:]

8.4.5.4.4 UL-MAP extended IE format

[8.4.5.4.4.1 UL-MAP extended IE format](#)

[Append the following to the end of section 8.4.5.4.4:]

[Table 289a](#) defined the encoding for Extended UIUC that shall be used by UL-MAP Extended IEs.

Table 289a—Extended UIUC Allocation

Extended UIUC	Usage
0x00	Power control IE
0x01	Mini-subchannel allocation IE
0x02	AAS UL IE
0x03	CQICH Alloc IE
0x04	UL Zone IE
0x05	PHYMOD UL IE
0x06	Fast Ranging IE

0x07	UL_MAP Fast Tracking IE
0x08	UL_PUSC_Burst_Allocation_in_Other_Segment_IE
0x09	MIMO UL Basic IE
0x0A ... 0x0F	Reserved

[Insert the following sections:]

8.4.5.4. 4.2 UL-MAP Extended-2 IE Format

A UL-MAP IE entry with a UIUC value of 11, indicates that the IE carries special information and conforms to the structure shown in Table 289b. A station shall ignore an extended-2 IE entry with an extended-2 UIUC value for which the station has no knowledge. In the case of a known extended-2 UIUC value but with a length field longer than expected, the station shall process information up to the known length and ignore the remainder of the IE.

Table 289b—UL-MAP Extended-2 IE Format

Syntax	Size	Note
UL_Extended-2_IE() {		
Extended-2_UIUC	4 bits	<u>0x00 ... 0x0F</u>
Length	8 bits	<u>Length in bytes of Unspecified data field</u>
Unspecific Data	Variable	
}		

Table 289c defines the encoding for Extended-2 UIUC that shall be used by UL-MAP Extended-2 IEs.

Table 289c—Extended-2 Type Allocation

Extended-2 Type	Usage
0x00	CQICH Enhanced Allocation IE
0x01	HO Anchor Active UL MAP IE
0x02	HO Active Anchor UL MAP
0x03	Anchor_BS_switch IE
0x04	UL sounding command IE
0x05	Feedback polling IE
<u>0x06</u>	<u>MIMO UL Enhanced IE</u>
<u>0x07</u>	<u>HARQ UL MAP IE</u>
<u>0x08</u>	<u>HARQ ACKCH Region Allocation IE</u>
<u>0x09</u>	<u>UL Allocation start IE</u>
0x0A ... 0x0F	Reserved

[Modify the following sections:]

8.4.5.4.15 CQICH Enhanced Allocation IE format

Table 298302a—CQICH Enhanced allocation IE format

Syntax	Size	Note
CQICH_Enhanced_Alloc_IE() {		
Extended-2 <u>UIUC</u>	4 bits	CQICH Enhance Alloc IE()=0x00
Length	<u>4 8</u> bits	Length in bytes of following fields
.....		
}		

.....

8.4.5.4.16 UL PUSC Burst Allocation in Other Segment IE

.....

Table 298302b—UL PUSC Burst Allocation in Other Segment IE

Syntax	Size	Note
UL PUSC Burst Allocation in Other Segment IE () {		
Extended <u>UIUC</u>	4 bits	UL PUSC Burst Allocation in Other Segment IE () = 0x08
Length	4 bits	Length=0x <u>08</u>
.....		
}		

.....

8.4.5.4.18 HO Anchor Active UL MAP IE

.....

Table 298302e—HO Anchor Active UL MAP IE

Syntax	Size	Note
HO Anchor Active UL MAP IE () {		
Extended- <u>2</u> <u>UIUC</u>	4 bits	HO Anchor Active MAP IE() = 0x01
Length	<u>4 8</u> bits	
.....		
}		

.....

8.4.5.4.19 HO Active Anchor UL MAP IE

.....

Table 298302f—HO Active Anchor UL MAP IE

Syntax	Size	Note
HO Active_Anchor UL MAP IE () {		
Extended- <u>2</u> <u>UIUC</u>	4 bits	HO Active_Anchor MAP IE() = 0x02
Length	<u>4 8</u> bits	
.....		
}		

.....

8.4.5.4.2021 OFDMA Fast_Ranging_IE format

.....

Table 298298g302h—OFDMA Fast_Ranging_IE format

Syntax	Size	Note
Fast_Ranging_IE {		
Extended UIUC	4 bits	Fast_Ranging_IE() = 0x06
Length	4 bits	variable
.....		
}		

.....

8.4.5.4.2122 UL_MAP_Fast_Tracking_IE

.....

Table 298h302i—UL_MAP_Fast_Tracking_IE

Syntax	Size	Note
UL_MAP_Fast_Tracking_IE() {		
Extended UIUC	4 bits	Fast Tracking IE() = 0x07
Length	4 bits	Variable
.....		
}		

.....

8.4.5.4.2223 Anchor BS Switch IE

.....

Table 298i302j—Anchor_BS_switch_IE format

Syntax	Size	Note
Anchor_BS_switch_IE() {		
Extended-2 UIUC	4 bits	Anchor_BS_switch_IE()=0x03
Length	4 8 bits	variable
.....		
}		

.....

8.4.6.2.78.1 Channel sounding

.....

Table 314315k—UL_sounding_command_IE()

Syntax	Size	Note
UL_sounding_command_IE() {		
Extended-2 UIUC	4 bits	UL_sounding_command_IE()=0x04
Length	4 8 bits	variable

.....		
}		

.....

4. References

- [1] IEEE 802.16-2004 IEEE Standards for local and metropolitan area networks part 16: Air interface for fixed broadband wireless access systems
- [2] IEEE P802.16e/D6
- [3] C80216e-05/88 Clarifications on the Extended DIUC/UIUC