

Project	IEEE 802.16 Broadband Wireless Access Working Group < <a href="http://ieee802.org/16">http://ieee802.org/16</a> >	
Title	MAC Header and Subheader Type Fields Encodings	
Date Submitted	2005-03-17	
Source(s)	Lei Wang Cygnus Communications Inc.  Rainer Ullmann Wavesat	Voice: 760-448-4168 Fax: 760-448-1989 <a href="mailto:lwang@cygnuscom.com">lwang@cygnuscom.com</a>
Re:	This is a contribution to IEEE 802.16e.	
Abstract	In the current document of 802.16e, i.e., 16e/D6, the type field code allocation is problematic, e.g., duplicated allocations. This contribution proposes to add tables to list the type fields encodings and also to clean up the type code allocation problems in 16e/D6.	
Purpose	To correct the errors of the type code allocations and also to improve the type code allocations.	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < <a href="http://ieee802.org/16/ipr/patents/policy.html">http://ieee802.org/16/ipr/patents/policy.html</a> >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < <a href="mailto:chair@wirelessman.org">mailto:chair@wirelessman.org</a> > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < <a href="http://ieee802.org/16/ipr/patents/notices">http://ieee802.org/16/ipr/patents/notices</a> >.	

# MAC Header and Subheader Type Fields Encodings

Session#36 MAC Header Drafting Group

## Introduction

In the current document of 802.16e, i.e., 16e/D6, the type field code allocation is problematic, e.g., duplicated allocations. This contribution proposes to add tables to list the type fields encodings and also to clean up the type code allocation problems in 16e/D6.

## References

IEEE Std 802.16-2004

IEEE P802.16e/D6, February 2005

## Suggested Changes

1. Insert Table 7g in line 32, page 13

Table 7g MAC Header HT and EC fields encoding

HT	EC	MAC PDU Type	Reference Figure	Reference Table
0	0	MAC PDU with data payload, no encryption, with a 6-bit type field, see Table 6 for its type field encodings.	19	5
0	1	MAC PDU with data payload, with encryption with a 6-bit type field, see Table 6 for its type field encodings.	19	5
1	0	MAC PDU without data payload, (also called Bandwidth Request Header), with a 3-bit type field, see Table 7h for type encoding definitions	20	7
1	1	<p><u>DL only: compressed MAP</u></p> <p><u>UL only: Feedback MAC Header</u> <del>MAC PDU without data payload, with a 1-bit type field, see Table 7i for its type encoding definitions.</del></p>	??	??

2. Insert Table 7h in line 23 page 14

Table 7h MAC Header Type Field Encodings with HT/EC=0b10

type field (3 bits)	MAC Header Type (with HT/EC=0b10)	Reference Figure	Reference Table
000	BR incremental	20	7
001	BR aggregate	20	7
010	PHY channel report header	20c	7c
011	BR with UL Tx power	20a	7a
100	BR with DL burst profile	20b	7b
101	BR with UL sleep control header	n/a	??
110	Extended MAC Header SN Report SN-report	21e-??	7f??
111	CQICH channel allocation request	20d??	7e??

3. move two subsections 6.3.2.1.5 and 6.3.2.1.6 to line 42 page 18; and then renumber those two sections to 6.3.2.1.45 and 6.3.2.1.56, respectively;
4. renumber section number on page 18 line 45 to 6.3.2.1.6
5. insert Table 7i to line 47 page 18

**Table 7i MAC Header type fields encoding with HT/EC=0x0b11**

FHD/EHD	MAC header Type with HT/EC=0b11	Reference Figure	Reference Table
0	UL only: Feedback header, with another 5-bit type field, see Table 7d for its type encodings.	20d-a	??
1	DL only: Compressed MAP Reserved Extended MAC Header	??	??

6. page 14 line 45, make the following changes:

e) The allowed types for bandwidth requests are “000” for incremental and “001” for aggregate BR, “011” for BR and UL Tx power report header, “100” for “BR and DBPC request header” and “111” for CQICH channel allocation request.

7. page 14 line 26, make the following changes:

The Bandwidth Request PDU shall consist of bandwidth request header alone and shall not contain a payload. The bandwidth request header is-types are illustrated in Table 7h. Figure 20, Figure 20a and Figure 20ba. An SS receiving a bandwidth request header on the downlink shall discard the PDU.

8. page 14 line 48 make the following changes:

The fields of the bandwidth request header are defined in Table 7 for types "000", "001 and "111", Table 7a for type "011" and Table 7b for "100". Every header is encoded, starting with the HT and EC fields. The coding of these fields is such that the first byte of a MAC header shall never have the value of 0xFF. This prevents false detection of the stuff byte.

9. page 14 line 61

change Figure ddd to Figure 20a

10. page 15 line 34, make the following changes:

d) The allowed types for bandwidth requests ~~with UL Tx transmit power report~~ are is “000” for incremental, “001” for aggregate, and “011” for an aggregate request ~~with UL Tx transmit power report~~. ~~The requested bandwidth is incremental.~~

11. page 16 line 4:

change Table 7a—Description of fields of the PHY channel report header to Table 7a -- Description of fields of BR and UL Tx power report header

12. page 24 line 41,

change “encoded as 000b” to “encoded as 0b101”

13. page 25 line 46

Change

The coding of these fields is such that the first byte of a MAC header shall never have the value of 0xFF.

to

The coding of these fields is such that the first byte of a MAC header shall never have the value of 0xFF.

