

Project	<b>IEEE 802.16 Broadband Wireless Access Working Group</b> < <a href="http://ieee802.org/16">http://ieee802.org/16</a> >	
Title	OFDMA Extended DIUC/UIUC and Extended-2 DIUC/UIUC Code Assignment Tables	
Date Submitted	<b>2005-05-05</b>	
	Lei Wang Cygnus Multimedia Communications, Inc.	Voice (760)448-1984 <a href="mailto:lwang@cygnuscom.com">lwang@cygnuscom.com</a>
	Jiho Jang Seung Joo Maeng Samsung Electronics	Voice: +82-31-279-3355 Fax: +82-31-279-3219 <a href="mailto:jiho.jang@samsung.com">[mailto:jiho.jang@samsung.com]</a>
Re:	IEEE P802.16e/D7	
Abstract	This contribution includes clarification on the current extended DL/UL IEs.	
Purpose	Review and adopt suggested change into P802.16e/D7	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures (Version 1.0) < <a href="http://ieee802.org/16/ipr/patents/policy.html">http://ieee802.org/16/ipr/patents/policy.html</a> >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, if there is technical justification in the opinion of the standards-developing committee and provided the IEEE receives assurance from the patent holder that it will license applicants under reasonable terms and conditions for the purpose of implementing the standard."  Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < <a href="mailto:r.b.marks@ieee.org">mailto:r.b.marks@ieee.org</a> > as early as possible, in written or electronic form, of any patents (granted or under application) that may cover technology that is under consideration by or has been approved by IEEE 802.16. The Chair will disclose this notification via the IEEE 802.16 web site < <a href="http://ieee802.org/16/ipr/patents/notices">http://ieee802.org/16/ipr/patents/notices</a> >.	

# Clarifications on the Extended DIUC/UIUC

Lei Wang and Jiho Jang

## 1. Problem Statement

Extended DIUC/UIUC usage needs to be clarified and /corrected. There are several Extended DL/UL IEs using the same DIUC/UIUC.

## 2. Proposed Solutions

This contribution proposes an Extended-2 format to increase the number of types of Extended IE for OFDMA PHY mode. This new Extended-2 format is defined for both DL MAP and UL MAP. The DIUC 14 and UIUC 11 are used to identify this new format. All Extended IEs defined in 802.16d remain unchanged and are identified by Extended DIUC/UIUC (0x00... 0x0F). This contribution redefines all Extended IE defined in 802.16e.

This contribution also adds allocation tables for Extended DIUC/Extended UIUC and Extended-2 Types. By adding these tables, duplicating usage can be avoided.

## 3. Specific Text Changes

***[Add the following subsection title right after the subsection title 8.4.5.3.2:]***

### 8.4.5.3.2 DL-MAP extended IE format

#### 8.4.5.3.2.1 DL-MAP extended IE format

***[Append the following to the end of section 8.4.5.3.2:]***

Table 277a defines the encoding for Extended DIUC that shall be used by DL-MAP Extended IEs.

**Table 277a—Extended DIUC Code Assignment for DIUC=15**

<u>Extended DIUC</u>	<u>Usage</u>
<u>0x00</u>	<u>Channel Measurement IE</u>
<u>0x01</u>	<u>STC Zone IE</u>
<u>0x02</u>	<u>AAS DL IE</u>
<u>0x03</u>	<u>Data location in another BS IE</u>
<u>0x04</u>	<u>CID Switch IE</u>
<u>0x05</u>	<u>MIMO DL Basic IE</u>
<u>0x06</u>	<u>MIMO DL Enhanced IE</u>
<u>0x07</u>	<u>H-ARQ Map Pointer IE</u>
<u>0x08</u>	<u>PHYMOD DL IE</u>
<u>0x09-0x0A</u>	<u>reserved</u>

<u>0x0B</u>	<u>DL PUSC Burst Allocation in Other Segment</u>
<u>0x0C-0x0E</u>	<u>reserved</u>
<u>0x0F</u>	<u>UL interference and noise level IE</u>

***[Insert the following section]***

#### **8.4.5.3.2.2 DL-MAP Extended-2 IE format**

A DL-MAP IE entry with a DIUC value of 14, indicates that the IE carries special information and conforms to the structure shown in Table 277b. A station shall ignore an extended-2 IE entry with an extended-2 DIUC value for which the station has no knowledge. In the case of a known extended-2 DIUC value but with a length field longer than expected, the station shall process information up to the known length and ignore the remainder of the IE.

**Table 277b—OFDMA DL-MAP extended-2 IE format**

<u>Syntax</u>	<u>Size</u>	<u>Note</u>
<u>DL Extended-2 IE {</u>		
<u>Extended-2 DIUC</u>	<u>4 bits</u>	<u>0x00 ... 0x0F</u>
<u>Length</u>	<u>8 bits</u>	<u>Length in bytes of Unspecified data field</u>
<u>Unspecified data</u>	<u>variable</u>	
<u>}</u>		

Table 277c defines the encoding for Extended-2 DIUC that shall be used by DL-MAP Extended-2 IEs.

**Table 277c—Extended-2 DIUC Code Assignment for DIUC=14**

<b><u>Extended-2 DIUC</u></b>	<b><u>Usage</u></b>
<u>0x00</u>	<u>MBS MAP IE</u>
<u>0x01</u>	<u>HO Anchor Active DL MAP IE</u>
<u>0x02</u>	<u>HO Active Anchor DL MAP IE</u>
<u>0x03</u>	<u>HO CID Translation MAP IE</u>
<u>0x04</u>	<u>MIMO in another BS IE</u>
<u>0x05</u>	<u>Macro-MIMO DL Basic IE</u>
<u>0x06</u>	<u>Skip IE</u>
<u>0x07</u>	<u>HARQ DL MAP IE</u>
<u>0x08</u>	<u>HARQ ACK IE</u>
<u>0x09</u>	<u>Enhanced DL MAP IE</u>
<u>0x0A</u>	<u>Closed-loop MIMO DL Enhanced IE</u>
<u>0x0B-0x0D</u>	<u>reserved</u>
<u>0x0E</u>	<u>AAS SDMA DL IE</u>
<u>0x0F</u>	<u>Reserved</u>

**[Modify the following sections:]**

**8.4.5.3.12 Multicast and Broadcast Service MAP IE (MBS\_MAP\_IE)**

.....

**Table 285a—Multicast and Broadcast Service MAP IE**

Syntax	Size	Note
MBS_MAP_IE {		
Extended-2 DIUC	4 bits	<a href="#">MBS_MAP_IE()=0x0A00</a>
Length	4 8 bits	variable
.....		
}		

.....

**8.4.5.3.14 HO Anchor Active DL MAP IE**

.....

**Table 285c—HO Anchor Active DL MAP IE**

Syntax	Size	Note
HO Anchor Active DL MAP IE() {		
Extended-2 DIUC	4 bits	<a href="#">HO Anchor Active MAP IE() = 0x0C01</a>
Length	4 8 bits	<a href="#">variable</a>
.....		
}		

.....

**8.4.5.3.15 HO Active Anchor DL MAP IE**

.....

**Table 285d—HO Active Anchor MAP IE**

Syntax	Size	Note
HO Active_Anchor_DL MAP IE () {		
Extended-2 DIUC	4 bits	<a href="#">HO Active_Anchor MAP IE = 0x0D02</a>
Length	4 8 bits	<a href="#">variable</a>
.....		
}		

.....

**8.4.5.3.16 HO CID Translation MAP IE**

.....

**Table 285e—HO CID Translation MAP IE**

Syntax	Size	Note
HO CID Translation		

MAP IE() {		
Extended-2 DIUC	4 bits	<a href="#">CID Translation MAP IE = 0x0E03</a>
Length	4 8 bits	<a href="#">variable</a>
.....		
}		

.....

**8.4.5.3.17 MIMO in another BS IE**

In the DL-MAP, a BS may transmit DIUC=~~15~~14 with the MIMO\_in\_another\_BS\_IE () to indicate that data is transmitted to the MS through other BS at the same frame. This IE shall be right after the IE defining the same data or data region received in the anchor BS.

**Table 285f—MIMO in another BS IE**

Syntax	Size	Note
MIMO in another BS IE () {		
Extended-2 DIUC	4 bits	<a href="#">MIMO in another BS IE = 0x0904</a>
Length	4 8 bits	<a href="#">variable</a>
.....		
}		

.....

**8.4.5.3.18 Macro-MIMO DL Basic IE format**

.....

**Table 285g—Macro MIMO DL Basic IE()**

Syntax	Size	Note
Macro_MIMO_DL_Basic_IE() {		
Extended-2 DIUC	4 bits	<a href="#">Macro MIMO DL Basic IE = 0x0b05</a>
Length	4 8 bits	<a href="#">variable</a>
.....		
}		

.....

**8.4.5.3.27 AAS SDMA DL IE { format**

.....

**Table 285u—AAS\_SDMA\_DL\_IE**

Syntax	Size	Note
AAS_SDMA_DL_IE() {		
Extended-2 DIUC	4 bits	<a href="#">AAS_SDMA_DL_IE = 0x0E</a>
Length	4 8 bits	<a href="#">variable</a>
.....		
}		

.....

**[Add the following subsection title right after the subsection title 8.4.5.4.4:]**

#### 8.4.5.4.4 UL-MAP extended IE format

##### 8.4.5.4.4.1 UL-MAP extended IE format

**[Append the following to the end of section 8.4.5.4.4:]**

Table 289a defined the encoding for Extended UIUC that shall be used by UL-MAP Extended IEs.

**Table 289a—Extended UIUC Code Assignment for UIUC=15**

<b>Extended UIUC</b>	<b>Usage</b>
0x00	Power control IE
0x01	Mini-subchannel allocation IE
0x02	AAS UL IE
0x03	CQICH Alloc IE
0x04	UL Zone IE
0x05	PHYMOD UL IE
0x06	MIMO UL Basic IE
0x07	UL MAP Fast Tracking IE
0x08	UL PUSC Burst Allocation in Other Segment IE
0x09	Fast Ranging IE
0x0A ... 0x0F	Reserved

**[Insert the following sections:]**

##### 8.4.5.4.4.2 UL-MAP Extended-2 IE Format

A UL-MAP IE entry with a UIUC value of 11, indicates that the IE carries special information and conforms to the structure shown in Table 289b. A station shall ignore an extended-2 IE entry with an extended-2 UIUC value for which the station has no knowledge. In the case of a known extended-2 UIUC value but with a length field longer than expected, the station shall process information up to the known length and ignore the remainder of the IE.

**Table 289b—UL-MAP Extended-2 IE Format**

<b>Syntax</b>	<b>Size</b>	<b>Note</b>
UL_Extended-2_IE() {		
Extended-2 UIUC	4 bits	0x00 ... 0x0F
Length	8 bits	Length in bytes of Unspecified data field
Unspecific Data	Variable	
}		

[Table 289c defines the encoding for Extended-2 UIUC that shall be used by UL-MAP Extended-2 IEs.](#)

**Table 289c—Extended-2 UIUC Code Assignment for UIUC=11**

<b>Extended-2 Type</b>	<b>Usage</b>
0x00	<a href="#">CQICH Enhanced Allocation IE</a>
0x01	<a href="#">HO Anchor Active UL MAP IE</a>
0x02	<a href="#">HO Active Anchor UL MAP</a>
0x03	<a href="#">Anchor BS switch IE</a>
0x04	<a href="#">UL sounding command IE</a>
0x05	reserved
<a href="#">0x06</a>	<a href="#">MIMO UL Enhanced IE</a>
<a href="#">0x07</a>	<a href="#">HARQ UL MAP IE</a>
<a href="#">0x08</a>	<a href="#">HARQ ACKCH Region Allocation IE</a>
<a href="#">0x09</a>	<a href="#">UL Allocation start IE</a>
0x0A ... 0x0D	Reserved
0x0E	<a href="#">AAS SDMA UL IE</a>
0x0F	<a href="#">Feedback polling IE</a>

**[Modify the following sections:]**

**8.4.5.4.15 CQICH Enhanced Allocation IE format**

**Table 302a—CQICH Enhanced allocation IE format**

<b>Syntax</b>	<b>Size</b>	<b>Note</b>
CQICH_Enhanced_Alloc_IE() {		
Extended-2 UIUC	4 bits	<a href="#">CQICH Enhance Alloc IE()=0x0900</a>
Length	4 8 bits	Length in bytes of following fields
.....		
}		

.....

**8.4.5.4.18 HO Anchor Active UL MAP IE**

.....

**Table 302e—HO Anchor Active UL MAP IE**

<b>Syntax</b>	<b>Size</b>	<b>Note</b>
HO Anchor Active UL MAP IE () {		
Extended-2 UIUC	4 bits	<a href="#">HO Anchor Active MAP IE() = 0x0901</a>
Length	4 8 bits	
.....		
}		

.....

**8.4.5.4.19 HO Active Anchor UL MAP IE**

.....

**Table 302f—HO Active Anchor UL MAP IE**

Syntax	Size	Note
HO Active Anchor UL MAP IE () {		
Extended-2 UIUC	4 bits	<a href="#">HO Active Anchor MAP IE() = 0x0902</a>
Length	4 8 bits	
.....		
}		

.....

**8.4.5.4.21 OFDMA Fast\_Ranging\_IE format**

.....

**Table 302h—OFDMA Fast\_Ranging\_IE format**

Syntax	Size	Note
Fast_Ranging_IE {		
Extended UIUC	4 bits	<a href="#">Fast_Ranging_IE() = 0x0609</a>
Length	4 bits	variable
.....		
}		

.....

**8.4.5.4.22 UL\_MAP\_Fast\_Tracking\_IE**

.....

**Table 302i—UL\_MAP\_Fast\_Tracking\_IE**

Syntax	Size	Note
UL_MAP_Fast_Tracking_IE() {		
Extended UIUC	4 bits	<a href="#">Fast Tracking IE() = 0x0307</a>
Length	4 bits	Variable
.....		
}		

.....

**8.4.5.3.28 AAS SDMA UL IE [format](#)**

.....

**Table 302r—AAS\_SDMA\_UL\_IE**

Syntax	Size	Note
AAS_SDMA_UL_IE() {		



Extended-2 UIUC	4 bits	<a href="#">AAS_SDMA_UL_IE = 0x0E</a>
Length	4 8 bits	<a href="#">variable</a>
.....		
}		

.....

**8.4.6.2.8.1 Channel sounding**

.....

**Table316a—UL\_sounding\_command\_IE()**

Syntax	Size	Note
UL_sounding_command_IE() {		
Extended-2 UIUC	4 bits	<a href="#">UL_sounding_command_IE()=0x0904</a>
Length	4 8 bits	variable
.....		
}		

.....

**4. References**

- [1] IEEE 802.16-2004 IEEE Standards for local and metropolitan area networks part 16: Air interface for fixed broadband wireless access systems
- [2] IEEE P802.16e/D7
- [3] C80216e-05/88r1
- [4] C80216e-05/160r1
- [5] C80216e-05/209