

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >	
Title	Network re-entry optimization	
Date Submitted	3-May-05	
Source(s)	Vladimir Yanover et al. Alvarion Ltd. 21 A Habarzel St. Ramat - Hahayal Tel - Aviv 69710 P.O. Box 13139, Tel-Aviv 61131, Israel Beomjoon Kim LGE Itzik Shahaar, Yigal Eliaspur Intel	Voice: +972-36457834 Fax: +972-36456222 mailto:vladimir.yanover@alvarion.com mailto:beom@lge.com mailto:yigal.eliaspur@intel.com mailto:itzik.shahar@intel.com
Re:	The document accompanies a comment submitted to 802.16e Sponsor Ballot	
Abstract	The document suggests changes in Handover section to make possible shortening of traffic interruption time	
Purpose	The document should be considered during resolution of 802.16e Sponsor Ballot comments	
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.	
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.	
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < http://ieee802.org/16/ipr/patents/policy.html >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < mailto:chair@wirelessman.org > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < http://ieee802.org/16/ipr/patents/notices >.	

Network re-entry optimization

Vladimir Yanover (Alvarion Ltd), Beomjoon Kim (LGE),
Itzik Shahr, Yigal Eliaspur (Intel), Hyoung Kyu Lim (Samsung)

1. Background

One of the most time consuming operations in Network Re-Entry is CDMA Initial ranging. In case ranging (as a part of Association) has been previously conducted between the MS and potential Target BS short time before the actual handover, results of that ranging are most probably still valid and therefore phase of CDMA ranging request / response may be skipped. The following explains sequence of events:

- MS performs Scanning with addition of ranging (i.e. Association) with respect to neighbor BS. During this procedure MS may estimate duration of validity interval for results of ranging (frequency, time and transmit power offsets). The MS supplies this estimation to Serving BS as a part of Scanning Report (this signaling is absent in 802.16e/D7).
- Shortly MS decides to initiate handover and provides in HO-REQ message estimated time interval for which results of ranging are still valid (needs clarification in 802.16e/D7)
- Serving BS negotiates with neighbor BS possibility of accommodation of the MS and timing of a dedicated allocation that will be provided for the MS to transmit RNG-REQ message during actual handover.
- Serving BS responds with BSHO-RSP message where provides information on that allocation (Action Time)
- MS sends HO-IND and leaves to Target BS
- Target BS allocates dedicated transmission opportunity for the MS to send RNG-REQ message

To provide for such procedure, definitions in HO section and formats of HO related messages should be slightly changes. There is a need also for some clarification.

2. Specific changes in 802.16e/D7

[Change at p.99, line 23]

Relative delay	8	—
}	8	
<u>TLV encoded information</u>	<u>Variable</u>	<u>Optional</u>
}	8	

[Add at p. 100 line 8]

[TLV tuples specified in 11.20 may be included into MOB_SCAN-REPORT message. Information provided by Nth TLV of this type is related to Nth BS listed in the message.](#)

[Change at p. 157 line 7]

When MOB_MSHO-REQ is sent by an MS, the MS may indicate one or more possible Target BS. When MOB_BSHO-REQ is sent by a BS, the BS may indicate one or more possible Target BS. MS may evaluate possible target BS through previously performed Scanning, ~~ranging~~, and Association activity.

Serving BS criteria for recommendation of target BS may include factors such as expected ~~target BS-MS QoS~~ performance at potential Target BS and MS QoS requirements. Serving BS may obtain expected ~~Target BS-QoS-MS~~ performance at potential Target BS indication through the exchange of backbone ~~messaging messages~~ with ~~Neighbor that~~ BS.

Dedicated allocation for transmission of RNG-REQ means that channel parameters learned by the MS during Scanning (Association) of that BS are considered valid during sufficient time and can be reused for actual Network Re-entry without preceding CDMA Ranging. This parameter is provided to the Serving BS over the backbone.

~~The MOB_MSHO-REQ message may also include an indication of the estimated time for performing the HO.~~ If Network Assisted HO supported flag is set to "1" in MOB_BSHO-REQ message, MS may perform a hand-over to any BS among the recommended BSs in MOB_BSHO-REQ (for which Action Time is specified) without notifying the serving BS of a selected target BS. As an acknowledgement to the MOB_BSHO-REQ message, the MS may send a MOB_HO-IND message with its target BSID set to "0x00000000".

When the serving BS, transmitted MOB_BSHO-REQ with ~~Network~~ Assisted HO supported flag = "1", receive MOB_HO-IND with target BS ID = "0x00000000", it may neglect target BS ID included in MOB_HO-IND message.

~~The serving BS may send messages to the recommended BSs even before receiving the MOB_HO-IND message in order to make the BSs to reserve Fast_UL_ranging_IE for the MS. This reserved UL resource may be released by a backbone message.~~

MS actual pursuit of hand-over to ~~one of BSs specified target BS~~ in MOB_BSHO-RSP is recommended, but not required. MS may ~~elect~~ decide to attempt hand-over to a different ~~target BS~~, a ~~target BS~~ that may or may not have been included in MOB_BSHO-RSP, ~~with the understanding that the different target BS may not receive notification of the pending hand-over from the serving BS over the backbone network prior to MS Initial Ranging of target BS.~~

If the MS signals rejection of serving BS instruction to HO through HO_IND_type field in the MOB_HOIND set value of 0b10 (HO reject option), the BS may reconfigure the target BS list and retransmit MOB_BSHO-RSP message including a new target BS list.

Serving BS may notify one or more target BS over the backbone network of MS intent to hand-over to target BS. Serving BS may also send MS information to target BS over the backbone ~~that can to~~ expedite hand-over.

Once MS sends MOB_HO-IND with option HO_IND_type = 0b00 indicating commitment to HO and intent to release the serving BS, the MS shall not be expected to monitor serving BS DL traffic after expiration of Resource retain timer.

[Change at p.105, line 31]

Action Time

For HO, this value is defined as number of frames until the Target BS allocates a ~~non-contention based ranging~~ dedicated transmission opportunity for either CDMA ranging or RNG-RSP message from the MSS using Fast Ranging IE. Dedicated allocation for transmission of RNG-

REQ means that channel parameters learned by the MS during Scanning (Association) of that BS stay valid and can be reused during actual Network Re-entry without preceding CDMA-based Initial Ranging. This parameter is decided by the Serving BS based on the information obtained from potential Target BSs over the backbone.

For SHO/FBSS, this is the time of update of Anchor BS and/or Active Set. A value of zero in this parameter signifies that this parameter should be ignored.

[Change at p.108, line 6]

Estimated HO start	8	The estimated HO time shall be the time for the recommended target BS
HMAC Tuple	168 (21 bytes)	See 11.1.2

[Change at p.108, line 23]

~~Estimated HO start~~

~~Estimated number of frames starting from the frame following the reception of the MOB_BSHO_RSP message until the HO may take place. A value of zero in this parameter signifies that this parameter should be ignored~~

[Change at p.114, line 35]

Action Time

For HO, this value is defined as number of frames until the Target BS allocates a ~~non-contention based ranging~~ dedicated transmission opportunity for RNG-REQ message to be transmitted by the MSS using Fast Ranging IE. Non-zero value of this parameter means that potential Target BS estimates that channel parameters learned by the MS during Association of that BS stay valid and can be reused during actual Network Re-entry without preceding CDMA-based Initial Ranging. This parameter is decided by the Serving BS based on the information obtained from potential Target BSs over the backbone.

For SHO/FBSS, this is the time of update of Anchor BS and/or Active Set. A value of zero in this parameter signifies that this parameter should be ignored.

[Add new section 11.20]

11.20. MOB_SCAN-REPORT message encodings

Name	Type	Length	Value
Ranging_Parameters_Validity_Time		1	Estimated number of frames starting from the frame following the reception of the MOB_SCAN-REPORT message, in which channel parameters learned by the MS during Association of specific BS stay valid and can be reused during future Network Re-entry to the BS without additional CDMA-based Initial Ranging. A value of zero in this parameter signifies that this parameter should be ignored