

Project	IEEE 802.16 Broadband Wireless Access Working Group < http://ieee802.org/16 >
Title	Bug Fix for SN reporting during FBSS and HO
Date Submitted	2005-06-14
Source(s)	Hang Zhang, Mo-Han Fong, Peiying Zhu, mhfong@nortelnetworks.com Wen Tong Nortel Networks
Re:	IEEE P802.16e/D8-2004
Abstract	This contribution provides bug fix for SN reporting during FBSS and HO
Purpose	Review and Adopt the suggested changes into P802.16e/D8
Notice	This document has been prepared to assist IEEE 802.16. It is offered as a basis for discussion and is not binding on the contributing individual(s) or organization(s). The material in this document is subject to change in form and content after further study. The contributor(s) reserve(s) the right to add, amend or withdraw material contained herein.
Release	The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.
Patent Policy and Procedures	The contributor is familiar with the IEEE 802.16 Patent Policy and Procedures < http://ieee802.org/16/ipr/patents/policy.html >, including the statement "IEEE standards may include the known use of patent(s), including patent applications, provided the IEEE receives assurance from the patent holder or applicant with respect to patents essential for compliance with both mandatory and optional portions of the standard." Early disclosure to the Working Group of patent information that might be relevant to the standard is essential to reduce the possibility for delays in the development process and increase the likelihood that the draft publication will be approved for publication. Please notify the Chair < mailto:chair@wirelessman.org > as early as possible, in written or electronic form, if patented technology (or technology under patent application) might be incorporated into a draft standard being developed within the IEEE 802.16 Working Group. The Chair will disclose this notification via the IEEE 802.16 web site < http://ieee802.org/16/ipr/patents/notices >.

1 Introduction

In p802.16e/D8, for the MS-assisted coordination of DL transmission during FBSS (6.3.21.3.5) and HO (6.3.21.3.5), a MS may send SN Report MAC header(s) to the new anchor or target BS to keep the continuity of DL data flow transmission without depending backhaul communication.

However, if the SN report MAC header(s) are lost, there is no means defined in the standard for the new anchor/target BS to request the SN report from the MS. This contribution defines “SN request” extended subheader to enable a new anchor/target to request the MS to send the SN report MAC header.

2 Proposed text change

[Modify Table 13b – Description of extended sunheaders as the following]:

ESF bit	Name	Size(bytes)	Description
0 (LSB)	SDU SN extended sunheader	1	See 6.3.2.2.7.1
1	DL Sleep control extended subheader	3	See 6.3.2.2.7.2
2	Feedabck request extended subheader	3	See 6.3.2.2.7.3
3	MIMO mode feedback extended subheader	1	See 6.3.2.2.7.4
4	UL Tx power report extended subheader	1	See 6.3.2.2.7.5
5	Mini-Feedback extended subheader	2	See 6.3.2.2.7.6
6	<u>SN request extended subheader</u>	<u>1</u>	<u>See 6.3.2.2.7.7</u>
Bit # 6 127	<i>Reserved</i>		

[Add a new section- 6.3.2.2.7.7 before Section 6.3.2.3 MAC Management messages]

6.3.2.2.7.7 SN request extended subheader

The SN request extended subheader is sent by the BS to request the MS to send the SN report header on the assigned UL region. The fields of the SN request extended subheader are defined in Table 13i.

Table 13i – Description of SN request extended sunheader.

<u>Name</u>	<u>Size (bits)</u>	<u>Description</u>
<u>SN report indication</u>	<u>2</u>	<u>Bit #0: set to 1 to request transmission of the first SN report header</u> <u>Bit #1: set to 1 to request transmission of the second SN report header</u>
<u>Reserved</u>	<u>6</u>	<u>Set to zero</u>

[Modify the paragraph on page 190, lines 41-47 in Section 6.3.21.3.5.1]

— At the expiration of the Anchor switch timer, the new anchor BS should assign UL resource through UL-MAP_IE for the MS to transmit the LSB of the sequence number(s) of ARQ block or virtual MAC SDU on the SN Report MAC header (6.3.2.1.6). At the expiration of the Anchor switch timer, the MS subsequently shall send up to two SN Report MAC headers (with RqstID = 0 and RqstID = 1 as described in 6.3.2.1.2.1.7) that include the next ARQ Block (or virtual MAC SDU) sequence number that it is expecting for each of its connections that have SN feedback enabled. The MS shall send the sequence number in numerical ascending order of the values of the CIDs values. The new anchor BS may send the SN request extended subheader to explicitly request a MS to send additional SN report header. After receiving the SN request extended subheader, the MS shall send the requested SN report header. The new anchor BS may assign UL resource through UL-MAP_IE for the MS to send the additional SN report header.

[Modify the paragraph on page 191, lines 27-34 in Section 6.3.21.3.5.2]

Upon completion of HO and NW re-entry, the Target BS (now new Serving BS) should assign UL resource

through UL-MAP_IE for the MS to transmit the LSB of the sequence number(s) of ARQ block or virtual MAC SDU on the SN Report MAC header (6.3.2.1.5). At the expiration of the Anchor switch timer, ~~the MS subsequently~~ shall send up to two SN Report MAC headers (with RqstID = 0 and RqstID = 1 as described in 6.3.2.1.2.1.7) that include the next ARQ Block (or virtual MAC SDU) sequence number that it is expecting for each of its connections that have SN feedback enabled. The MS shall send the sequence number in numerical ascending order of the values of the CIDs values. The new anchor BS may send the SN request extended subheader to explicitly request a MS to send additional SN report header. After receiving the SN request extended subheader, the MS shall send the requested SN report header. The new anchor BS may assign UL resource through UL-MAP_IE for the MS to send the additional SN report header.