

|                |  |  |
|----------------|--|--|
| Project        | <b>IEEE 802.16 Broadband Wireless Access Working Group</b> < <a href="http://ieee802.org/16">http://ieee802.org/16</a> >   |  |
| Title          | <b>Prioritized Uplink Bandwidth Allocation</b>   |  |
| Date Submitted | <b>2008-09-10</b>  |  |
| Source(s)      | Yerang Hur, Hyung-Joon Jeon,<br>Seunghyun Lee, Jaehyeong Kim<br><br>POSDATA  | Voice: +1-408-986-1143<br>E-mail: <a href="mailto:yehur@posdata-usa.com">yehur@posdata-usa.com</a><br><a href="mailto:hjjun@posdata.co.kr">hjjun@posdata.co.kr</a><br><a href="mailto:huhuya@posdata.co.kr">huhuya@posdata.co.kr</a><br><a href="mailto:jaekim@posdata.co.kr">jaekim@posdata.co.kr</a> |
| Re:            | MAC: Data Plane; in response to the TGM Call from Contributions and Comments 802.16m-08/033 for Session 57   |  |
| Abstract       | Bandwidth allocation providing the usage of uplink bandwidth grants  |  |
| Purpose        | To discuss and adopt the proposed text in the IEEE 802.16m SDD   |  |
| Notice         | <i>This document does not represent the agreed views of the IEEE 802.16 Working Group or any of its subgroups. It represents only the views of the participants listed in the "Source(s)" field above. It is offered as a basis for discussion. It is not binding on the contributor(s), who reserve(s) the right to add, amend or withdraw material contained herein.</i>   |  |
| Release        | The contributor grants a free, irrevocable license to the IEEE to incorporate material contained in this contribution, and any modifications thereof, in the creation of an IEEE Standards publication; to copyright in the IEEE's name any IEEE Standards publication even though it may include portions of this contribution; and at the IEEE's sole discretion to permit others to reproduce in whole or in part the resulting IEEE Standards publication. The contributor also acknowledges and accepts that this contribution may be made public by IEEE 802.16.   |  |
| Patent Policy  | The contributor is familiar with the IEEE-SA Patent Policy and Procedures:<br>< <a href="http://standards.ieee.org/guides/bylaws/sect6-7.html#6">http://standards.ieee.org/guides/bylaws/sect6-7.html#6</a> > and<br>< <a href="http://standards.ieee.org/guides/opman/sect6.html#6.3">http://standards.ieee.org/guides/opman/sect6.html#6.3</a> >.<br>Further information is located at < <a href="http://standards.ieee.org/board/pat/pat-material.html">http://standards.ieee.org/board/pat/pat-material.html</a> > and<br>< <a href="http://standards.ieee.org/board/pat">http://standards.ieee.org/board/pat</a> >. |  |

# Prioritized Uplink Bandwidth Allocation

*Yerang Hur, Hyung-Joon Jeon, Seunghyun Lee, Jaehyoung Kim*  
 POSDATA

## 1. Introduction

In legacy systems, the BS grants the uplink bandwidth addressed by the MS Basic CID for the unicast bandwidth requests. This helps the MS utilize its uplink scheduling algorithm when the grant is actually used, however, it can cause a mismatch between the expectation of the BS when the bandwidth is granted and the execution of the MS when the bandwidth is utilized. For example, when the BS expects the ARQ feedback for the connections with ARQ enabled, if the MS delays the ARQ feedback due to uplink traffic, the overall system performance can be degraded.

We propose that the BS be able to classify the grants and indicate the purpose of its grant when the bandwidth is allocated. If the purpose of the grant is provided by the BS, the MS shall use such grants for the purpose indicated by the BS.

## 2. Proposed Text for the 802.16m SDD

----- Start of the proposed text -----

### 10.x Data Plane

#### 10.x.y Bandwidth allocation

Each MS requests uplink bandwidth on a connection basis. For the bandwidth requested by the MS, the uplink grant can be identified by Basic CID of the MS to be backward compatible with the legacy MS/BS, however, the BS may classify the grants using a field for referencing the specific connection to indicate the purpose of the grant the BS provides. In such a case, the BS will identify which grant is for the management connection and which grant is for the transport connection. For each category, the BS may provide further details of the usage of the uplink grant. If the BS identifies a grant for the specific connection, the MS shall use granted bandwidth for the identified connection – management connection or transport connection.

–

----- End of the proposed text -----

## References

- [1] IEEE 802.16m-08/003r4. The Draft IEEE 802.16m System Description Document, July 2008.
- [2] IEEE P802.16Rev2/D6. Draft Standard for Local and Metropolitan Area Networks Part 16: Air Interface for Broadband Wireless Access Systems, July 2008.