2003-07-15	Project	IEEE 802.20 Working Group on Mobile Broadband Wireless Access < <u>http://grouper.ieee.org/groups/802/20/></u> Market Requirements for IEEE 802.20		IEEE 802.20-03/65
	Title			
	Date Submitted	2003-7-15		
	Source(s)	James F. Mollenauer	Voice: 617-244-0077	
		Technical Strategy Associates	Email: jmollenauer@technicalstrategy.com	
		Joseph R. Cleveland	Voice: 972-761-7981	
		Samsung Telecommunications America	Fax: 972-761-7909 Email: <u>jclevela@sta.samsung.com</u>	
		Paul Odlyzko	Voice: 847-538-5234 Fax: 847-576-0892	
		Motorola Inc.	Email: <u>Paul.Odlyzko@motorola.com</u>	
	Re:	MBWA Call for Contributions		
	Abstract	To be successful, 802.20 must prov Existing systems and techniques we performance will be discussed.		
	Purpose	To facilitate discussion of the 802.2		
	Notice	This document has been prepared to assist discussion and is not binding on the contri document is subject to change in form and to add, amend or withdraw material contai	ıt	
	Release	The contributor grants a free, irrevocable l contribution, and any modifications thereo the IEEE's name any IEEE Standards pub and at the IEEE's sole discretion to permit Standards publication. The contributor also public by IEEE 802.20.	in	
	Patent Policy	The contributor is familiar with IEEE pate Board Operations Manual < <u>http://standard</u> Patent Issues During IEEE Standards Dev	nt policy, as outlined in Section 6.3 of the IEEE-SA Standards <u>s.ieee.org/guides/opman/sect6.html#6.3</u> > and in <i>Understanding</i> elopment < <u>http://standards.ieee.org/board/pat/guide.html</u> >.	

Market Requirements for IEEE 802.20

July 2003

James F. Mollenauer Technical Strategy Associates

Joseph R. Cleveland Samsung Telecommunications America

> Paul Odlyzko Motorola Inc.

The Most Effective Requirements...

....Are simply stated

Emperor Nero, to his banquet entertainers

"Astonish me"

President Kennedy, to NASA

"A man on the moon by the end of the decade"

Goal for 802.20

To be the technology of choice for mobile data

to achieve this, we must:

- Go beyond what 3G or 3G enhanced can do
 - Higher in data rate
 - Better in dealing with high-speed mobility
 - Simpler in interfacing with IP land-line networks
 - Faster in handoff
- Also, be better than 802.16e

Otherwise, why bother?

The Classic Mistake

- Assuming that our next-generation system will be better than the competition
 - Just because it's better than their last one
 - They are working on their next generation, too

Consider ATM vs. Ethernet: 25 & 155 Mbps vs. 10 Mbps--Ethernet moved to 100 Mbps and wiped out premises ATM

- To succeed, we need to be have higher throughput than existing systems
 - And higher than their next (enhanced) version

The Current State of the Art

We need to beat these numbers by a significant margin:

	Channel width, MHz	Data rate, Mbps	
TD-CDMA (Rel. '99)	5	FWD	REV
Peak rate (no uplink)		5	-
Peak rate (3:1 TDD split)		~3.4	~1.1
Avg throughput per sector		~1.5	~0.9
TD-CDMA (Rel. 5)	5	FWD	REV
Sector throughput		~1.9	
EVDO	5	FWD	REV
Peak		2.4	0.153
Throughput		0.7	
Throughput @ 3 km/h, 1 Rayleigh path 1.2			
Enhanced DO (proposed)	5	FWD	REV
Peak		~3	~1.2
IEEE 802.16a (non-mobile)	20		
Peak (3:1 TDD split)		60	10

What is our Sustainable Technical Edge?

- Packets?
 - Most new systems use packets
- More complex modulation ?
 - All current systems have discovered the laws of physics
- CDMA?
 - 2G, 2.5G, and 3G have CDMA
- OFDM?
 - 802.16a has that
- Narrow channels to fit existing allocations?
 - New spectrum is unlikely to require narrow channels
- Maybe it's complex antennas
 - 802.16 and even 802.11 are thinking about smart antennas
- Maybe it's our simple IP-based protocol stack
 - Nothing prevents 802.16 from using the same stack

Bottom line: if there is no single "killer" advantage, then we have to tune our system better. The devil is in the details.

The Tools We Have

• Simple protocol stack

- Conformance to normal data practice
- Voice and video support via QoS scheduling

Smart antennas

- Great improvements in rate are possible
- But the competition can add this to existing standards
- Targeted primarily at mobile users
 - Not an add-on
 - Power consumption considered from the start
- Consistency across different channel sizes
 - Easy roaming for the user and system migration for the operator
- Adaptive modulation and coding
 - Optimize for varying signal strength and different multipath environments
- Smart scheduling
 - Predict user's nulls and avoid them
 - Identify user clustering