

IEEE 802.3 Criteria for Standards Development (CSD)

The IEEE 802 Criteria for Standards Development (CSD) are defined in Clause 14 of the IEEE 802 LAN/MAN Standards Committee (LMSC) Operations Manual. The criteria include project process requirements (“Managed Objects”) and 5 Criteria (5C) requirements. The 5C are supplemented by subclause 7.2 ‘Five Criteria’ of the ‘Operating Rules of IEEE Project 802 Working Group 802.3, CSMA/CD LANs’.

The following are the CSD Responses in relation to the IEEE P802.3c? – **IEEE 802.3 Next-generation 200 Gb/s and 400 Gb/s MMF PHYs Study Group** PAR

Items required by the IEEE 802 CSD are shown in Black text and supplementary items required by IEEE 802.3 are shown in **blue** text.

Managed Objects

Describe the plan for developing a definition of managed objects. The plan shall specify one of the following:

- a) The definitions will be part of this project.
 - b) The definitions will be part of a different project and provide the plan for that project or anticipated future project.
 - c) The definitions will not be developed and explain why such definitions are not needed.
- The definition of protocol independent managed objects will be part of this project.
 - In addition, it is expected that the protocol-specific definition of managed objects will be added in a future amendment to an IEEE 802.3 Standard for Management.

Coexistence

A WG proposing a wireless project shall demonstrate coexistence through the preparation of a Coexistence Assurance (CA) document unless it is not applicable.

- a) **Will the WG create a CA document as part of the WG balloting process as described in Clause 13?**
 - b) **If not, explain why the CA document is not applicable**
-
- A CA document is not applicable because the proposed project is not a wireless project.

Broad Market Potential

Each proposed IEEE 802 LMSC standard shall have broad market potential. At a minimum, address the following areas:

- a) **Broad sets of applicability.**
- b) **Multiple vendors and numerous users.**

- **Broad Sets of Applicability:**
 - The rate of deployment of MMF continues to grow both globally and in North America, producing a growing installed base of both OM3 & OM4 1-pair and 4-pair cable.
 - Recent market evidence shows that higher speeds over both duplex and parallel MMF cable have been needed in the first year that new switch speeds enter the market, including the rapid uptake of 100GBASE-SR4 in QSFP.
 - Market applications for low-cost, high density, short-reach MMF links at higher speeds include switch-to-switch, server-to-switch and switch-to-router connections in cloud and large enterprise data centers and CO transformation at service providers.
 - It has been shown that the electrical specifications for 50 Gb/s lanes from 802.3bs can be re-used, such that PMDs from this project can share the same ports.
- **Standardizing lower cost applications for MMF facilitates upgrades and enlarges Ethernet market.**
- **Multiple vendors and numerous users:**
 - 55 individuals from 38 companies were Supporters for Call For Interest (CFI), including cloud and enterprise end-users. At the CFI, 56 individuals from 24 companies indicated participation in this project.
 - It is anticipated that there will be sufficient participation to effectively complete the standardization process including representatives from end-users, equipment manufacturers and component suppliers.

Compatibility

Each proposed IEEE 802 LMSC standard should be in conformance with IEEE Std 802, IEEE 802.1AC, and IEEE 802.1Q. If any variances in conformance emerge, they shall be thoroughly disclosed and reviewed with IEEE 802.1 WG prior to submitting a PAR to the Sponsor.

- a) Will the proposed standard comply with IEEE Std 802, IEEE Std 802.1AC and IEEE Std 802.1Q?
 - b) If the answer to a) is “no”, supply the response from the IEEE 802.1 WG.
 - c) **Compatibility with IEEE Std 802.3**
 - d) **Conformance with the IEEE Std 802.3 MAC**
 - e) **Managed object definitions compatible with SNMP**
- As a PHY amendment to IEEE Std 802.3, the proposed project will remain in conformance with IEEE Std 802, IEEE Std 802.1AC, and IEEE Std 802.1Q.
 - As was the case in previous IEEE Std 802.3 amendments, new physical layers will be defined for 200 Gb/s and 400 Gb/s operation.
 - The proposed amendment will conform to the full-duplex operating mode of the IEEE 802.3 MAC.
 - The project will include a protocol independent specification of managed objects. In addition, it is expected that the protocol-specific definition of managed objects will be added in a future amendment to an IEEE 802.3 Standard for Management.

Distinct Identity

Each proposed IEEE 802 LMSC standard shall provide evidence of a distinct identity. Identify standards and standards projects with similar scopes and for each one describe why the proposed project is substantially different.

Substantially different from other IEEE 802.3 specifications / solutions.

- The proposed amendment will be the first IEEE 802.3 standard defining operation at 200 Gb/s and 400 Gb/s over fewer than 4 pairs and 16 pairs, respectively, of multimode fiber physical media.

Technical Feasibility

Each proposed IEEE 802 LMSC standard shall provide evidence that the project is technically feasible within the time frame of the project. At a minimum, address the following items to demonstrate technical feasibility:

- a) Demonstrated system feasibility.
 - b) Proven similar technology via testing, modeling, simulation, etc.
 - c) Confidence in reliability.
- The principle of building equipment that supports IEEE 802.3 networks operating at different Ethernet rates has been amply demonstrated by a broad set of product offerings.
 - The proposed project will build on the array of Ethernet component and system design experience, and the broad knowledge base of Ethernet network operation
 - Component vendors, including PHY vendors, cabling vendors and systems vendors have presented data on the feasibility of the necessary components for this project. Proposals which leverage existing technologies have been provided.
 - Electrical interfaces sufficient to support this project have already been standardized in IEEE P802.3bs.
 - Single-lane 50 Gb/s PHY for operation over MMF are under development for other Ethernet projects (IEEE P802.3cd) and technical feasibility has been established at 850 nm.
 - Multiple experimental demonstrations of technical feasibility of combining wavelength division multiplexing with 50 Gb/s PAM4 over MMF can be found in published literature. Both 40 Gb/s & 100 Gb/s VCSEL modules based on both two and four wavelengths are in production.
 - The reliability of Ethernet components and systems can be projected in the target environments with a high degree of confidence.

Economic Feasibility

Each proposed IEEE 802 LMSC standard shall provide evidence of economic feasibility. Demonstrate, as far as can reasonably be estimated, the economic feasibility of the proposed project for its intended applications.

Among the areas that may be addressed in the cost for performance analysis are the following:

- a) **Balanced costs (infrastructure versus attached stations).**
 - b) **Known cost factors.**
 - c) **Consideration of installation costs.**
 - d) **Consideration of operational costs (e.g., energy consumption).**
 - e) **Other areas, as appropriate.**
- The cost factors for Ethernet components and systems are well known. Re-use of common technologies from prior Ethernet projects will allow economies of scale to reduce cost.
 - In consideration of installation costs, the project is expected to use proven and familiar MMF media.
 - In consideration of balancing costs, it is anticipated the project will examine alternatives that trade off between PMD complexity and the number of fibers in order to maintain a reasonable balance between these two costs.
 - One or more PHYs will be specified which operate over fewer fiber pairs than currently defined in IEEE 802.3 standards and projects for the same speed(s), reducing infrastructure costs.
 - One or more PHYs will be specified which enable operation over MMF cables in the installed base.
 - Adding wavelengths & PAM4 to MMF modules preserves the historical low cost & low power advantages associated with VCSEL-based technology.
 - Network design, installation and maintenance costs are minimized by preserving network architecture, management, and software.
 - Energy Efficient Ethernet will reduce the operational costs and the environmental footprint.