

RF Spectrum Ad Hoc – Minutes March 5, 2013

Provided the IEEE-SA Patent Policy link. Everyone on the call was familiar with the patent policy.

- <https://development.standards.ieee.org/myproject/Public/mytools/mob/slideset.pdf>

Everyone on the call was familiar with the IEEE patent policy.

Straw Polls (Duane Remein)

Straw Poll #3a

I support FDD downstream Frequency band edges of 108 MHz & 1200 MHz

Yes 5

No 5

Straw Poll #4 (People can vote for as many options as they like)

The granularity for setting the location and width of DS Exclusion Bands should be

2 MHz	7
1 MHz	9
500 kHz	4
200 kHz	0
50 kHz	0
25 kHz	0
Other	None

Straw Poll #4b

The minimum contiguous DS spectrum should be 24 MHz

Yes 10

No 0

Straw Poll #5 (People can vote for as many categories as they like)

I would prefer to set internal exclusion bands by:

- A) Specifying start location and width
- B) Specifying start location and end location
- C) Specifying center frequency and width
- D) Abstain

A 5

B 7

C 5

D 1

Attendance

Person	Affiliation
Edward Boyd	Broadcom

Alan Brown	Aurora
Hesham ElBakoury	Huawei
Jim Farmer	Aurora Networks
Robert Howald	Motorola
Christian Pietsch	Qualcomm
Bill Powell	Alcatel Lucent
Saif Rahman	Comcast
Duane Remein	Huawei
Steve Shellhammer	Qualcomm