

TDD sub-Task Force – Minutes July 8, 2013

Provided the IEEE-SA Patent Policy link. Everyone on the call was familiar with the patent policy.

- <https://development.standards.ieee.org/myproject/Public/mytools/mob/slideset.pdf>

Everyone on the call was familiar with the IEEE patent policy.

Reviewed eStraw Polls

- No new votes from the previous week

Straw Poll

The standard shall support provisioning of the TDD Guard Time (in μ s) for the following values, 1.25, 2.5, 3.75, 5.0, 6.25, ... TBD

Yes 9
No 0

Information about the TDD downstream time window
10 ms \approx 200 symbols (4k FFT) and 100 symbols (8K FFT)
For most applications 1 ms is the largest value required.
32 bit field of TQs is 68.72 seconds

Straw Poll

The standard shall support provisioning of the TDD Downstream Time window measured in multiples of the symbol plus cyclic prefix duration. The standard shall support from 1 symbol plus cyclic prefix up to 255 symbols plus cyclic prefix for 4k FFT, and up to 127 symbols plus cyclic prefix for 8k FFT.

Yes 3
No 1
Abstain 5

Attendance

Person	Affiliation
Marek Hajduczenia	ZTE
Yan Kezhou	Xidian University
Curtis Knittle	CableLabs
Michael Peters	Sumitomo Electric
Bill Powell	Alcatel Lucent
Saif Rahman	Comcast
Duane Remein	Huawei
Steve Shellhammer	Qualcomm
Joe Solomon	Comcast
Tom Staniec	Cohere Communications