

Meeting agenda for 8 July 2020

Topic	Comments
C2M TP4/TP4a parameters (direction only)	11060, 107, 108, 109, 115, 116, 130, 135, 175,176, 177, 178, 228, 191, 192, 193, 194, 196, 197, 211, 212, 215, 238, hidaka_3ck_01_0720, ghiasi_3ck_02_0720, ran_3ck_01a_0720
C2M EW/ESMW	[*231, 173]
C2C TX linear fit pulse, reference	[166] brown_3ck_02_0720 slide 8
C2C RX IT Np	[11156] brown_3ck_02_0720 slide 2
C2C test channel RL	[*11078, 170] brown_3ck_02_0720 slide 3
C2C TX jitter	[168] brown_3ck_02_0720 slide 4
C2C TX RSSDFE4	[171] brown_3ck_02_0720 slide 5
KR TX SNDR Np value	[155] brown_3ck_02_0720 slide 9
KR channel differential to CM conversion loss	[11039] wu_3ck_01_0720, brown_3ck_01_0720 slide 7
KR/C2C TX AC CM noise	[*28, 54, 205] [29] wu_3ck_01_0720, brown_3ck_01_0720 slides 3-6
C2C TX EQ FB	[11059]
RLCC	208, 207, brown_3ck_01_0720 slide 8