

Maximum distance for 400GBASE-LR4

Peter Stassar, Huawei
Pete Anslow, Ciena

IEEE P802.3cu Task Force meeting, Indianapolis, 9 September 2019

Introduction

- This presentation provides further considerations on maximum distance for proposed baseline specifications for the 400GBASE-LR4 optical interface specification.
- Over the past meetings a lot of information has been made available with test results of TDECQ, SECQ and TDECQ minus SECQ over the relevant dispersion/wavelength ranges proposed for 400GBASE-LR4
- The proposed and extensively discussed options are a choice between operating the 4 transmitter wavelengths on a 20 nm spaced CWDM grid or on an 800 GHz spaced DWDM grid (also known as LAN-WDM).

Relevant straw poll Vienna meeting July 2019

Straw Poll #3:

If further technical analysis doesn't resolve option A, I would prefer the following option as a way to close the 400G 10km baseline: [A: Further technical analysis to select a single CWDM or LAN-WDM based baseline]

- B. CWDM baseline using a restricted fiber approach for 10km and a reduced reach for worst case fiber.
- C. Additional objective so both a CWDM and LAN-WDM baselines can be adopted
- D. Modify 10km objective to shorter reach or to be based on loss budget
- E. Remove 400G 10km objective

Vote for one


Results: B) 3 C) 7 D) 33 E) 0

- Straw poll #3 indicated that if option A was not resolved, there was a strong preference for option D, either modifying the distance to less than 10 km or a budget-based objective.
- Whichever will be chosen, it will be necessary to define a maximum dispersion limited distance in the specification.

Available test results


- Over the past meetings a lot of test results on TDECQ and SECQ versus chromatic dispersion have been made available from a variety of sources.
- As discussed in [anslow_3cu_02a_0519](#), Salt Lake City meeting, May 2019, the two most important curves are:
 - TDECQ versus chromatic dispersion
 - TDECQ – SECQ versus chromatic dispersion
- The following 2 slides show updated versions of those curves, including most recent test results.

TDECQ vs dispersion



- △ [johnson optx 01 0319](#) un-optimised
- ▲ [johnson optx 01 0319](#) optimised
- [yu optx 01a 0319](#)
- [yu optx 01a 0319](#) predicted
- [lewis cu adhoc 041719](#)
- ◇ [schube 3cu 01 0519](#) Si Ph (CD pen)
- X [mazzini 3cu adhoc 082119](#) Si Ph
- 100G Lambda MSA
- ↑ 100G Lambda MSA excessive
- -40 to 15 ps/nm with 3.9 dB penalty

TDECQ – SECQ vs dispersion



- △ [johnson_optx_01_0319](#) un-optimised
- ▲ [johnson_optx_01_0319](#) optimised
- [yu_optx_01a_0319](#)
- P ● [yu_optx_01a_0319](#) predicted
- [lewis_cu_adhoc_041719](#)
- ◇ [schube_3cu_01_0519](#) Si Ph (CD pen)
- × [mazzini_3cu_adhoc_082119](#) Si Ph
- 100G Lambda MSA
- ▲ 100G Lambda MSA excessive
- -47 to 20 ps/nm with 2.5 dB penalty

Observations

- The results for TDCEQ versus chromatic dispersion are quite scattered
- The results for TDECQ – SECQ are much better correlated and are quite consistent
 - These also confirm that it would be prudent to keep TDECQ – SECQ below 2 – 2.5 dB, because for higher penalties the penalty could significantly increase for small increases of chromatic dispersion
 - Because of testing at room temperature one could look at the dispersion levels for 2 dB penalty, yielding limits of -47 ps/nm and 20 ps/nm
 - For worst case fiber: ~ 7.9 km (@ -47 ps/nm) and ~ 6 km (@ 20ps/nm)
 - Thus positive dispersion limit is more restrictive than negative dispersion
 - Reducing lambda range of the 1331 nm channel to 1324.5 – 1330.5 nm, then the maximum distance increases from ~ 6 km to ~ 7.3 km.


Observations, continued

- Looking again at the results for TDCEQ versus chromatic dispersion in a similar way as for TDECQ – SECQ
 - For the proposed 3.9 dB limit, a dispersion window of -40 to $+15$ ps/nm could be assumed.
 - -40 ps/nm translates to a maximum distance of ~ 6.7 km and 15 ps/nm to ~ 4.5 km.
 - If we apply the same restricted CWDM wavelength of $1324.5 - 1330.5$ nm then the maximum distance increases to ~ 5.5 km.
- The TDECQ – SECQ results suggest maximum dispersion limited distances of $6 - 7$ km for CWDM based transmitters, allowing both SiP and EML based transmitters.

Considerations


- The philosophy behind TDECQ for PAM4 based transmitters (as TDP for NRZ based transmitters) is to allow trade-off between transmitter distortion and penalties due to chromatic dispersion.
- Since the consideration of TDECQ values in the range of 3.9 dB (higher than current in-force values of up to 3.4 dB), transmitters causing TDECQ – SECQ penalties in excess of 2.5 dB, have become likely, which should be avoided.
- Therefore it would not be overly conservative to introduce an additional parameter TDECQ – SECQ, with a strawman limit of 2.5 dB for this specific interface.
- If P802.3cu favours a CWDM solution rather than an 800 GHz spaced solution, then a proposed strawman maximum dispersion limited distance would be 7 km.
- For worst case G.652 fiber this would imply chromatic dispersion limits of –41 to +23 ps/nm for worst case CWDM grid, as shown on next two slides

TDECQ vs dispersion



- △ [johnson_optx_01_0319](#) un-optimised
- ▲ [johnson_optx_01_0319](#) optimised
- [yu_optx_01a_0319](#)
- P● [yu_optx_01a_0319](#) predicted
- [lewis_cu_adhoc_041719](#)
- ◇ [schube_3cu_01_0519](#) Si Ph (CD pen)
- X [mazzini_3cu_adhoc_082119](#) Si Ph
- 100G Lambda MSA
- ▲ 100G Lambda MSA excessive
- CWDM grid 10 km
- - - - CWDM grid 7 km

TDECQ – SECQ vs dispersion



- △ [johnson optx 01 0319](#) un-optimised
- ▲ [johnson optx 01 0319](#) optimised
- [yu optx 01a 0319](#)
- P● [yu optx 01a 0319](#) predicted
- [lewis cu adhoc 041719](#)
- ◇ [schube 3cu 01 0519](#) Si Ph (CD pen)
- X [mazzini 3cu adhoc 082119](#) Si Ph
- 100G Lambda MSA
- ▲ 100G Lambda MSA excessive
- CWDM grid 10 km
- CWDM grid 7 km

Proposals

- Perform a straw poll on the preference for:
 - Option A: 800 GHz based configuration with distances up to 10 km.
 - Option B: CWDM based configuration with distances up to 7 km.
- Introduce an additional parameter TDECQ – SECQ, with a strawman limit of 2.5 dB.

Thanks!