

IEEE P802.3cw D2.3 400 Gb/s over DWDM systems 3rd Working Group recirculation ballot comments

CI 155 SC 155 P 42 L 4 # 17

Dawe, Piers Nvidia

Comment Type TR Comment Status R

D2.1 comment 278: this project is too slow, and has descended to only 25 comments from only four commenters when there is a lot to fix still. The moment for doing this spec in 802.3 has passed, it doesn't add significantly to 400ZR, it lacks momentum and there are not enough willing participants in P802.3cw to justify it.

SuggestedRemedy

Cancel this project.
Encourage those interested to feed their learnings into OIF's "400ZR" maintenance.
Re-use relevant parts of the draft in P802.3dj when the time comes.

Response Response Status U

REJECT.

As noted by commentor, this issue was previously raised in D2.1 comment #278 and there was no consensus to cancel the project.

https://www.ieee802.org/3/cw/comments/D2p1/8023cw_D2p1_comments_final_by_ID_230619.pdf.

Per Motion #1 from https://www.ieee802.org/3/cw/public/23_06/minutes_3cw_2306_approved.pdf the modified project timeline was approved. See https://www.ieee802.org/3/cw/proj_doc/timeline_3cw_230608.pdf

This plan of action was presented to the 802.3 WG at the July 2023 Plenary. See Slide #3 of https://www.ieee802.org/3/minutes/jul23/0723_3cw_open_report.pdf

There is no consensus to change this plan of action at this time.

CI 155 SC 155 P 42 L 4 # 18

Dawe, Piers Nvidia

Comment Type TR Comment Status R

D2.1 comment 281: this PCS/PMA is way too complicated for just a "directive" specification. We need examples, as in Annex 91A, RS-FEC codeword examples, or Annex 76A, FEC Encoding example, or the OIF test vectors for 400ZR.

SuggestedRemedy

Publish examples of e.g. FEC and other blocks before and after coding. Smallish ones can go in the document, all can be uploaded to the directory that IEEE provides for these things.
If no-one does the work needed, cancel the project.

Response Response Status U

REJECT.

As noted by commentor, this issue was previously raised in D2.1 comment #281 which was rejected with the response "No data was provided for the editors to be able to implement this change. Contributions of such material would be welcomed."

CI 156 SC 156.9 P 102 L 13 # 20

Dawe, Piers Nvidia

Comment Type TR Comment Status R

D2.1 comment 285, optical parameters are inadequately defined.

SuggestedRemedy

Review the 400ZR maintenance projects' activities for corrections and improvements and changes that would apply to this draft, including to EVM.

Response Response Status U

REJECT.

A detailed suggested remedy containing an editor's instruction on how to modify the draft was not provided.

IEEE P802.3cw D2.3 400 Gb/s over DWDM systems 3rd Working Group recirculation ballot comments

CI 156 SC 156.9.6 P 105 L 8 # 25

Dawe, Piers

Nvidia

Comment Type TR Comment Status R

D2.1 comments 285, optical parameters are inadequately defined, and 286, define frequency noise and write down how it may be measured. For example, it is not stated what is measured in Hz². It is not stated adequately what to do with the two sidebands. The table column header says one-sided, but that's the wrong place to attempt a definition, and does it mean one folds both sidebands together, explicitly or as in a self-homodyne measurement, or takes the worst of the two, or what? It is not stated whether +ve and -ve frequencies are taken into account or just +ve. It seems that this extremely arcane term is more of a concept, or at most a laser modeller's input parameter, than an observable output, so it is not clear that it is the right thing to be specifying, as it may not be measurable.

SuggestedRemedy

Define and specify something relevant and measurable, clearly and completely, with an explanation of how it may be measured and what instrument may be used, and references as necessary. Probably an example is needed. Phase noise is a better-known parameter with some literature, although it needs careful definition to avoid ambiguity. See e.g. IEC 61280-1-3, Fibre optic communication subsystem test procedures--Part 1-3: General communication subsystems--Central wavelength and spectral width measurement for an example of a measurement spec that can be referred to in a definition.

Response Response Status U

REJECT.

No consensus to make a change.

The CRG expressed interest in contributions related to laser frequency noise.

Contributions are encouraged.

CI 156 SC 156.9.6 P 105 L 9 # 26

Dawe, Piers

Nvidia

Comment Type TR Comment Status R

D2.1 comments 285, optical parameters are inadequately defined, and 286, define frequency noise. This text says "The mask frequencies are relative to the laser center frequency from *less than* 100 Hz to half the signaling rate", Table 156-13 has 10² to 10⁹ Hz, and Figure 156-7 shows 10² to something indeterminate above 10¹⁰.

SuggestedRemedy

Reconcile the frequency range for this spec, with clear and consistent lower and upper frequencies. For example, 100 Hz to 59.84375/2 = 29.921875 GHz, or 100 Hz to 30 GHz, or 100 Hz to 30.8 GHz to match the transmit spectrum.

Response Response Status U

REJECT.

No consensus to make a change.

The CRG expressed interest in contributions related to laser frequency noise.

Contributions are encouraged.

CI 156 SC 156.9.6 P 105 L 9 # 28

Dawe, Piers

Nvidia

Comment Type TR Comment Status R

D2.1 comments 285, optical parameters are inadequately defined, and 286, define frequency noise and write down how it may be measured. The laser frequency noise is supposed to be controlled down to less than 100 Hz. That's too vague for a spec. No indication is given of how it might be measured, but instruments that can measure GHz often don't measure kHz and below.

SuggestedRemedy

Either don't say anything about frequencies lower than the spec range, or use a separate recommendation (not expected to be testable). Review whether 100 Hz is feasible or necessary, change the limit if appropriate.

Response Response Status U

REJECT.

No consensus to make a change.

The CRG expressed interest in contributions related to laser frequency noise.

Contributions are encouraged.

IEEE P802.3cw D2.3 400 Gb/s over DWDM systems 3rd Working Group recirculation ballot comments

CI 156 SC 156.9.6 P 105 L 21 # 30

Dawe, Piers Nvidia

Comment Type TR Comment Status R

D2.1 comments 285, optical parameters are inadequately defined, and 286, define frequency noise and write down how it may be measured. This says "One-sided frequency noise power spectral density (Hz²/Hz)". I can see that a spectral density can be per hertz. Power has dimensions of energy per time, while Hz² is time⁻². These are incompatible.

SuggestedRemedy

If the units are not changed, delete "power" in the table row header and caption, and Figure 156-7, both y axis and caption.

Response Response Status U

REJECT.

No consensus to make a change.

The CRG expressed interest in contributions related to laser frequency noise.

Contributions are encouraged.

CI 156 SC 156.9.1 P 102 L 45 # 31

Dawe, Piers Nvidia

Comment Type TR Comment Status R

D2.1 comments 285, optical parameters are inadequately defined, and 286, define frequency noise. The header for this column is "Parameter" but "Laser frequency noise mask" is not an observable property of a signal, not even hypothetically. It's a mask, a property of the spec.

SuggestedRemedy

Change "Laser frequency noise mask" here, in Table 156-7 and in the title of 156.9.6. In 156.9.6, start by saying what frequency noise is before discussing the mask.

Response Response Status U

REJECT.

No consensus to make a change.

The CRG expressed interest in contributions related to laser frequency noise.

Contributions are encouraged.

CI 156 SC 156.9.6 P 105 L 8 # 36

Dawe, Piers Nvidia

Comment Type TR Comment Status R

D2.1 comments 285, optical parameters are inadequately defined, and 286, define frequency noise. The method of interpolation for the laser frequency noise mask is not specified. Figure 156-7 implies log-log interpolation but that is illustrative not normative.

SuggestedRemedy

State that log-log interpolation is used to build the mask is not specified.

Response Response Status U

REJECT.

No consensus to make a change.

The CRG expressed interest in contributions related to laser frequency noise.

Contributions are encouraged.

CI 156 SC 156.9.6 P 105 L 15 # 37

Dawe, Piers Nvidia

Comment Type TR Comment Status R

D2.1 comments 285, optical parameters are inadequately defined, and 286, define frequency noise. This says "The definition of maximum laser linewidth is provided in ITU-T G.698.2." G.698.2, 7.2.8 Maximum laser linewidth, says "The laser linewidth is defined as: The level of the white noise component of the power spectrum density of the instantaneous laser frequency multiplied by pi." We need a definition of linewidth, not maximum laser linewidth. A power spectrum density would be in the dimensions of power per frequency, which is not inverse time, so this definition is not satisfactory as it stands.

SuggestedRemedy

Use another reference with a dimensionally correct definition, or write one for laser linewidth (not "maximum laser linewidth" here).

Response Response Status U

REJECT.

No consensus to make a change.

The CRG expressed interest in contributions related to laser frequency noise.

Contributions are encouraged.

IEEE P802.3cw D2.3 400 Gb/s over DWDM systems 3rd Working Group recirculation ballot comments

CI 155 SC 155.2.5.11 P 54 L 30 # 38

Dawe, Piers Nvidia

Comment Type TR Comment Status R

D2.0 comment 463: generic operation ... in ITU-T G.709.3 Annex D: but that contains undefined symbols and terms. As it seems it is not very long, write it out cleanly here This is supposed to be a spec, we need a specific definition, not "generic". G.709.3 Annex D describes GMP (as referenced in 155.2.5.3), not the Hamming SD-FEC scheme. Also, G.709.3 is in revision. 400ZR 10.5, Inner Hamming Code, which is about one page long, specifically addresses a systematic (128, 119) double-extended Hamming code.

SuggestedRemedy

Copy the material from 400ZR 10.5, changing some of the b to m if appropriate to match the usual FEC notation in 802.3, and replacing the undefined symbols that look like ^ and V with the ones usually used in 802.3. Whatever symbols are used, say what they mean.

Response Response Status U

REJECT.

As noted by commentor, this issue was previously raised in D2.0 comment #463 which was rejected with the response "No consensus to make a change."

https://www.ieee802.org/3/cw/comments/D2p0/8023cw_D2p0_comments_final_by_ID.pdf.

ITU G.709.3 has been amended in November 2022, but there were no changes to Annex D.

CI 156 SC 156.7 P 84 L 22 # 20334

Ghiasi, Ali Ghiasi Quantum/Marvell

Comment Type TR Comment Status R

The receiver must tolerate 26 dB OSNR and meet the required error rate, it is not clear what receive OSNR (min) of 29 dB provides

SuggestedRemedy

Need discussions on the intent

Response Response Status U

REJECT.

Receiver OSNR tolerance is measured without line impairments, see 156.9.24, which is different than Receiver OSNR which includes line impairments, see 156.9.23

CI 156 SC 156.10.1.1 P 93 L 44 # 20336

Ghiasi, Ali Ghiasi Quantum/Marvell

Comment Type TR Comment Status R

Assuming just 4 bits ENOB from 10 MHz to 29.9 MHz the reference receiver will have additional penalty than real receiver that has typically 6+ bits ENOB at low frequencies and about 4 bits at high frequency

SuggestedRemedy

If there is interest I can bring a frequency dependent ENOB mask

Response Response Status U

REJECT.

No suggested remedy provided

CI 156 SC 156.7.1 P 82 L 48 # 20337

Ghiasi, Ali Ghiasi Quantum/Marvell

Comment Type TR Comment Status R

For full interoperability using EVM may need additional constrains based on the data in rahn_3cw_01a_220223 and way_3cw_01a_220523

SuggestedRemedy

Need more data to prove that EVM will provide the IEEE level of interoperability

Response Response Status U

REJECT.

No suggested remedy provided

IEEE P802.3cw D2.3 400 Gb/s over DWDM systems 3rd Working Group recirculation ballot comments

Cl 155 SC 155.3.1.3 P 51 L 26 # 20345

Zimmerman, George CME Consulting/APL Group, Cisco, Commscope, Ma

Comment Type TR Comment Status A rewrite bucket

This figure is supposed to be a functional block diagram, not an implementation diagram. There are no characteristics for the DAC blocks defined in the specification. The closest thing in the text is 155.3.3.4 which are called the 16QAM encode and signal drivers. However, most other 802.3 PHY clauses leave out signal drivers, DACs and the like, and there are no specific requirements in 155.3.3.4, so deleting the blocks seems the right approach to making a functional block diagram.

SuggestedRemedy

Preferably, delete the "DAC" blocks from Figure 155-10 (going straight to the output is fine) Alternatively, Relabel "16QAM Encoder and Signal Driver" (probably drawing as 2 blocks since you show I&Q paths)

Response Response Status U

ACCEPT IN PRINCIPLE.

See response to comment #346.

Cl 116 SC 116.1.3 P 27 L 22 # 20419

Dawe, Piers Nvidia

Comment Type TR Comment Status R

The manipulations described in this draft don't describe a BASE-R "native Ethernet"; rather, they are like 10GBASE-W. An Ethernet signal is packed into a telecoms wrapper (then, based on SONET, here, based on OTN). The combination is clumsy and messy. Starting from Ethernet building blocks, one would not engineer it like this. I understand that the rationale is because those designs were already there, and the cost of a clean design was thought to outweigh the inefficiencies of this scheme. But that calls "broad market potential" into question. 800G coherent will affect the market for this.

SuggestedRemedy

I can think of three options:

Redo Clause 155, leaving out GMP and FAW and simplifying the training sequence and pilot sequence to make an Ethernet PHY;

Cancel this project, and encourage those interested to feed their learnings into OIF's "400ZR" maintenance;

Rename this PHY to 400GBASE-ZW, which is more honest and leaves the "400GBASE-ZR" name available to any future native Ethernet PHY, should the broad market potential be found.

Response Response Status U

REJECT.

No consensus within the CRG to change the name of the 400GBASE-ZR PHY

IEEE P802.3cw D2.3 400 Gb/s over DWDM systems 3rd Working Group recirculation ballot comments

Cl 155 SC 155.1.5 P 35 L 1 # 20427

Dawe, Piers Nvidia

Comment Type TR Comment Status R

This PCS is too complicated for just a "directive" specification. We need examples.

SuggestedRemedy

Create examples of e.g. FEC and other blocks before and after coding. Smallish ones can go in the document, all can be uploaded to the directory that IEEE provides for these things. They might need to cover some of the PMA.

Response Response Status U

REJECT.

A detailed suggested remedy containing an editor's instruction on how to modify the draft was not provided.

The following straw poll was taken:

I would support rejecting comment #427
Yes - 10

N- 2

Cl 155 SC 155.2.4.11 P 44 L 36 # 20463

Dawe, Piers Nvidia

Comment Type TR Comment Status R

generic operation ... in ITU-T G.709.3 Annex D: but that contains undefined symbols and terms.

SuggestedRemedy

As it seems it is not very long, write it out cleanly here

Response Response Status U

REJECT.

No consensus to make a change.

Cl 156 SC 156.10.1.2.2 P 94 L 36 # 20564

Dawe, Piers Nvidia

Comment Type TR Comment Status R

Need a bigger block size for at least one of these, to go with the jitter corner frequency

SuggestedRemedy

Response Response Status U

REJECT.

The CRG had no consensus to make a change at this, more study on a suitable solution is required.

Cl 156 SC 156.9.27 P 103 L 48 # 21145

Dudek, Mike Marvell

Comment Type TR Comment Status A

The maximum ripple is specified as 2.5dB in table 156-8 but it is stated as being between 3dB points so with that definitions it must be at least 3dB.

SuggestedRemedy

Clarify the definition. Maybe it should be measured over a narrower wavelength range or maybe relative to a specific mask.

Response Response Status U

ACCEPT IN PRINCIPLE.

In 156.9.27 change "The ripple is the maximum peak-to-peak insertion loss variation between 3 dB points in the channel passband."

to

"The ripple is the maximum peak-to-peak insertion loss variation measured between the +/- 3 dB frequency points as defined by the maximum spectral excursion mask."

IEEE P802.3cw D2.3 400 Gb/s over DWDM systems 3rd Working Group recirculation ballot comments

Cl 155 SC 155 P 39 L 1 # 21278

Dawe, Piers Nvidia

Comment Type TR Comment Status R

This PCS/PMA is over-complicated and messy. We would not engineer it like this now (see nicholl_3dj_optx_01_230413 for a small step in the right direction, and maniloff_3dj_01a_2303 for an example of how to do coherent cleanly). OIF's so-called "400ZR" has had a draft since 2018, was issued in 2020 and revised last year. 800G coherent is coming in OIF and P802.3dj, which will take much of the market away. This P802.3cw project is on about its ninth draft and still the actual specifications are vague and incomplete, the previous draft was issued 8 months ago; not the usual two-monthly cadence we expect from an active project and an enthusiastic group. The moment for doing this spec in 802.3 has passed, it doesn't add significantly to 400ZR, and I observe there are not enough active participants in P802.3cw to justify it.

SuggestedRemedy

Cancel this project.
Encourage those interested to feed their learnings into OIF's "400ZR" maintenance.
Re-use relevant parts of the draft in P802.3dj when the time comes.

Response Response Status U

REJECT.

In the D2.0 review, 582 comments from 22 commentors were received which shows continued interest in the project.

In the D2.1 review, 290 comments from 13 commentors were received which shows continued interest in the project.

No consensus to cancel the project at this time.

Cl 116 SC 116.1.3 P 33 L 12 # 21280

Dawe, Piers Nvidia

Comment Type TR Comment Status R

As is made clear by the non-BASE-R Table 116-5a and 116.4.3 and 116.4.4, "400GBASE-ZR" is not BASE-R. However, the "R" in the name implies that it is, which causes confusion. Clause 155 describes a "WAN PHY" like 10GBASE-W: an Ethernet signal is carried in a telecoms wrapper (then, based on SONET, here, based on OTN). Also, misnaming this spec blocks the way for a future native BASE-R 400G Z class PHY. The name "400GBASE-ZW", while correct, doesn't flow very easily, but "400GBASE-Z" avoids the misrepresentation and provides a cleaner name.

SuggestedRemedy

Change "400GBASE-ZR" to "400GBASE-Z" throughout.

Response Response Status U

REJECT.

Changing the name from 400GBASE-ZR was previously considered in D2.0 comment #419 (https://www.ieee802.org/3/cw/comments/D2p0/8023cw_D2p0_comments_final_by_clause.pdf) and there was no consensus to make a change.

The comment does not provide sufficient justification to support the suggested remedy.

There was no consensus to make a change.

Cl 155 SC 155 P 39 L 1 # 21281

Dawe, Piers Nvidia

Comment Type TR Comment Status R

This PCS/PMA is way too complicated for just a "directive" specification, and much more complicated than the mainstream 256/257/RS-FEC. We need examples, as in Annex 91A, RS-FEC codeword examples, or Annex 76A, FEC Encoding example. If no-one is willing to provide them, we don't have a quorum to complete the project.

SuggestedRemedy

Create examples of e.g. FEC and other blocks before and after coding. Smallish ones can go in the document, all can be uploaded to the directory that IEEE provides for these things.
Alternatively, cancel the project.

Response Response Status U

REJECT.

No data was provided for the editors to be able to implement this change. Contributions of such material would be welcomed.

Regarding the project cancel proposal see response to comment #278.

IEEE P802.3cw D2.3 400 Gb/s over DWDM systems 3rd Working Group recirculation ballot comments

CI 156 SC 156.8 P 96 L 33 # 21284

Dawe, Piers Nvidia
 Comment Type **TR** Comment Status **A** Adjacent channel isolation

It is hard to grasp what this table is meant to say.

SuggestedRemedy

Provide a graph to illustrate it. Define the terms "frequency offset" and "isolation".

Response Response Status **U**

ACCEPT IN PRINCIPLE.

Resolve using the response to comment #251.

Straw poll #1:

Do you support the addition of a graph as part of the resolution to this comment to further define adjacent channel isolation.

Yes: 5
 No: 6

No consensus to add the graph to the draft.

CI 156 SC 156.9 P 97 L 12 # 21285

Dawe, Piers Nvidia
 Comment Type **TR** Comment Status **R**

Multiple optical parameters are inadequately defined; some (or more) measurement methods are needed for some of them

SuggestedRemedy

Complete the definitions of the optical parameters, with measurement methods and references as necessary

Response Response Status **U**

REJECT.

Comment unclear and no suggested remedy provided.

CI 156 SC 156.9.6 P 99 L 34 # 21286

Dawe, Piers Nvidia
 Comment Type **TR** Comment Status **R**

"Frequency noise" is extremely arcane, and not defined here. Phase noise is much more commonplace (but ambiguous, so that would need definition too). Also, it is not clear how the "frequency noise" is to be measured if the transmitter is transmitting Pattern 5; there needs to be a method that can tell unwanted "frequency noise" from the intended modulation.

SuggestedRemedy

If there is a well-known metric that does the job, use that instead. Either way, define the parameter with the relevant text, equation(s) and/or references, and write down how it may be measured.

Response Response Status **U**

REJECT.

No suitable definitions were found and a contribution to recommend a definition would be welcome.

No consensus to make a change at this time.