

P802.3dj COM Parameter Value Proposal – AUI C2M

Kent Lusted, Intel Corporation

Comment #72

Reference EQ Focus Points

- Setting reference EQ parameter values is important to determine many aspects of the specification
- A wide range of COM parameter values were used for analysis
- We propose to focus on several key COM parameters first:
 - # of pre/post RXFFE taps and type (fixed vs. floating)
 - Eta_0
- Other COM parameters and values can be determined later

Parameter Values in Recent Contributions

Contribution	RXFFE (pre/pst)	Eta_0
Ghiasi_3dj_01_2405	Pre: 6 Pst: 18 fixed	1.25E-8
Kareti_3dj_01_2405	Pre: 6 Pst: (A) 8 fixed (B) 4 fixed + 1x4 floating	4.2E-9, 6E-9, 8E-9
Lit_3dj_02_2405	Pre: 5 Pst: (A) 20 fixed (B) 8 fixed + 1x4 floating	1.25E-8

Proposal – AUI C2M

- For 200G/lane AUI C2M, set:
 - $\text{Eta}_0 = \text{TBD}$
 - # RXFFE taps
 - Number of pre-cursor taps (d_w) = TBD
 - Number of fixed-position taps (N_{fix}) = TBD
 - Number of floating tap groups (N_g) = TBD
 - Number of taps per floating tap group (N_f) = TBD
 - Highest allowed tap index (N_{max}) = TBD

Summary

- Setting reference EQ parameter values is important to determine many aspects of the specification
- These values are a BIG initial step to the closing of hundreds of TBDs in the electrical portions of the specification
- More work to do!

Backup