



WILDER
TECHNOLOGIES

It's all about integrity

224G C2M MTF Measured Data

Steve Sekel, Ray Schmelzer - Wilder Technologies

References

- Considerations for CR Insertion Loss Budget Baseline: Cable Assemblies and Test Fixtures (diminico_3dj_01_2311)
- Considerations of Technical Feasibility for Mated Compliance Fixtures (kocsis_3dj_01_2311)
- Proposed specification for 224G C2M Compliance Test Board Insertion Loss (sekel_3dj_01_2406)

Intent

- Present additional measurement data from prototype 224G C2M compliance test fixtures
- Demonstrate feasibility to fabricate compliance test fixtures to recommended specifications and validate with measured data.
- Prototypes developed agnostic to form factor. Both QSFP-DD and OSFP prototypes were fabricated and tested

Prototype Construction and Measurement



HCB and MCB loss reference boards were created and measured including all transmission lines up to, but excluding connector, connector pads, and vias in pads.

HCB, MCB and MTF IL @ 53.125 GHZ



Component	Insertion Loss (dB)
Module Compliance Board transmission line	2.7
Host Compliance Board transmission line	3.8
Mated Test Fixture	9.4
MTF connector + 2 via's	2.9

Prototype Construction – OSFP

To minimize loss, HCB uses short paddle card PCB launched into coax cables




Prototype Construction – QSFP-DD



802.3dj Task Force

Prototype Measurement Results – MTF QSFP-DD



Blue: HCB (o.c. estimate)

Red: MCB w/ connector (o.c. estimate)

Green: MTF (actual thru, raw & smoothed)

Summary and Conclusion

- Measured data shows good correlation with insertion loss simulation results for HCB, MCB, and MTF.