

IEEE 802.3 Ethernet Working Group
DRAFT Liaison Communication

Source: IEEE 802.3 Working Group¹

To: Karl Bois Technical Committee chair, OIF
[REDACTED]

Kimberly Naughton Project Manager, OIF
[REDACTED]

CC: Alpesh Shah Secretary, IEEE-SA Standards Board
Secretary, IEEE-SA Board of Governors
[REDACTED]

James Gilb Chair, IEEE 802 LMSC
[REDACTED]

Adam Healey Vice-chair, IEEE 802.3 Ethernet Working Group
[REDACTED]

Jon Lewis Secretary, IEEE 802.3 Ethernet Working Group
[REDACTED]

John D'Ambrosia Chair, IEEE P802.3dj Task Force
[REDACTED]

Mark Nowell Vice Chair, IEEE P802.3dj Task Force
[REDACTED]

From: David Law Chair, IEEE 802.3 Ethernet Working Group
[REDACTED]

Subject: Liaison to OIF, P802.3dj Status Update, dated 19 September 2024

Approval: Agreed at IEEE 802.3 interim meeting, Hamburg, Germany, 19 September 2024

Dear Mr. Bois and members of the OIF,

We wish to provide you a status update regarding IEEE P802.3dj that might be of interest to your members. The IEEE P802.3dj project recently initiated the third Task Force review and is actively working towards a technically complete document. **The review opened on DATE_HERE** and we anticipate considering responses to received comments during the IEEE 802 November 2024 Plenary meeting.

Recently, there were changes to the electrical interfaces that may be of interest to OIF for the CEI-224G specifications. **Specifically, we want to call your attention to the Channel Operating Margin (COM) parameter values for the copper cable and backplane PHYs as well as the COM parameter values for the AUI C2C electrical interface.**

As noted in our prior communication, the IEEE P802.3dj Task Force has been evaluating different transmitter quality metric (TQM) approaches for the different coherent PHYs being

¹ This document solely represents the views of the IEEE 802.3 Working Group, and does not necessarily represent a position of the IEEE, the IEEE Standards Association, or IEEE 802.

developed as part of the project. Based on input from the ITU-T, the Task Force has adopted the following TQM calculation:

- $TQM = \Delta RSNR_{tx}$, Tx-only RSNR penalty (Renamed as "Extended TCC") in dB (normative with a maximum specification)

This TQM approach has been implemented in IEEE P802.3dj D1.2 for the project's different coherent PHYs. It will be subject to further refinement and development, as well as continued collaboration with the ITU-T. This implementation also includes the definition of a TQM reference receiver. This definition also provides guidance on the calibrated coherent detector front-end with the goal of improving measurement repeatability. Please refer to Sub-Clauses 185.9 and 187.9.

We have attached D1.2 for your reference.

For further information on the task force activities, please see https://www.ieee802.org/3/dj/public/24_09/index.html

We look forward to the continued collaboration between our two groups.

Sincerely,

David Law

Chair, IEEE 802.3 Ethernet Working Group