

# Proposal for the MTF ILdd Mask

Sam Kocsis, Amphenol (and Editor of Annex 179B)

March 2025

# Motivation

- Get rid of TBDs in D1P4, Annex 179B

## 179B.4.1 Mated test fixtures insertion loss

The insertion loss of the mated test fixtures shall meet Equation (179B-3) and Equation (179B-4).

$$ILdd(f) \leq ILdd_{MTFmax}(f) = \begin{cases} TBD & 0.01 \leq f < TBD \\ TBD & TBD \leq f \leq 67 \end{cases} \quad (179B-3)$$

$$ILdd(f) \geq ILdd_{MTFmin}(f) = TBD \quad (179B-4)$$

for  $0.01 \leq f \leq 67$

where

$ILdd(f)$	is the measured insertion loss in dB at frequency $f$
$ILdd_{MTFmax}(f)$	is the maximum mated test fixtures insertion loss in dB at frequency $f$
$ILdd_{MTFmin}(f)$	is the minimum mated test fixtures insertion loss in dB at frequency $f$
$f$	is the frequency in GHz

# Proposed Mated Test Fixture ILdd Mask

$$0.0061f^2 - 0.0613f^{1.5} + 0.2867f + 0.3799\sqrt{f} + 0.1564$$

$$0.0175f^{1.5} + 0.0918f + 0.5166\sqrt{f} - 0.0294$$

## 179B.4.1 Mated test fixtures insertion loss

The insertion loss of the mated test fixtures shall meet Equation (179B-3) and Equation (179B-4).

$$ILdd(f) \leq ILdd_{MTFmax}(f) = \begin{cases} TBD & 0.01 \leq f < 67 \\ \cancel{TBD} & \cancel{TBD} \leq f \leq 67 \end{cases} \quad (179B-3)$$

$$ILdd(f) \geq ILdd_{MTFmin}(f) = TBD \quad (179B-4)$$

for  $0.01 \leq f \leq 67$

where

- $ILdd(f)$  is the measured insertion loss in dB at frequency  $f$
- $ILdd_{MTFmax}(f)$  is the maximum mated test fixtures insertion loss in dB at frequency  $f$
- $ILdd_{MTFmin}(f)$  is the minimum mated test fixtures insertion loss in dB at frequency  $f$
- $f$  is the frequency in GHz

# Proposed Mated Test Fixture ILdd Mask

$$0.0061f^2 - 0.0613f^{1.5} + 0.2867f + 0.3799\sqrt{f} + 0.1564$$

$$0.0175f^{1.5} - 0.0918f + 0.5166\sqrt{f} - 0.0294$$

Note: sign change on second term of  $ILdd_{MTFmin}(f)$  equation (for 179B-4)

## 179B.4.1 Mated test fixtures insertion loss

The insertion loss of the mated test fixtures shall meet Equation (179B-3) and Equation (179B-4).

$$ILdd(f) \leq ILdd_{MTFmax}(f) = \begin{cases} TBD & 0.01 \leq f < 67 \\ ~~TBD \quad TBD \leq f \leq 67~~ \end{cases} \quad (179B-3)$$

$$ILdd(f) \geq ILdd_{MTFmin}(f) = TBD \quad (179B-4)$$

for  $0.01 \leq f \leq 67$

where

$ILdd(f)$	is the measured insertion loss in dB at frequency $f$
$ILdd_{MTFmax}(f)$	is the maximum mated test fixtures insertion loss in dB at frequency $f$
$ILdd_{MTFmin}(f)$	is the minimum mated test fixtures insertion loss in dB at frequency $f$
$f$	is the frequency in GHz